

Package ‘cansim’

May 10, 2022

Type Package

Title Accessing Statistics Canada Data Table and Vectors

Version 0.3.11

Maintainer Jens von Bergmann <jens@mountainmath.ca>

Description Searches for, accesses, and retrieves new-format and old-format Statistics Canada data tables, as well as individual vectors, as tidy data frames. This package deals with encoding issues, allows for bilingual English or French language data retrieval, and bundles convenience functions to make it easier to work with retrieved table data. Optional caching features are provided.

License MIT + file LICENSE

Encoding UTF-8

ByteCompile yes

NeedsCompilation no

LazyData true

Depends R (>= 2.10)

Imports digest (>= 0.1), dplyr (>= 0.7), httr (>= 1.0.0), jsonlite (>= 1.0), readr, rlang, xml2, rvest, stringr, purrr, tibble, utils, DBI, RSQLite

RoxygenNote 7.1.2

Suggests knitr, rmarkdown, scales, tidyr, ggplot2, dbplyr

URL <https://github.com/mountainMath/cansim>,
<https://mountainmath.github.io/cansim/>,
<https://www.statcan.gc.ca/>

BugReports <https://github.com/mountainMath/cansim/issues>

VignetteBuilder knitr

Language en-CA

Author Jens von Bergmann [cre],
Dmitry Shkolnik [aut]

Repository CRAN

Date/Publication 2022-05-10 05:30:09 UTC

R topics documented:

add_provincial_abbreviations	2
cansim_old_to_new	3
categories_for_level	4
collect_and_normalize	5
correspondence	6
disconnect_cansim_sqlite	6
get_cansim	7
get_cansim_changed_tables	8
get_cansim_code_set	9
get_cansim_column_categories	9
get_cansim_column_list	10
get_cansim_cube_metadata	11
get_cansim_data_for_table_coord_periods	12
get_cansim_key_release_schedule	13
get_cansim_ndm	13
get_cansim_sqlite	14
get_cansim_table_info	16
get_cansim_table_last_release_date	17
get_cansim_table_notes	17
get_cansim_table_overview	18
get_cansim_table_short_notes	19
get_cansim_table_subject	20
get_cansim_table_survey	21
get_cansim_table_url	22
get_cansim_vector	22
get_cansim_vector_for_latest_periods	24
get_cansim_vector_info	25
list_cansim_cubes	25
list_cansim_sqlite_cached_tables	26
list_cansim_tables	27
normalize_cansim_values	27
remove_cansim_sqlite_cached_table	29
search_cansim_cubes	29
search_cansim_tables	30
view_cansim_webpage	31
Index	33

add_provincial_abbreviations

Add provincial abbreviations as factor

Description

Add provincial abbreviations as factor

Usage

```
add_provincial_abbreviations(data)
```

Arguments

data A tibble as returned by `get_cansim` with provincial level data

Value

The input tibble with additional factor `GEO.abb` that contains language-specific provincial abbreviations

Examples

```
## Not run:  
df <- get_cansim("17-10-0005")  
df <- add_provincial_abbreviations(df)  
  
## End(Not run)
```

cansim_old_to_new	<i>Translate deprecated CANSIM table number into new NDM-format table catalogue number</i>
-------------------	--

Description

Returns NDM table catalogue equivalent given a standard old-format CANSIM table number

Usage

```
cansim_old_to_new(oldCansimTableNumber)
```

Arguments

oldCansimTableNumber
 deprecated style CANSIM table number (e.g. "427-0001")

Value

A character string with the new-format NDM table number

Examples

```
## Not run:  
cansim_old_to_new("026-0018")  
  
## End(Not run)
```

categories_for_level *Use metadata to extract categories for column of specific level*

Description

For tables with data with hierarchical categories, metadata containing hierarchy level descriptions is used to extract categories at a specified level of hierarchy only.

Usage

```
categories_for_level(  
  data,  
  column_name,  
  level = NA,  
  strict = FALSE,  
  remove_duplicates = TRUE  
)
```

Arguments

data	data table object as returned from <code>get_cansim()</code>
column_name	the quoted name of the column to extract categories from
level	the hierarchy level depth to which to extract categories, where 0 is top category
strict	(default FALSE) when TRUE will only extract that specific hierarchy level
remove_duplicates	(default TRUE) When set to TRUE higher level grouping categories already captured by lower level hierarchy data will be removed

Value

A vector of categories

Examples

```
## Not run:  
data <- get_cansim("16-10-0117")  
categories_for_level(data, "North American Industry Classification System (NAICS)", level=2)  
  
## End(Not run)
```

collect_and_normalize *Collect data from connection and normalize cansim table output*

Description

Collect data from connection and normalize cansim table output

Usage

```
collect_and_normalize(  
  connection,  
  replacement_value = "val_norm",  
  normalize_percent = TRUE,  
  default_month = "07",  
  default_day = "01",  
  factors = FALSE,  
  strip_classification_code = FALSE,  
  disconnect = FALSE  
)
```

Arguments

connection	A connection to a local StatCan table SQLite database as returned by <code>get_cansim_sqlite</code> , possibly with filters or other <code>dbplyr</code> verbs applied
replacement_value	(Optional) the name of the column the manipulated value should be returned in. Defaults to adding the 'val_norm' value field.
normalize_percent	(Optional) When true (the default) normalizes percentages by changing them to rates
default_month	The default month that should be used when creating Date objects for annual data (default set to "07")
default_day	The default day of the month that should be used when creating Date objects for monthly data (default set to "01")
factors	(Optional) Logical value indicating if dimensions should be converted to factors. (Default set to FALSE).
strip_classification_code	(Optional) Logical value indicating if classification code should be stripped from names. (Default set to false).
disconnect	(Optional) Logical value to indicate if the database connection should be disconnected. (Default is FALSE)

Value

A tibble with the collected and normalized data

Examples

```
## Not run:
library(dplyr)

con <- get_cansim_sqlite("34-10-0013")
data <- con %>%
  filter(GEO=="Ontario") %>%
  collect_and_normalize()

disconnect_cansim_sqlite(con)

## End(Not run)
```

correspondence	<i>The correspondence file for old to new StatCan table numbers is included in the package</i>
----------------	--

Description

The correspondence file for old to new StatCan table numbers is included in the package

Author(s)

Statistics Canada

References

https://www.statcan.gc.ca/eng/developers-developpeurs/cansim_id-product_id-concordance.csv

disconnect_cansim_sqlite	<i>Disconnect from a cansim database connection</i>
--------------------------	---

Description

Disconnect from a cansim database connection

Usage

```
disconnect_cansim_sqlite(connection)
```

Arguments

connection	connection to database
------------	------------------------

Value

‘NULL‘

Examples

```
## Not run:
con <- get_cansim_sqlite("34-10-0013")
disconnect_cansim_sqlite(con)

## End(Not run)
```

get_cansim

Retrieve a Statistics Canada data table using NDM catalogue number

Description

Retrieves a data table using an NDM catalogue number as a tidy data frame. Retrieved table data is cached for the duration of the current R session only by default.

Usage

```
get_cansim(
  cansimTableNumber,
  language = "english",
  refresh = FALSE,
  timeout = 200,
  factors = TRUE,
  default_month = "07",
  default_day = "01"
)
```

Arguments

cansimTableNumber	the NDM table number to load
language	"en" or "english" for English and "fr" or "french" for French language versions (defaults to English)
refresh	(Optional) When set to TRUE, forces a reload of data table (default is FALSE)
timeout	(Optional) Timeout in seconds for downloading cansim table to work around scenarios where StatCan servers drop the network connection.
factors	(Optional) Logical value indicating if dimensions should be converted to factors. (Default set to TRUE).
default_month	The default month that should be used when creating Date objects for annual data (default set to "07")
default_day	The default day of the month that should be used when creating Date objects for monthly data (default set to "01") Set to higher values for large tables and slow network connection. (Default is 200).

Value

A tibble with StatCan Table data and added Date column with inferred date objects and added val_norm column with normalized value from the VALUE column.

Examples

```
## Not run:  
get_cansim("34-10-0013")  
  
## End(Not run)
```

get_cansim_changed_tables

Retrieve a list of modified tables since a given date

Description

Retrieve a list of tables that have been modified or updated since the specified date.

Usage

```
get_cansim_changed_tables(start_date, end_date = NULL)
```

Arguments

start_date	Starting date in YYYY-MM-DD format to look for changes that changed on or after that date
end_date	Optional end date in YYYY-MM-DD format to look for changes that changed on or before that date, default is same as start date

Value

A tibble with Statistics Canada data table product ids and their release times

Examples

```
## Not run:  
get_cansim_changed_tables("2018-08-01")  
  
## End(Not run)
```

get_cansim_code_set *Get NDM code sets*

Description

Useful to get a list of surveys or subjects and used internally

Usage

```
get_cansim_code_set(  
  code_set = c("scalar", "frequency", "symbol", "status", "uom", "survey", "subject",  
              "wdsResponseStatus"),  
  refresh = FALSE  
)
```

Arguments

code_set	the code set to retrieve.
refresh	Default is FALSE, repeated calls during the same session will hit the cached data. To refresh the code list during a running R session set to TRUE

Value

A tibble with english and french labels for the given code set

Examples

```
## Not run:  
get_cansim_code_set("survey")  
  
## End(Not run)
```

get_cansim_column_categories
Retrieve Statistics Canada data table categories for a specific column

Description

Returns table column details given an NDM table number in English or French. Retrieved table information data is cached for the duration of the R session only.

Usage

```
get_cansim_column_categories(
  cansimTableNumber,
  column,
  language = "english",
  refresh = FALSE,
  timeout = 200
)
```

Arguments

cansimTableNumber	the NDM table number to load
column	the specified column for which to retrieve category information for
language	"en" or "english" for English and "fr" or "french" for French language versions (default set to English)
refresh	(Optional) When set to TRUE, forces a reload of data table (default is FALSE)
timeout	(Optional) Timeout in seconds for downloading cansim table to work around scenarios where StatCan servers drop the network connection.

Value

A tibble with detailed information on StatCan table categories for the specified field

Examples

```
## Not run:
get_cansim_column_categories("34-10-0013", "Geography")

## End(Not run)
```

```
get_cansim_column_list
```

Retrieve Statistics Canada data table column list

Description

Returns table column details given an NDM table number in English or French. Retrieved table information data is cached for the duration of the R session only.

Usage

```
get_cansim_column_list(
  cansimTableNumber,
  language = "english",
  refresh = FALSE,
  timeout = 200
)
```

Arguments

cansimTableNumber	the NDM table number to load
language	"en" or "english" for English and "fr" or "french" for French language versions (default set to English)
refresh	(Optional) When set to TRUE, forces a reload of data table (default is FALSE)
timeout	(Optional) Timeout in seconds for downloading cansim table to work around scenarios where StatCan servers drop the network connection.

Value

A tibble listing the column names of the StatCan table.

Examples

```
## Not run:
get_cansim_column_list("34-10-0013")

## End(Not run)
```

```
get_cansim_cube_metadata
```

Retrieve table metadata from Statistics Canada API

Description

Retrieves table metadata given an input table number or vector of table numbers using either the new or old table number format. Patience is suggested as the Statistics Canada API can be very slow. The 'list_cansim_tables()' function can be used as an alternative to retrieve a (cached) list of CANSIM tables with (more limited) metadata.

Usage

```
get_cansim_cube_metadata(cansimTableNumber)
```

Arguments

cansimTableNumber	A new or old CANSIM/NDM table number or a vector of table numbers
-------------------	---

Value

a tibble containing the table metadata

Examples

```
## Not run:
get_cansim_cube_metadata("34-10-0013")

## End(Not run)
```

```
get_cansim_data_for_table_coord_periods
```

Retrieve data for specified Statistics Canada data product for last N periods for specific coordinates

Description

Allows for the retrieval of data for a Statistics Canada data table with specific coordinates for the N most-recently released periods. Caution: coordinates are concatenations of table member ID values and require familiarity with the TableMetadata data structure. Coordinates have a maximum of ten dimensions.

Usage

```
get_cansim_data_for_table_coord_periods(
  cansimTableNumber,
  coordinate,
  periods = 1,
  refresh = FALSE,
  timeout = 200,
  factors = TRUE,
  default_month = "07",
  default_day = "01"
)
```

Arguments

cansimTableNumber	Statistics Canada data table number
coordinate	A string of table coordinates in the form "1.1.1.36.1.0.0.0.0.0"
periods	Numeric value for number of latest periods to retrieve data for
refresh	(Optional) When set to TRUE, forces a reload of data table (default is FALSE)
timeout	(Optional) Timeout in seconds for downloading cansim table to work around scenarios where StatCan servers drop the network connection.
factors	(Optional) Logical value indicating if dimensions should be converted to factors. (Default set to TRUE).
default_month	The default month that should be used when creating Date objects for annual data (default set to "07")
default_day	The default day of the month that should be used when creating Date objects for monthly data (default set to "01")

Value

A tibble with data matching specified coordinate and period input arguments

Examples

```
## Not run:
get_cansim_data_for_table_coord_periods("35-10-0003", coordinate="1.12.0.0.0.0.0.0", periods=3)

## End(Not run)
```

```
get_cansim_key_release_schedule
```

Major economic indicator release schedule

Description

Returns every release date of major economic indicators since March 14, 2012. This also includes scheduled future releases.

Usage

```
get_cansim_key_release_schedule()
```

Value

a tibble with data, and details for major economic indicator release

Examples

```
## Not run:
get_cansim_key_release_schedule()

## End(Not run)
```

```
get_cansim_ndm
```

Retrieves a Statistics Canada data table using CANSIM code or NDM table number

Description

Retrieves a data table as a tidy dataframe using either an old-style CANSIM code or a new-format NDM table number. This function will automatically convert old-style CANSIM codes into their new equivalents. Retrieved table data is cached for the duration of the current R session only by default.

Usage

```
get_cansim_ndm(
  cansimTableNumber,
  language = "english",
  refresh = FALSE,
  timeout = 200
)
```

Arguments

cansimTableNumber	the table number to load, accepts old CANSIM or new NDM table numbers
language	"en" or "english" for English and "fr" or "french" for French language versions (default is set to English)
refresh	(Optional) When set to TRUE, forces a reload of data table (default is FALSE)
timeout	(Optional) Timeout in seconds for downloading cansim table to work around scenarios where StatCan servers drop the network connection.

Details

Deprecated, use 'get_cansim' instead. This will be removed in future releases.

Value

A tibble with the StatCan table data

Examples

```
## Not run:
# Retrieve a table with an NDM code
get_cansim("34-10-0013")
# Retrieve a table with an old-style CANSIM code
get_cansim("026-0018")

## End(Not run)
```

get_cansim_sqlite	<i>Retrieve a Statistics Canada data table using NDM catalogue number as SQLite database connection</i>
-------------------	---

Description

Retrieves a data table using an NDM catalogue number as an SQLite table. Retrieved table data is cached permanently if a cache path is supplied or for duration of the current R session. The function will check against the latest release data for the table and emit a warning message if the cached table is out of date.

Usage

```
get_cansim_sqlite(  
  cansimTableNumber,  
  language = "english",  
  refresh = FALSE,  
  auto_refresh = FALSE,  
  timeout = 1000,  
  cache_path = getOption("cansim.cache_path")  
)
```

Arguments

cansimTableNumber	the NDM table number to load
language	"en" or "english" for English and "fr" or "french" for French language versions (defaults to English)
refresh	(Optional) When set to TRUE, forces a reload of data table (default is FALSE)
auto_refresh	(Optional) When set to TRUE, it will reload of data table if a new version is available (default is FALSE)
timeout	(Optional) Timeout in seconds for downloading cansim table to work around scenarios where StatCan servers drop the network connection.
cache_path	(Optional) Path to where to cache the table permanently. By default, the data is cached in the path specified by 'getOption("cansim.cache_path")', if this is set. Otherwise it will use 'tempdir()'.

Value

A database connection to a local SQLite database with the StatCan Table data.

Examples

```
## Not run:  
con <- get_cansim_sqlite("34-10-0013")  
  
# Work with the data connection  
head(con)  
  
disconnect_cansim_sqlite(con)  
  
## End(Not run)
```

get_cansim_table_info *Retrieve Statistics Canada data table information*

Description

Returns table information given an NDM table catalogue number in English or French. Retrieved table information data is cached for the duration of the R session only.

Usage

```
get_cansim_table_info(  
  cansimTableNumber,  
  language = "english",  
  refresh = FALSE,  
  timeout = 200  
)
```

Arguments

cansimTableNumber	the NDM table number to load
language	"en" or "english" for English and "fr" or "french" for French language versions (default set to English)
refresh	(Optional) When set to TRUE, forces a reload of data table (default is FALSE)
timeout	(Optional) Timeout in seconds for downloading cansim table to work around scenarios where StatCan servers drop the network connection.

Value

A tibble with the table overview information

Examples

```
## Not run:  
get_cansim_table_info("34-10-0013")  
  
## End(Not run)
```

`get_cansim_table_last_release_date`*Get the latest release data for a StatCan table, if available*

Description

This can be used to check when a table has last been updated.

Usage

```
get_cansim_table_last_release_date(cansimTableNumber)
```

Arguments

```
cansimTableNumber  
    the NDM table number
```

Value

A datetime object if a release data is available, NULL otherwise.

Examples

```
## Not run:  
get_cansim_table_last_release_date("34-10-0013")  
  
## End(Not run)
```

`get_cansim_table_notes`*Retrieve Statistics Canada data table notes and column categories*

Description

Returns table notes given an NDM table number in English or French. Retrieved table information data is cached for the duration of the R session only.

Usage

```
get_cansim_table_notes(  
  cansimTableNumber,  
  language = "en",  
  refresh = FALSE,  
  timeout = 200  
)
```

Arguments

cansimTableNumber	the NDM table number to load
language	"en" or "english" for English and "fr" or "french" for French language versions (default set to English)
refresh	(Optional) When set to TRUE, forces a reload of data table (default is FALSE)
timeout	(Optional) Timeout in seconds for downloading cansim table to work around scenarios where StatCan servers drop the network connection.

Value

A tibble with table notes.

Examples

```
## Not run:
get_cansim_table_notes("34-10-0013")

## End(Not run)
```

```
get_cansim_table_overview
```

Retrieve Statistics Canada data table overview text

Description

Prints table overview information as console output. In order to display table overview information, the selected CANSIM table must be loaded entirely to display overview information. Overview information is printed in console an in English or French, as specified.

Usage

```
get_cansim_table_overview(
  cansimTableNumber,
  language = "english",
  refresh = FALSE
)
```

Arguments

cansimTableNumber	the NDM table number to load
language	"en" or "english" for English and "fr" or "french" for French language versions (default set to English)
refresh	(Optional) When set to TRUE, forces a reload of data table (default is FALSE)

Value

none

Examples

```
## Not run:
get_cansim_table_overview("34-10-0013")

## End(Not run)
```

```
get_cansim_table_short_notes
```

Retrieve Statistics Canada data table short notes

Description

Returns table notes given an NDM table number in English or French. Retrieved table information data is cached for the duration of the R session only.

Usage

```
get_cansim_table_short_notes(
  cansimTableNumber,
  language = "english",
  refresh = FALSE,
  timeout = 200
)
```

Arguments

cansimTableNumber	the NDM table number to load
language	"en" or "english" for English and "fr" or "french" for French language versions (default set to English)
refresh	(Optional) When set to TRUE, forces a reload of data table (default is FALSE)
timeout	(Optional) Timeout in seconds for downloading cansim table to work around scenarios where StatCan servers drop the network connection.

Value

A tibble with the StatCan Notes for the table

Examples

```
## Not run:
get_cansim_table_short_notes("34-10-0013")

## End(Not run)
```

`get_cansim_table_subject`*Retrieve Statistics Canada data table subject detail*

Description

Returns table subject detail given an NDM table number in English or French. Retrieved table information data is cached for the duration of the R session only.

Usage

```
get_cansim_table_subject(  
  cansimTableNumber,  
  language = "english",  
  refresh = FALSE,  
  timeout = 200  
)
```

Arguments

<code>cansimTableNumber</code>	the NDM table number to load
<code>language</code>	"en" or "english" for English and "fr" or "french" for French language versions (default set to English)
<code>refresh</code>	(Optional) When set to TRUE, forces a reload of data table (default is FALSE)
<code>timeout</code>	(Optional) Timeout in seconds for downloading cansim table to work around scenarios where StatCan servers drop the network connection.

Value

A tibble with the table subject code and name.

Examples

```
## Not run:  
get_cansim_table_subject("34-10-0013")  
  
## End(Not run)
```

`get_cansim_table_survey`*Retrieve Statistics Canada data table survey detail*

Description

Returns table survey detail given an NDM table number in English or French. Retrieved table information data is cached for the duration of the R session only.

Usage

```
get_cansim_table_survey(  
  cansimTableNumber,  
  language = "english",  
  refresh = FALSE,  
  timeout = 200  
)
```

Arguments

<code>cansimTableNumber</code>	the NDM table number to load
<code>language</code>	"en" or "english" for English and "fr" or "french" for French language versions (default set to English)
<code>refresh</code>	(Optional) When set to TRUE, forces a reload of data table (default is FALSE)
<code>timeout</code>	(Optional) Timeout in seconds for downloading cansim table to work around scenarios where StatCan servers drop the network connection.

Value

A tibble with the table survey code and name

Examples

```
## Not run:  
get_cansim_table_survey("34-10-0013")  
  
## End(Not run)
```

`get_cansim_table_url` *Retrieve a Statistics Canada data table URL given a table number*

Description

Retrieve URL of a table from the API given a table number. Offers a more stable approach than manually guessing the URL of the table.

Usage

```
get_cansim_table_url(cansimTableNumber, language = "en")
```

Arguments

<code>cansimTableNumber</code>	the NDM table number to load
<code>language</code>	"en" or "english" for English and "fr" or "french" for French language versions (defaults to English)

Value

String object containing URL for specified table number

Examples

```
## Not run:
get_cansim_table_url("34-10-0013")
get_cansim_table_url("34-10-0013", language = "fr")

## End(Not run)
```

`get_cansim_vector` *Retrieve data for a Statistics Canada data vector released within a given time frame*

Description

Retrieve data for a Statistics Canada data vector released within a given time frame

Usage

```
get_cansim_vector(
  vectors,
  start_time = as.Date("1800-01-01"),
  end_time = Sys.time(),
  use_ref_date = TRUE,
  refresh = FALSE,
  timeout = 200,
  factors = TRUE,
  default_month = "07",
  default_day = "01"
)
```

Arguments

vectors	The list of vectors to retrieve
start_time	Starting date in YYYY-MM-DD format, applies to REF_DATE or releaseTime, depending on use_ref_date parameter
end_time	Set an optional end time filter in YYYY-MM-DD format (defaults to current system time)
use_ref_date	Optional, TRUE by default. When set to TRUE, uses REF_DATE of vector data to filter, otherwise it uses StatisticsCanada's releaseDate value for filtering the specified vectors.
refresh	(Optional) When set to TRUE, forces a reload of data table (default is FALSE)
timeout	(Optional) Timeout in seconds for downloading cansim table to work around scenarios where StatCan servers drop the network connection.
factors	(Optional) Logical value indicating if dimensions should be converted to factors. (Default set to TRUE).
default_month	The default month that should be used when creating Date objects for annual data (default set to "07")
default_day	The default day of the month that should be used when creating Date objects for monthly data (default set to "01")

Value

A tibble with data for vectors released between start and end time

Examples

```
## Not run:
get_cansim_vector("v41690973", "2015-01-01")

## End(Not run)
```

```
get_cansim_vector_for_latest_periods
```

Retrieve data for specified Statistics Canada data vector(s) for last N periods

Description

Allows for the retrieval of data for specified vector series for the N most-recently released periods.

Usage

```
get_cansim_vector_for_latest_periods(  
  vectors,  
  periods = 1,  
  refresh = FALSE,  
  timeout = 200,  
  factors = TRUE,  
  default_month = "07",  
  default_day = "01"  
)
```

Arguments

vectors	The list of vectors to retrieve
periods	Numeric value for number of latest periods to retrieve data for
refresh	(Optional) When set to TRUE, forces a reload of data table (default is FALSE)
timeout	(Optional) Timeout in seconds for downloading cansim table to work around scenarios where StatCan servers drop the network connection.
factors	(Optional) Logical value indicating if dimensions should be converted to factors. (Default set to TRUE).
default_month	The default month that should be used when creating Date objects for annual data (default set to "07")
default_day	The default day of the month that should be used when creating Date objects for monthly data (default set to "01")

Value

A tibble with data for specified vector(s) for the last N periods

Examples

```
## Not run:  
get_cansim_vector_for_latest_periods("v41690973", 10)  
  
## End(Not run)
```

`get_cansim_vector_info`*Retrieve metadata for specified Statistics Canada data vectors*

Description

Allows for the retrieval of metadata for Statistics Canada data vectors

Usage

```
get_cansim_vector_info(vectors)
```

Arguments

`vectors` a vector of cansim vectors

Value

A tibble with metadata for selected vectors

Examples

```
## Not run:  
get_cansim_vector_info("v41690973")  
  
## End(Not run)
```

`list_cansim_cubes`*Get overview list for all Statistics Canada data cubes*

Description

Generates an overview table containing metadata of available Statistics Canada data cubes.

Usage

```
list_cansim_cubes(lite = FALSE, refresh = FALSE)
```

Arguments

`lite` Get the version without cube dimensions and comments for faster retrieval, default is FALSE.

`refresh` Default is FALSE, repeated calls during the same session will hit the cached data. To refresh the code list during a running R session set to TRUE

Value

A tibble with available Statistics Canada data cubes, including NDM table number, cube title, start and end dates, achieve status, subject and survey codes, frequency codes and a list of cube dimensions.

Examples

```
## Not run:  
list_cansim_cubes()  
  
## End(Not run)
```

```
list_cansim_sqlite_cached_tables  
List cached cansim SQLite database
```

Description

List cached cansim SQLite database

Usage

```
list_cansim_sqlite_cached_tables(cache_path = getOption("cansim.cache_path"))
```

Arguments

cache_path Optional, default value is 'getOption("cansim.cache_path")'.

Value

A tibble with the list of all tables that are currently cached at the given cache path.

Examples

```
## Not run:  
list_cansim_sqlite_cached_tables()  
  
## End(Not run)
```

list_cansim_tables *Get overview list for all Statistics Canada data tables (deprecated)*

Description

This method is deprecated, please use 'list_cansim_cubes' instead. Generates an overview table containing metadata of available Statistics Canada data tables. A new and updated table will be generated if this table does not already exist in cached form or if the force refresh option is selected (set to FALSE by default). This can take some time as this process involves scraping through hundreds of Statistics Canada web pages to gather the required metadata. If option cansim.cache_path is set it will look for and store the overview table in that directory.

Usage

```
list_cansim_tables(refresh = FALSE)
```

Arguments

refresh Default is FALSE, and will regenerate the table if set to TRUE

Value

A tibble with available Statistics Canada data tables, listing title, Statistics Canada data table catalogue number, deprecated CANSIM table number, description, and geography

Examples

```
## Not run:  
list_cansim_tables()  
  
## End(Not run)
```

normalize_cansim_values
Normalize retrieved data table values to appropriate scales

Description

Facilitates working with Statistics Canada data table values retrieved using the package by setting all units to counts/dollars instead of millions, etc. If "replacement_value" is not set, it will replace the VALUE field with normalized values and drop the scale column. Otherwise it will keep the scale columns and create a new column named replacement_value with the normalized value. It will attempt to parse the REF_DATE field and create an R date variable. This is currently experimental.

Usage

```
normalize_cansim_values(
  data,
  replacement_value = NA,
  normalize_percent = TRUE,
  default_month = "01",
  default_day = "01",
  factors = FALSE,
  strip_classification_code = FALSE,
  cansimTableNumber = NULL
)
```

Arguments

data A retrieved data table as returned from `get_cansim()` or `get_cansim_ndm()`

replacement_value (Optional) the name of the column the manipulated value should be returned in. Defaults to replacing the current value field

normalize_percent (Optional) When true (the default) normalizes percentages by changing them to rates

default_month The default month that should be used when creating Date objects for annual data (default set to "01")

default_day The default day of the month that should be used when creating Date objects for monthly data (default set to "01")

factors (Optional) Logical value indicating if dimensions should be converted to factors. (Default set to false).

strip_classification_code (strip_classification_code) Logical value indicating if classification code should be stripped from names. (Default set to false).

cansimTableNumber (Optional) Only needed when operating on results of SQLite connections.

Value

Returns the input tibble with with adjusted values

Examples

```
## Not run:
cansim_table <- get_cansim("34-10-0013")
normalize_cansim_values(cansim_table)

## End(Not run)
```

```
remove_cansim_sqlite_cached_table
```

Remove cached cansim SQLite database

Description

Remove cached cansim SQLite database

Usage

```
remove_cansim_sqlite_cached_table(  
  cansimTableNumber,  
  language = NULL,  
  cache_path = getOption("cansim.cache_path")  
)
```

Arguments

cansimTableNumber	Number of the table to be removed
language	Language for which to remove the cached data. If unspecified ('NULL') tables for all languages will be removed
cache_path	Optional, default value is 'getOption("cansim.cache_path")'

Value

'NULL'

Examples

```
## Not run:  
con <- get_cansim_sqlite("34-10-0013")  
disconnect_cansim_sqlite(con)  
remove_cansim_sqlite_cached_table("34-10-0013")  
  
## End(Not run)
```

```
search_cansim_cubes
```

Search through Statistics Canada data cubes

Description

Searches through Statistics Canada data cubes using a search term.

Usage

```
search_cansim_cubes(search_term, refresh = FALSE)
```

Arguments

search_term	User-supplied search term used to find Statistics Canada data cubes with matching titles, table numbers, subject and survey codes.
refresh	Default is FALSE. The underlying cube list is cached for the duration of the R sessions and will regenerate the cube list if set to TRUE

Value

A tibble with available Statistics Canada data cubes, listing title, Statistics Canada data cube catalogue number, deprecated CANSIM table number, survey and subject.

Examples

```
## Not run:
search_cansim_cubes("Labour force")

## End(Not run)
```

search_cansim_tables *Search through Statistics Canada data tables (deprecated)*

Description

This method is deprecated, please use ‘search_cansim_cubes’ instead. Searches through Statistics Canada data tables using a search term. A new table is generated if it already does not exist or if refresh option is set to TRUE. Search-terms are case insensitive, but will accept regular expressions for more advanced searching. The search function can search either through table titles or through table descriptions, depending on the whether or not search_description is set to TRUE or not. If refresh = TRUE, the table will be updated and regenerated using Statistics Canada’s latest data. This can take some time since this process involves scraping through several hundred web pages to gather the required metadata. If option cache_path is set it will look for and store the overview table in that directory.

Usage

```
search_cansim_tables(search_term, search_fields = "both", refresh = FALSE)
```

Arguments

search_term	User-supplied search term used to find Statistics Canada data tables with matching titles
search_fields	By default, this function will search through table titles and keywords. Setting this parameter to "title" will only search through the title, setting it to "keyword" will only search through keywords
refresh	Default is FALSE, and will regenerate the table if set to TRUE

Value

A tibble with available Statistics Canada data tables, listing title, Statistics Canada data table catalogue number, deprecated CANSIM table number, description and geography that match the search term.

Examples

```
## Not run:
search_cansim_tables("Labour force")

## End(Not run)
```

view_cansim_webpage *View CANSIM table information in browser*

Description

Opens CANSIM table on Statistics Canada's website using default browser. This may be useful for getting further info on CANSIM table and survey methods.

Usage

```
view_cansim_webpage(cansimTableNumber = NULL)
```

Arguments

cansimTableNumber
CANSIM or NDM table number. If no number is provided, the vector search page on the Statistic Canada website will be opened.

Value

none

Examples

```
## Not run:  
view_cansim_webpage("34-10-0013")  
  
## End(Not run)
```


Index

- * **data**
 - correspondence, [6](#)
- [add_provincial_abbreviations, 2](#)
- [cansim_old_to_new, 3](#)
- [categories_for_level, 4](#)
- [collect_and_normalize, 5](#)
- [correspondence, 6](#)
- [disconnect_cansim_sqlite, 6](#)
- [get_cansim, 7](#)
- [get_cansim_changed_tables, 8](#)
- [get_cansim_code_set, 9](#)
- [get_cansim_column_categories, 9](#)
- [get_cansim_column_list, 10](#)
- [get_cansim_cube_metadata, 11](#)
- [get_cansim_data_for_table_coord_periods, 12](#)
- [get_cansim_key_release_schedule, 13](#)
- [get_cansim_ndm, 13](#)
- [get_cansim_sqlite, 14](#)
- [get_cansim_table_info, 16](#)
- [get_cansim_table_last_release_date, 17](#)
- [get_cansim_table_notes, 17](#)
- [get_cansim_table_overview, 18](#)
- [get_cansim_table_short_notes, 19](#)
- [get_cansim_table_subject, 20](#)
- [get_cansim_table_survey, 21](#)
- [get_cansim_table_url, 22](#)
- [get_cansim_vector, 22](#)
- [get_cansim_vector_for_latest_periods, 24](#)
- [get_cansim_vector_info, 25](#)
- [list_cansim_cubes, 25](#)
- [list_cansim_sqlite_cached_tables, 26](#)
- [list_cansim_tables, 27](#)
- [normalize_cansim_values, 27](#)
- [remove_cansim_sqlite_cached_table, 29](#)
- [search_cansim_cubes, 29](#)
- [search_cansim_tables, 30](#)
- [view_cansim_webpage, 31](#)