

Package ‘inti’

May 19, 2022

Type Package

Version 0.5.6

Title Tools and Statistical Procedures in Plant Science

Description The 'inti' package is part of the 'inkaverse' project for developing different procedures and tools used in plant science and experimental designs. The main aim of the package is to support researchers during the planning of experiments and data collection (`tarpu()`), data analysis and graphics (`yupana()`), and technical writing.

Learn more about the 'inkaverse' project at [<https://inkaverse.com/>](https://inkaverse.com/).

Date 2022-05-18

URL <https://inkaverse.com/>, <https://github.com/flavjack/inti>

BugReports <https://github.com/flavjack/inti/issues/>

Depends shiny, ggplot2, dplyr, tidyr, tibble, R (>= 2.10)

Imports lme4, agricolae, FactoMineR, emmeans, purrr, stringr, stringi,
DT

Suggests gsheets, knitr, rmarkdown, bookdown

VignetteBuilder knitr

License GPL-3 | file LICENSE

LazyData true

Encoding UTF-8

RoxygenNote 7.2.0

NeedsCompilation no

Author Flavio Lozano-Isla [aut, cre] (<https://orcid.org/0000-0002-0714-669X>),
QuipoLab [ctb],
Inkaverse [cph]

Maintainer Flavio Lozano-Isla <flavjack@gmail.com>

Repository CRAN

Date/Publication 2022-05-19 06:50:06 UTC

R topics documented:

colortext	2
figure2rmd	3
footnotes	4
gdoc2rmd	4
H2cal	5
include_figure	7
include_table	8
jc_tombola	9
mean_comparison	10
met	11
metamorphosis	12
outliers_remove	13
plot_diag	14
plot_raw	15
plot_smr	17
potato	19
split_folder	20
table2rmd	21
tarpuy	21
tarpuy_design	22
tarpuy_plex	23
tarpuy_plotdesign	25
tarpuy_varlist	26
web_table	27
yupana	28
yupana_analysis	29
yupana_export	30
yupana_import	32
yupana_mvr	33
yupana_reshape	34
Index	36

colortext

Colourise text for display in the terminal

Description

If R is not currently running in a system that supports terminal colours the text will be returned unchanged.

Usage

```
colortext(text, fg = "red", bg = NULL)
```

Arguments

text	character vector
fg	foreground colour, defaults to white
bg	background colour, defaults to transparent

Details

Allowed colours are: black, blue, brown, cyan, dark gray, green, light blue, light cyan, light gray, light green, light purple, light red, purple, red, white, yellow

Author(s)

testthat package

Examples

```
print(colortext("Red", "red"))
cat(colortext("Red", "red"), "\n")
cat(colortext("White on red", "white", "red"), "\n")
```

figure2rmd

Figure to Rmarkdown

Description

Use Articul8 Add-ons from Google docs to build Ricles

Usage

```
figure2rmd(text, path = ".", opts = NA, prefix = "Figure")
```

Arguments

text	String with the table information
path	Path of the image fot the figure
opts	chunk options in brackets.
prefix	Prefix for the name of the figure

Value

Mutated string

footnotes	<i>Footnotes in tables</i>
-----------	----------------------------

Description

Include tables footnotes and symbols for kables in pandoc format

Usage

```
footnotes(table, notes = NULL, label = "Note:", notation = "alphabet")
```

Arguments

table	Kable output in pandoc format.
notes	Footnotes for the table.
label	Label for start the footnote.
notation	Notation for the footnotes (default = "alphabet"). See details.

Details

You should use the pandoc format `kable(format = "pipe")`. You can add the footnote symbol using `{hyphen}` in your table. notation could be use: "alphabet", "number", "symbol", "none".

Value

Table with footnotes for word and html documents

gdoc2rmd	<i>Google docs to Rmarkdown</i>
----------	---------------------------------

Description

Use Articul8 Add-ons from Google docs to build Rticles

Usage

```
gdoc2rmd(file, export = "files", prefix_fig = "Figure", prefix_tab = "Table")
```

Arguments

file	Zip file path from Articul8 exported in md format
export	path to export the files. Default file directory
prefix_fig	Prefix for the name of the figure
prefix_tab	Prefix for the name of the table

Value

folder

H2cal

*Broad-sense heritability in plant breeding***Description**

Heritability in plant breeding on a genotype difference basis

Usage

```
H2cal(
  data,
  trait,
  gen.name,
  rep.n,
  env.n = 1,
  year.n = 1,
  env.name = NULL,
  year.name = NULL,
  fixed.model,
  random.model,
  summary = FALSE,
  emmeans = FALSE,
  weights = NULL,
  plot_diag = FALSE,
  outliers.rm = FALSE,
  trial = NULL
)
```

Arguments

data	Experimental design data frame with the factors and traits.
trait	Name of the trait.
gen.name	Name of the genotypes.
rep.n	Number of replications in the experiment.
env.n	Number of environments (default = 1). See details.
year.n	Number of years (default = 1). See details.
env.name	Name of the environments (default = NULL). See details.
year.name	Name of the years (default = NULL). See details.
fixed.model	The fixed effects in the model (BLUEs). See examples.
random.model	The random effects in the model (BLUPs). See examples.

summary	Print summary from random model (default = FALSE).
emmeans	Use emmeans for calculate the BLUEs (default = FALSE).
weights	an optional vector of 'prior weights' to be used in the fitting process (default = NULL).
plot_diag	Show diagnostic plots for fixed and random effects (default = FALSE). Options: "base", "ggplot". .
outliers.rm	Remove outliers (default = FALSE). See references.
trial	Column with the name of the trial in the results (default = NULL).

Details

The function allows to made the calculation for individual or multi-environmental trials (MET) using fixed and random model.

1. The variance components based in the random model and the population summary information based in the fixed model (BLUEs).
2. Heritability under three approaches: Standard (ANOVA), Cullis (BLUPs) and Piepho (BLUEs).
3. Best Linear Unbiased Estimators (BLUEs), fixed effect.
4. Best Linear Unbiased Predictors (BLUPs), random effect.
5. Table with the outliers removed for each model.

For individual experiments is necessary provide the `trait`, `gen.name`, `rep.n`.

For MET experiments you should `env.n` and `env.name` and/or `year.n` and `year.name` according your experiment.

The BLUEs calculation based in the pairwise comparison could be time consuming with the increase of the number of the genotypes. You can specify `emmeans = FALSE` and the calculate of the BLUEs will be faster.

If `emmeans = FALSE` you should change 1 by 0 in the fixed model for exclude the intersect in the analysis and get all the genotypes BLUEs.

For more information review the references.

Value

list

Author(s)

Maria Belen Kistner

Flavio Lozano Isla

References

Bernal Vasquez, Angela Maria, et al. "Outlier Detection Methods for Generalized Lattices: A Case Study on the Transition from ANOVA to REML." *Theoretical and Applied Genetics*, vol. 129, no. 4, Apr. 2016.

Buntaran, H., Piepho, H., Schmidt, P., Ryden, J., Halling, M., and Forkman, J. (2020). Cross validation of stagewise mixed model analysis of Swedish variety trials with winter wheat and spring barley. *Crop Science*, 60(5).

Schmidt, P., J. Hartung, J. Bennewitz, and H.P. Piepho. 2019. Heritability in Plant Breeding on a Genotype Difference Basis. *Genetics* 212(4).

Schmidt, P., J. Hartung, J. Rath, and H.P. Piepho. 2019. Estimating Broad Sense Heritability with Unbalanced Data from Agricultural Cultivar Trials. *Crop Science* 59(2).

Tanaka, E., and Hui, F. K. C. (2019). Symbolic Formulae for Linear Mixed Models. In H. Nguyen (Ed.), *Statistics and Data Science*. Springer.

Zystro, J., Colley, M., and Dawson, J. (2018). Alternative Experimental Designs for Plant Breeding. In *Plant Breeding Reviews*. John Wiley and Sons, Ltd.

Examples

```
library(inti)

dt <- potato

hr <- H2cal(data = dt
            , trait = "stemdw"
            , gen.name = "geno"
            , rep.n = 5
            , fixed.model = "0 + (1|bloque) + geno"
            , random.model = "1 + (1|bloque) + (1|geno)"
            , emmeans = TRUE
            , plot_diag = FALSE
            , outliers.rm = TRUE
            )

hr$tabsmr
hr$blues
hr$blups
hr$outliers
```

include_figure

Figure with caption and notes

Description

Include figures with title and notes using a data base

Usage

```
include_figure(figure, caption = NA, notes = NA, label = NA)
```

Arguments

figure	Path or URL of the figure.
caption	Figure caption (default = NA).
notes	Figure notes (default = NA).
label	Label for the notes (default = NA).

Value

Figure with caption and notes

Examples

```
library(inti)

figure <- "https://inkaverse.com/reference/figures/logo.png"

figure %>% include_figure(caption = "Title test."
  , notes = "Note test.")
```

include_table	<i>Table with footnotes</i>
---------------	-----------------------------

Description

Include tables with title and footnotes for word and html documents

Usage

```
include_table(table, caption = NA, notes = NA, label = NA, notation = "none")
```

Arguments

table	Data frame.
caption	Table caption (default = NULL). See details.
notes	Footnotes for the table (default = NA). See details.
label	Label for start the footnote (default = NA).
notation	Notation for the symbols and footnotes (default = "none") Others: "alphabet", "number", "symbol".

Value

Table with caption and footnotes

Examples

```
library(inti)

table <- data.frame(
  x = rep_len(1, 5)
  , y = rep_len(3, 5)
  , z = rep_len("c", 5)
)

table %>% inti::include_table(
  caption = "Title caption b) line 0
a) line 1
b) line 2"
  , notes = "Footnote"
  , label = "Where:"
)
```

jc_tombola

Journal Club Tombola

Description

Function for arrange journal club schedule

Usage

```
jc_tombola(
  data,
  members,
  papers = 1,
  group,
  gr_lvl,
  status,
  st_lvl,
  frq,
  date,
  seed = NULL
)
```

Arguments

data	Data frame with the members and their information.
members	Columns with the members names.
papers	Number of paper by meeting
group	Column for arrange the group.

gr_lvl	Levels in the groups for the arrange. See details.
status	Column with the status of the members.
st_lvl	Level to confirm the assistance in the JC. See details.
frq	Number of the day for each session.
date	Date when start the first session of JC.
seed	Number for replicate the results (default = date).

Details

The function could consider n levels for gr_lvl. In the case of two level the third level will be both. The suggested levels for st_lvl are: active or spectator. Only the active members will enter in the schedule.

Value

data frame with the schedule for the JC

mean_comparison	<i>Mean comparison test</i>
-----------------	-----------------------------

Description

Function to compare treatment from lm or aov using data frames

Usage

```
mean_comparison(
  data,
  response,
  model_factors,
  comparison,
  test_comp = "SNK",
  sig_level = 0.05
)
```

Arguments

data	Fieldbook data.
response	Model used for the experimental design.
model_factors	Factor in the model.
comparison	Significance level for the analysis (default = 0.05).
test_comp	Comparison test (default = "SNK"). Others: "TUKEY", "DUNCAN".
sig_level	Significance level for the analysis (default = 0.05).

Value

list

Examples

```
## Not run:

library(inti)
library(gsheets)

url <- paste0("https://docs.google.com/spreadsheets/d/"
             , "15r7ZwcZZHbEglt1F6gSFvCTFA-CFzVBWwg3mF1RyKPs/"
             , "edit#gid=172957346")
# browseURL(url)

fb <- gsheets2tbl(url)

mc <- mean_comparison(data = fb
                     , response = "spad_29"
                     , model_factors = "bloque* geno*treat"
                     , comparison = c("geno", "treat")
                     , test_comp = "SNK"
                     )

mc$comparison
mc$stat

## End(Not run)
```

met

*Swedish cultivar trial data***Description**

The datasets were obtained from official Swedish cultivar tests. Dry matter yield was analyzed. All trials were laid out as alpha-designs with two replicates. Within each replicate, there were five to seven incomplete blocks.

Usage

met

Format

A data frame with 1069 rows and 8 variables:

zone Sweden is divided into three different agricultural zones: South, Middle, and North

location Locations: 18 location in the Zones
rep Replications (4): number of replication in the experiment
alpha Incomplete blocks (8) in the alpha-designs
cultivar Cultivars (30): genotypes evaluated
yield Yield in kg/ha
year Year (1): 2016
env enviroment (18): combination zone + location + year

Source

[doi:10.1002/csc2.20177](https://doi.org/10.1002/csc2.20177)

metamorphosis	<i>Transform fieldbooks based in a dictionary</i>
---------------	---

Description

Transform entire fieldbook according to data a dictionary

Usage

```
metamorphosis(fieldbook, dictionary, from, to, index, colnames)
```

Arguments

fieldbook	Data frame with the original information.
dictionary	Data frame with new names and categories. See details.
from	Column of the dictionary with the original names.
to	Column of the dictionary with the new names.
index	Column of the dictionary with the type and level of the variables.
colnames	Character vector with the name of the columns.

Details

The function require at least three columns.

1. Original names (from).
2. New names (to).
3. Variable type (index).

Value

List with two objects. 1. New data frame. 2. Dictionary.

outliers_remove	<i>Remove outliers</i>
-----------------	------------------------

Description

Use the method M4 in Bernal Vasquez (2016). Bonferroni Holm test to judge residuals standardized by the re scaled MAD (BH MADR).

Usage

```
outliers_remove(data, trait, model)
```

Arguments

data	Experimental design data frame with the factors and traits.
trait	Name of the trait.
model	The fixed or random effects in the model.

Details

Function to remove outliers in MET experiments

Value

list. 1. Table with date without outliers. 2. The outliers in the dataset.

References

Bernal Vasquez, Angela Maria, et al. "Outlier Detection Methods for Generalized Lattices: A Case Study on the Transition from ANOVA to REML." Theoretical and Applied Genetics, vol. 129, no. 4, Apr. 2016.

Examples

```
library(inti)

rmout <- outliers_remove(
  data = potato
  , trait = "stemdw"
  , model = "0 + (1|bloque) + geno"
)

rmout$outliers
```

`plot_diag`*Diagnostic plots*

Description

Function to plot the diagnostic of models

Usage

```
plot_diag(model, title = NA)
```

Arguments

<code>model</code>	Statistical model
<code>title</code>	Plot title

Value

plots

Examples

```
## Not run:  
  
dt <- potato  
  
lm <- aov(stemdw ~ bloque + geno*treat, dt)  
  
#lm <- lme4::lmer(stemdw ~ bloque + (1|geno:treat), dt)  
  
plot(lm, which = 1)  
plot_diag(lm)[3]  
  
plot(lm, which = 2)  
plot_diag(lm)[2]  
  
plot(lm, which = 3)  
plot_diag(lm)[4]  
  
plot(lm, which = 4)  
plot_diag(lm)[1]  
  
## End(Not run)
```

plot_raw	<i>Plot raw data</i>
----------	----------------------

Description

Function use the raw data for made a boxplot graphic

Usage

```
plot_raw(
  data,
  type = "boxplot",
  x,
  y,
  group = NULL,
  xlab = NULL,
  ylab = NULL,
  glab = NULL,
  ylimits = NULL,
  xlimits = NULL,
  xrotation = NULL,
  legend = "top",
  xtext = NULL,
  gtext = NULL,
  color = TRUE,
  linetype = 1,
  opt = NULL
)
```

Arguments

data	raw data
type	Type of graphic. "boxplot" or "scatterplot"
x	Axis x variable
y	Axis y variable
group	Group variable
xlab	Title for the axis x
ylab	Title for the axis y
glab	Title for the legend
ylimits	Limits and break of the y axis c(initial, end, brakes)
xlimits	For scatter plot. Limits and break of the x axis c(initial, end, brakes)
xrotation	Rotation in x axis c(angle, h, v)
legend	the position of legends ("none", "left", "right", "bottom", "top", or two-element numeric vector)

xtext	Text labels in x axis using a vector
gtext	Text labels in groups using a vector
color	Colored figure (TRUE), black & white (FALSE) or color vector
linetype	Line type for regression. Default = 0
opt	Add new layers to the plot

Details

You could add additional layer to the plot using "+" with ggplot2 options

Value

plot

Examples

```
## Not run:

library(inti)

fb <- potato

fb %>%
  plot_raw(type = "box"
           , x = "geno"
           , y = "twue"
           , group = NULL
           , ylab = NULL
           , xlab = NULL
           , glab = ""
           )

fb %>%
  plot_raw(type = "sca"
           , x = "hi"
           , y = "twue"
           , group = ""
           )

## End(Not run)
```

plot_smr	<i>Plot summary data</i>
----------	--------------------------

Description

Graph summary data into bar o line plot

Usage

```
plot_smr(
  data,
  type = NULL,
  x = NULL,
  y = NULL,
  group = NULL,
  xlab = NULL,
  ylab = NULL,
  glab = NULL,
  ylimits = NULL,
  xrotation = c(0, 0.5, 0.5),
  xtext = NULL,
  gtext = NULL,
  legend = "top",
  sig = NULL,
  sigsize = 3,
  error = NULL,
  color = TRUE,
  opt = NULL
)
```

Arguments

data	Output from summary data
type	Type of graphic. "bar" or "line"
x	Axis x variable
y	Axis y variable
group	Group variable
xlab	Title for the axis x
ylab	Title for the axis y
glab	Title for the legend
ylimits	limits of the y axis c(initial, end, brakes)
xrotation	Rotation in x axis c(angle, h, v)
xtext	Text labels in x axis using a vector
gtext	Text labels in group using a vector

legend	the position of legends ("none", "left", "right", "bottom", "top", or two-element numeric vector)
sig	Column with the significance
sigsize	Font size in significance letters
error	Show the error bar ("ste" or "std")
color	colored figure (TRUE), black & white (FALSE) or color vector
opt	Add news layer to the plot

Details

If the table is a out put of `mean_comparison(graph_opts = TRUE)` function. Its contain all the parameter for the plot.

You could add additional layer to the plot using "+" with `ggplot2` options

Value

plot

Examples

```
## Not run:

library(inti)

fb <- potato#'

yrs <- yupana_analysis(data = fb
  , response = "hi"
  , model_factors = "geno*treat"
  , comparison = c("geno", "treat")
)

yrs$meancomp %>%
  plot_smr(type = "line"
    , x = "geno"
    , y = "hi"
    , xlab = ""
    , group = "treat"
    , glab = "Tratamientos"
    , ylimits = c(0, 1, 0.2)
    , color = c("red", "black")
    , gtext = c("Irrigado", "Sequia")
  )

## End(Not run)
```

potato

Water use efficiency in 15 potato genotypes

Description

Experiment to evaluate the physiological response from 15 potato genotypes under water deficit condition. The experiment had a randomized complete block design with five replications. The stress started at 30 day after planting.

Usage

potato

Format

A data frame with 150 rows and 17 variables:

treat Water deficit treatments: sequia, irrigado

geno 15 potato genotypes

bloque blocks for the experimentl design

spad_29 Relative chlorophyll content (SPAD) at 29 day after planting

spad_83 Relative chlorophyll content (SPAD) at 84 day after planting

rwc_84 Relative water content (percentage) at 84 day after planting

op_84 Osmotic potential (Mpa) at 84 day after planting

leafdw leaf dry weight (g)

stemdw stem dry weight (g)

rootdw root dry weight (g)

tubdw tuber dry weight (g)

biomdw total biomass dry weight (g)

hi harvest index

ttrans total transpiration (l)

wue water use efficiency (g/l)

twue tuber water use efficiency (g/l)

lfa leaf area (cm²)

`split_folder`*Split folder*

Description

Function to split folder by size or number of elements

Usage

```
split_folder(  
  folder,  
  export,  
  units = "megas",  
  size = 500,  
  zip = TRUE,  
  remove = FALSE  
)
```

Arguments

<code>folder</code>	Path of folder to split (path).
<code>export</code>	Path to export the split folders (path).
<code>units</code>	Units to split folder (string: "megas", "number").
<code>size</code>	Folder size by the units selected (numeric).
<code>zip</code>	Zip split folders (logical).
<code>remove</code>	Remove the split folder after zip (logical).

Value

zip files

Examples

```
## Not run:  
  
split_folder("pictures/QUINOA 2018-2019 SC SEEDS EDWIN - CAMACANI/"  
  , "pictures/split_num", remove = T, size = 400, units = "number")  
  
## End(Not run)
```

table2rmd	<i>Table to Rmarkdown</i>
-----------	---------------------------

Description

Use Articul8 Add-ons from Google docs to build Rarticles

Usage

```
table2rmd(text, opts = NA, prefix = "Table")
```

Arguments

text	String with the table information
opts	chunk options in brackets.
prefix	Prefix for the name of the table

Value

Mutated string

tarpuv	<i>Interactive fieldbook designs</i>
--------	--------------------------------------

Description

Invoke RStudio addin to create fieldbook designs

Usage

```
tarpuv(dependencies = FALSE)
```

Arguments

dependencies	Install package dependencies for run the app
--------------	--

Details

Tarpuv allow to create experimental designs under an interactive app.

Value

Shiny app

Examples

```
if(interactive()){
  inti::tarpuy()
}
```

tarpuy_design

Fieldbook experimental designs

Description

Function to deploy experimental designs

Usage

```
tarpuy_design(
  data,
  nfactors = 1,
  type = "crd",
  rep = 2,
  serie = 2,
  seed = 0,
  barcode = NA
)
```

Arguments

data	Experimental design data frame with the factors and level. See examples.
nfactors	Number of factor in the experiment(default = 1). See details.
type	Type of experimental arrange (default = "crd"). See details.
rep	Number of replications in the experiment (default = 3).
serie	Digits in the plot id (default = 2).
seed	Replicability of draw results (default = 0) always random. See details.
barcode	Barcode prefix for data collection.

Details

The function allows to include the arguments in the sheet that have the information of the design. You should include 2 columns in the sheet: {arguments} and {values}. See examples. The information will be extracted automatically and deploy the design. nfactors = 1: crd, rcbd, lsd, lattice. nfactors = 2 (factorial): split-crd, split-rcbd split-lsd nfactors >= 2 (factorial): crd, rcbd, lsd.

Value

A list with the fieldbook design

Examples

```
## Not run:

library(inti)
library(gsheets)

url <- paste0("https://docs.google.com/spreadsheets/d/"
             , "1tDcLZZ9C80uBJK8RRW6_WIyxil8bIHACStJyf8avuCU/edit#gid=59220990")
# browseURL(url)

fb <- gsheets2tbl(url)

tarpuy_design(data = fb)

## End(Not run)
```

tarpuy_plex

Fieldbook plan information

Description

Information for build a plan for an experiment (PLEX)

Usage

```
tarpuy_plex(
  data = NULL,
  idea = NULL,
  goal = NULL,
  hypothesis = NULL,
  rationale = NULL,
  objectives = NULL,
  plan = NULL,
  institutions = NULL,
  researchers = NULL,
  manager = NULL,
  location = NULL,
  altitude = NULL,
  georeferencing = NULL,
  environment = NULL,
  start = NA,
  end = NA,
```

```

    about = NULL,
    fieldbook = NULL,
    album = NULL,
    github = NULL,
    nfactor = 2,
    design = "rcbd",
    rep = 3,
    serie = 2,
    seed = 0
  )

```

Arguments

data	Data with the fieldbook information.
idea	How the idea was born.
goal	The main goal of the project.
hypothesis	What are the expected results.
rationale	Based in which evidence is planned the experiment.
objectives	The objectives of the project.
plan	General description of the project (M & M).
institutions	Institutions involved in the project.
researchers	Persons involved in the project.
manager	Persons responsible of the collection of the data.
location	Location of the project.
altitude	Altitude of the experiment (m.a.s.l).
georeferencing	Georeferencing information.
environment	Environment of the experiment (greenhouse, lab, etc).
start	The date of the start of the experiments.
end	The date of the end of the experiments.
about	Short description of the project.
fieldbook	Name or ID for the fieldbook/project.
album	link with the photos of the project.
github	link with the github repository.
nfactor	Number of factors for the design.
design	Type of design.
rep	Number of replication.
serie	Number of digits in the plots.
seed	Seed for the randomization.

Details

Provide the information available.

Value

data frame or list of arguments:

1. info
2. variables
3. design
4. logbook
5. timetable
6. budget

tarpuv_plotdesign *Fieldbook plot experimental designs*

Description

Plot fieldbook sketch designs based in experimental design

Usage

```
tarpuv_plotdesign(  
  data,  
  factor,  
  dim = NULL,  
  fill = "plots",  
  xlab = NULL,  
  ylab = NULL,  
  glab = NULL  
)
```

Arguments

data	Experimental design data frame with the factors and level. See examples.
factor	Vector with the name of the columns with the factors.
dim	Dimension for reshape the design arrangement.
fill	Value for fill the experimental units (default = "plots").
xlab	Title for x axis.
ylab	Title for y axis.
glab	Title for group axis.

Details

The function allows to plot the experimental design according the field experiment design.

Value

plot

tarpuy_varlist	<i>Fieldbook variable list</i>
----------------	--------------------------------

Description

Function to include the variables to evaluate in the fieldbook design.

Usage

```
tarpuy_varlist(fieldbook, varlist = NULL)
```

Arguments

fieldbook	Data frame with the fieldbook.
varlist	Data frame with the variables information. See examples.

Details

The function allows to include the arguments in the sheet that have the information of the variables. You should include 3 columns in the sheet: {abbreviation}, {evaluation} and {sampling}. See examples. The information will be extracted automatically and deploy the list of variable for the fieldbook design.

Value

data frame

Examples

```
## Not run:

library(inti)
library(gsheets)

url <- paste0("https://docs.google.com/spreadsheets/d/"
             , "183upHd4wriZz2UnInoo5Ate5YFdk7cZlhE0sMQ2x5iw/edit#gid=532773890")
# browseURL(url)

info <- gsheets2tbl(url)

fieldbook <- tarpuy_design(data = info)

url_var <- paste0("https://docs.google.com/spreadsheets/d/"
                 , "183upHd4wriZz2UnInoo5Ate5YFdk7cZlhE0sMQ2x5iw/edit#gid=1335288687")

varlist <- gsheets2tbl(url_var)

tarpuy_varlist(fieldbook = fieldbook, varlist = varlist)
```

```
## End(Not run)
```

web_table	<i>HTML tables for markdown documents</i>
-----------	---

Description

Export tables with download, pasta and copy buttons

Usage

```
web_table(
  data,
  caption = NULL,
  digits = 2,
  rnames = FALSE,
  buttons = NULL,
  file_name = "file",
  scrolly = NULL,
  columnwidth = "200px",
  width = "100%"
)
```

Arguments

data	Dataset.
caption	Title for the table.
digits	Digits number in the table exported.
rnames	Row names.
buttons	Buttons: "excel", "copy" or "none". Default c("excel", "copy")
file_name	Excel file name
scrolly	Windows height to show the table. Default "45vh"
columnwidth	Column width. Default '200px'
width	Width in pixels or percentage (Defaults to automatic sizing)

Value

table in markdown format for html documents

Examples

```
## Not run:  
  
library(inti)  
  
met %>%  
  web_table(caption = "Web table")  
  
## End(Not run)
```

yupana

Interactive data analysis

Description

Invoke RStudio addin to analyze and graph experimental design data

Usage

```
yupana(dependencies = FALSE)
```

Arguments

`dependencies` Install package dependencies for run the app

Details

Yupana: data analysis and graphics for experimental designs.

Value

Shiny app

Examples

```
if(interactive()){  
  inti::yupana()  
}
```

yupana_analysis *Fieldbook analysis report*

Description

Function to create a complete report of the fieldbook

Usage

```
yupana_analysis(  
  data,  
  last_factor = NULL,  
  response,  
  model_factors,  
  comparison,  
  test_comp = "SNK",  
  sig_level = 0.05,  
  plot_dist = "boxplot",  
  plot_diag = FALSE,  
  digits = 2  
)
```

Arguments

data	Field book data.
last_factor	The last factor in your fieldbook.
response	Response variable.
model_factors	Model used for the experimental design.
comparison	Factors to compare
test_comp	Comprasion test c("SNK", "TUKEY", "DUNCAN")
sig_level	Significal test (default: p = 0.005)
plot_dist	Plot data distribution (default = "boxplot")
plot_diag	Diagnostic plots for model (default = FALSE).
digits	Digits number in the table exported.

Value

list

Examples

```
## Not run:

library(inti)

fb <- potato

rsl <- yupana_analysis(data = fb
                      , last_factor = "bloque"
                      , response = "spad_83"
                      , model_factors = "geno * treat"
                      , comparison = c("geno", "treat")
                      )

## End(Not run)
```

yupana_export

Graph options to export

Description

Function to export the graph options and model parameters

Usage

```
yupana_export(
  data,
  type = NA,
  xlab = NA,
  ylab = NA,
  glab = NA,
  ylimits = NA,
  xrotation = c(0, 0.5, 0.5),
  xtext = NA,
  gtext = NA,
  legend = "top",
  sig = NA,
  error = NA,
  color = TRUE,
  opt = NA,
  dimension = c(20, 10, 100)
)
```

Arguments

data	Result from yupana_analysis or yupana_import.
type	Plot type
xlab	Title for the axis x
ylab	Title for the axis y
glab	Title for the legend
ylimits	limits of the y axis
xrotation	Rotation in x axis c(angle, h, v)
xtext	Text labels in x axis
gtext	Text labels in group
legend	the position of legends ("none", "left", "right", "bottom", "top", or two-element numeric vector)
sig	Column with the significance
error	Show the error bar ("ste" or "std").
color	colored figure (TRUE), otherwise black & white (FALSE)
opt	Add news layer to the plot
dimension	Dimension of graphs

Value

data frame

Examples

```
## Not run:

library(inti)
library(gsheets)

url <- paste0("https://docs.google.com/spreadsheets/d/"
             , "15r7ZwcZZHbEglt1F6gSFvCTFA-CFzVBWwg3mF1RyKPs/edit#gid=172957346")
# browseURL(url)

fb <- gsheets2tbl(url)

smr <- yupana_analysis(data = fb
                      , last_factor = "bloque"
                      , response = "spad_83"
                      , model_factors = "block + geno*treat"
                      , comparison = c("geno", "treat")
                      )

gtab <- yupana_export(smr, type = "line", ylimits = c(0, 100, 2))

#> import
```

```
url <- paste0("https://docs.google.com/spreadsheets/d/"
             , "15r7ZwcZZHbEglt1F6gSFvCTFA-CFzVBWwg3mF1RyKPs/edit#gid=1202800640")
# browseURL(url)

fb <- gsheets2tbl(url)

info <- yupana_import(fb)

etab <- yupana_export(info)

info2 <- yupana_import(etab)

etab2 <- yupana_export(info2)

## End(Not run)
```

yupana_import	<i>Import information from data summary</i>
---------------	---

Description

Graph summary data

Usage

```
yupana_import(data)
```

Arguments

data Summary information with options

Value

list

Examples

```
## Not run:

library(inti)
library(gsheets)

url <- paste0("https://docs.google.com/spreadsheets/d/"
             , "15r7ZwcZZHbEglt1F6gSFvCTFA-CFzVBWwg3mF1RyKPs/edit#gid=338518609")
# browseURL(url)
```



```
fb <- gsheets2tbl(url)

info <- yupana_import(fb)

## End(Not run)
```

yupana_mvr

Multivariate Analysis

Description

Multivariate analysis for PCA and HCPC

Usage

```
yupana_mvr(
  data,
  last_factor = NULL,
  summary_by = NULL,
  groups = NULL,
  variables = NULL
)
```

Arguments

data	Field book data.
last_factor	The last factor in your fieldbook.
summary_by	Variables for group the analysis.
groups	Groups for color in PCA.
variables	Variables to be use in the analysis.

Details

Compute and plot information for multivariate analysis (PCA, HCPC and correlation).

Value

result and plots

Examples

```
## Not run:

library(inti)
library(gsheet)

url <- paste0("https://docs.google.com/spreadsheets/d/"
              , "15r7ZwcZZHbEglt1F6gSFvCTFA-CFzVBWwg3mF1RyKPs/edit#gid=172957346")
# browseURL(url)

fb <- gsheet2tbl(url)

mv <- yupana_mvr(data = fb
                , last_factor = "bloque"
                , summary_by = c("geno", "treat")
                , groups = NULL
                )

FactoMineR::plot.PCA(mv$pca, choix = "ind", habillage = mv$param$groups)

## End(Not run)
```

yupana_reshape

Fieldbook reshape

Description

Function to reshape fieldbook according a separation character

Usage

```
yupana_reshape(
  data,
  last_factor,
  sep,
  new_colname,
  from_var = NULL,
  to_var = NULL,
  exc_factors = NULL
)
```

Arguments

`data` Field book raw data.
`last_factor` The last factor in your field book.

<code>sep</code>	Character that separates the last value.
<code>new_colname</code>	The new name for the column created.
<code>from_var</code>	The first variable in case you want to exclude several variables.
<code>to_var</code>	The last variable in case you want to exclude several variables.
<code>exc_factors</code>	Factor to exclude during the reshape.

Details

If you variable name is `variable_evaluation_rep`. The reshape function will help to create the column `rep` and the new variable name will be `variable_evaluation`.

Value

data frame

Index

- * **datasets**
 - met, [11](#)
 - potato, [19](#)
- colortext, [2](#)
- figure2rmd, [3](#)
- footnotes, [4](#)
- gdoc2rmd, [4](#)
- H2cal, [5](#)
- include_figure, [7](#)
- include_table, [8](#)
- jc_tombola, [9](#)
- mean_comparison, [10](#)
- met, [11](#)
- metamorphosis, [12](#)
- outliers_remove, [13](#)
- plot_diag, [14](#)
- plot_raw, [15](#)
- plot_smr, [17](#)
- potato, [19](#)
- split_folder, [20](#)
- table2rmd, [21](#)
- tarpu, [21](#)
- tarpu_design, [22](#)
- tarpu_plex, [23](#)
- tarpu_plotdesign, [25](#)
- tarpu_varlist, [26](#)
- web_table, [27](#)
- yupana, [28](#)
- yupana_analysis, [29](#)
- yupana_export, [30](#)
- yupana_import, [32](#)
- yupana_mvr, [33](#)
- yupana_reshape, [34](#)