

Package ‘openai’

December 13, 2022

Type Package

Title R Wrapper for OpenAI API

Version 0.3.0

Date 2022-12-12

Description An R wrapper of OpenAI API endpoints (see <https://beta.openai.com/docs/introduction> for details). This package covers Models, Completions, Edits, Images, Embeddings, Files, Fine-tunes, Moderations, and legacy Engines endpoints.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.2.1

URL <https://github.com/irudnyts/openai>,
<https://irudnyts.github.io/openai/>

BugReports <https://github.com/irudnyts/openai/issues>

Depends R (>= 4.2)

Imports assertthat (>= 0.2.1), glue (>= 1.6.2), httr (>= 1.4.3),
jsonlite (>= 1.8.0), lifecycle (>= 1.0.1), magrittr (>= 2.0.3)

Suggests testthat (>= 3.0.0), purrr (>= 0.3.4), covr (>= 3.5.1)

Config/testthat/edition 3

NeedsCompilation no

Author Igor Rudnytskyi [aut, cre]

Maintainer Igor Rudnytskyi <iegor.rudnytskyi@gmail.com>

Repository CRAN

Date/Publication 2022-12-12 23:50:08 UTC

R topics documented:

cancel_fine_tune	2
create_completion	3
create_edit	6
create_embedding	7
create_fine_tune	8
create_image	10
create_image_edit	11
create_image_variation	13
create_moderation	14
delete_file	15
delete_fine_tune_model	16
list_files	17
list_fine_tunes	18
list_fine_tune_events	19
list_models	20
retrieve_file	21
retrieve_file_content	22
retrieve_fine_tune	23
retrieve_model	24
upload_file	25

Index	27
--------------	-----------

cancel_fine_tune	<i>Cancel fine-tune</i>
------------------	-------------------------

Description

Cancel a running fine-tune job. See [this page](#) for details.

Usage

```
cancel_fine_tune(
  fine_tune_id,
  openai_api_key = Sys.getenv("OPENAI_API_KEY"),
  openai_organization = NULL
)
```

Arguments

`fine_tune_id` required; a length one character vector.

`openai_api_key` required; defaults to `Sys.getenv("OPENAI_API_KEY")` (i.e., the value is retrieved from the `.Renviron` file); a length one character vector. Specifies OpenAI API key.

`openai_organization` optional; defaults to `NULL`; a length one character vector. Specifies OpenAI organization.

Details

For arguments description please refer to the [official documentation](#).

Value

Returns a list, elements of which contains information about the cancelled fine-tune.

See Also

Other fine-tune functions: [create_fine_tune\(\)](#), [delete_fine_tune_model\(\)](#), [list_fine_tune_events\(\)](#), [list_fine_tunes\(\)](#), [retrieve_fine_tune\(\)](#)

Examples

```
## Not run:
training_file <- system.file(
  "extdata", "sport_prepared_train.jsonl", package = "openai"
)
validation_file <- system.file(
  "extdata", "sport_prepared_train.jsonl", package = "openai"
)

training_info <- upload_file(training_file, "fine-tune")
validation_info <- upload_file(validation_file, "fine-tune")

info <- create_fine_tune(
  training_file = training_info$id,
  validation_file = validation_info$id,
  model = "ada",
  compute_classification_metrics = TRUE,
  classification_positive_class = " baseball" # Mind space in front
)

id <- ifelse(
  length(info$data$id) > 1,
  info$data$id[length(info$data$id)],
  info$data$id
)

cancel_fine_tune(fine_tune_id = id)

## End(Not run)
```

create_completion *Create completion*

Description

Creates a completion based on the provided prompt and parameters. See [this page](#) for details.

Usage

```

create_completion(
  engine_id = deprecated(),
  model,
  prompt = "<|endoftext|>",
  suffix = NULL,
  max_tokens = 16,
  temperature = 1,
  top_p = 1,
  n = 1,
  stream = FALSE,
  logprobs = NULL,
  echo = FALSE,
  stop = NULL,
  presence_penalty = 0,
  frequency_penalty = 0,
  best_of = 1,
  logit_bias = NULL,
  user = NULL,
  openai_api_key = Sys.getenv("OPENAI_API_KEY"),
  openai_organization = NULL
)

```

Arguments

engine_id	[Deprecated]
model	required; a length one character vector.
prompt	required; defaults to "< endoftext >"; an arbitrary length character vector.
suffix	optional; defaults to NULL; a length one character vector.
max_tokens	required; defaults to 16; a length one numeric vector with the integer value greater than 0.
temperature	required; defaults to 1; a length one numeric vector with the value between 0 and 2.
top_p	required; defaults to 1; a length one numeric vector with the value between 0 and 1.
n	required; defaults to 1; a length one numeric vector with the integer value greater than 0.
stream	required; defaults to FALSE; a length one logical vector. Currently is not implemented.
logprobs	optional; defaults to NULL; a length one numeric vector with the integer value between 0 and 5.
echo	required; defaults to FALSE; a length one logical vector.
stop	optional; defaults to NULL; a character vector of length between one and four.
presence_penalty	required; defaults to 0; a length one numeric vector with a value between -2 and 2.

frequency_penalty	required; defaults to 0; a length one numeric vector with a value between -2 and 2.
best_of	required; defaults to 1; a length one numeric vector with the integer value greater than 0.
logit_bias	optional; defaults to NULL; a named list.
user	optional; defaults to NULL; a length one character vector.
openai_api_key	required; defaults to <code>Sys.getenv("OPENAI_API_KEY")</code> (i.e., the value is retrieved from the <code>.Renviron</code> file); a length one character vector. Specifies OpenAI API key.
openai_organization	optional; defaults to NULL; a length one character vector. Specifies OpenAI organization.

Details

For arguments description please refer to the [official documentation](#).

Value

Returns a list, elements of which contain completion(s) and supplementary information.

Examples

```
## Not run:
create_completion(
  model = "text-davinci-002",
  prompt = "Say this is a test",
  max_tokens = 5
)

logit_bias <- list(
  "11" = -100,
  "13" = -100
)
create_completion(
  model = "ada",
  prompt = "Generate a question and an answer",
  n = 4,
  best_of = 4,
  logit_bias = logit_bias
)

## End(Not run)
```

 create_edit

Create edit

Description

Creates an edit based on the provided input, instruction, and parameters. See [this page](#) for details.

Usage

```
create_edit(
  engine_id = deprecated(),
  model,
  input = "\",
  instruction,
  temperature = 1,
  top_p = 1,
  openai_api_key = Sys.getenv("OPENAI_API_KEY"),
  openai_organization = NULL
)
```

Arguments

engine_id	[Deprecated]
model	required; a length one character vector.
input	required; defaults to '"'; a length one character vector.
instruction	required; a length one character vector.
temperature	required; defaults to 1; a length one numeric vector with the value between 0 and 2.
top_p	required; defaults to 1; a length one numeric vector with the value between 0 and 1.
openai_api_key	required; defaults to Sys.getenv("OPENAI_API_KEY") (i.e., the value is retrieved from the .Renviron file); a length one character vector. Specifies OpenAI API key.
openai_organization	optional; defaults to NULL; a length one character vector. Specifies OpenAI organization.

Details

For arguments description please refer to the [official documentation](#).

Value

Returns a list, elements of which contain edited version of prompt and supplementary information.

Examples

```
## Not run:
create_edit(
  model = "text-davinci-edit-001",
  input = "What day of the wek is it?",
  instruction = "Fix the spelling mistakes"
)

## End(Not run)
```

create_embedding	<i>Create embeddings</i>
------------------	--------------------------

Description

Creates an embedding vector that represents the provided input. See [this page](#) for details.

Usage

```
create_embedding(
  engine_id = deprecated(),
  model,
  input,
  user = NULL,
  openai_api_key = Sys.getenv("OPENAI_API_KEY"),
  openai_organization = NULL
)
```

Arguments

engine_id	[Deprecated]
model	required; a length one character vector.
input	required; an arbitrary length character vector.
user	optional; defaults to NULL; a length one character vector.
openai_api_key	required; defaults to Sys.getenv("OPENAI_API_KEY") (i.e., the value is retrieved from the .Renviron file); a length one character vector. Specifies OpenAI API key.
openai_organization	optional; defaults to NULL; a length one character vector. Specifies OpenAI organization.

Details

For arguments description please refer to the [official documentation](#).

Value

Returns a list, an element of which contains embedding vector(s) for a given input.

Examples

```
## Not run:
create_embedding(
  model = "text-similarity-babbage-001",
  input = c(
    "Ah, it is so boring to write documentation",
    "But examples are really crucial"
  )
)

## End(Not run)
```

create_fine_tune	<i>Create fine-tune</i>
------------------	-------------------------

Description

Creates a job that fine-tunes a specified model based on a given dataset. See [this page](#) for details.

Usage

```
create_fine_tune(
  training_file,
  validation_file = NULL,
  model = c("curie", "ada", "babbage", "davinci"),
  n_epochs = 4,
  batch_size = NULL,
  learning_rate_multiplier = NULL,
  prompt_loss_weight = 0.1,
  compute_classification_metrics = FALSE,
  classification_n_classes = NULL,
  classification_positive_class = NULL,
  classification_betas = NULL,
  suffix = NULL,
  openai_api_key = Sys.getenv("OPENAI_API_KEY"),
  openai_organization = NULL
)
```

Arguments

`training_file` required; a length one character vector.
`validation_file` optional; defaults to NULL; a length one character vector.

model	model required; defaults to "curie"; a length one character vector, one among "ada", "babbage", "curie", and "davinci".
n_epochs	required; defaults to 4; a length one numeric vector with the integer value greater than 0.
batch_size	optional; defaults to NULL; a length one numeric vector with the integer value greater than 0.
learning_rate_multiplier	optional; defaults to NULL; a length one numeric vector with the value greater than 0.
prompt_loss_weight	required; defaults to 0.1; a length one numeric vector.
compute_classification_metrics	required; defaults to FALSE; a length one logical vector.
classification_n_classes	optional; defaults to NULL; a length one numeric vector with the value greater than 0.
classification_positive_class	optional; defaults to NULL; a length one character vector.
classification_betas	optional; defaults to NULL; a list elements of which are numeric values greater than 0.
suffix	optional; defaults to NULL; a length one character vector.
openai_api_key	required; defaults to Sys.getenv("OPENAI_API_KEY") (i.e., the value is retrieved from the .Renvirom file); a length one character vector. Specifies OpenAI API key.
openai_organization	optional; defaults to NULL; a length one character vector. Specifies OpenAI organization.

Details

For arguments description please refer to the [official documentation](#).

Value

Returns a list, elements of which contain information about the fine-tune.

See Also

Other fine-tune functions: [cancel_fine_tune\(\)](#), [delete_fine_tune_model\(\)](#), [list_fine_tune_events\(\)](#), [list_fine_tunes\(\)](#), [retrieve_fine_tune\(\)](#)

Examples

```
## Not run:
training_file <- system.file(
  "extdata", "sport_prepared_train.jsonl", package = "openai"
```

```

)
validation_file <- system.file(
  "extdata", "sport_prepared_train.jsonl", package = "openai"
)

training_info <- upload_file(training_file, "fine-tune")
validation_info <- upload_file(validation_file, "fine-tune")

info <- create_fine_tune(
  training_file = training_info$id,
  validation_file = validation_info$id,
  model = "ada",
  compute_classification_metrics = TRUE,
  classification_positive_class = " baseball" # Mind space in front
)

## End(Not run)

```

create_image

Create image

Description

Creates an image given a prompt. See [this page](#) for details.

Usage

```

create_image(
  prompt,
  n = 1,
  size = c("1024x1024", "256x256", "512x512"),
  response_format = c("url", "b64_json"),
  user = NULL,
  openai_api_key = Sys.getenv("OPENAI_API_KEY"),
  openai_organization = NULL
)

```

Arguments

prompt	required; a length one character vector.
n	required; defaults to 1; a length one numeric vector with the integer value greater than 0.
size	required; defaults to "1024x1024"; a length one character vector, one among "256x256", "512x512", and "1024x1024".
response_format	required; defaults to "url"; a length one character vector, one among "url" and "b64_json".
user	optional; defaults to NULL; a length one character vector.

`openai_api_key` required; defaults to `Sys.getenv("OPENAI_API_KEY")` (i.e., the value is retrieved from the `.Renviron` file); a length one character vector. Specifies OpenAI API key.

`openai_organization` optional; defaults to `NULL`; a length one character vector. Specifies OpenAI organization.

Details

For arguments description please refer to the [official documentation](#).

Value

Returns a list, an element of which contain either a link to the generated image or the generated image decoded in Base64.

See Also

Other image functions: [create_image_edit\(\)](#), [create_image_variation\(\)](#)

Examples

```
## Not run:  
create_image("An astronaut riding a horse in a photorealistic style")  
  
## End(Not run)
```

<code>create_image_edit</code>	<i>Create image edit</i>
--------------------------------	--------------------------

Description

Creates an edited or extended image given an original image and a prompt. See [this page](#) for details.

Usage

```
create_image_edit(  
  image,  
  mask,  
  prompt,  
  n = 1,  
  size = c("1024x1024", "256x256", "512x512"),  
  response_format = c("url", "b64_json"),  
  user = NULL,  
  openai_api_key = Sys.getenv("OPENAI_API_KEY"),  
  openai_organization = NULL  
)
```

Arguments

image	required; a length one character vector.
mask	required; a length one character vector.
prompt	required; a length one character vector.
n	required; defaults to 1; a length one numeric vector with the integer value greater than 0.
size	required; defaults to "1024x1024"; a length one character vector, one among "256x256", "512x512", and "1024x1024".
response_format	required; defaults to "url"; a length one character vector, one among "url" and "b64_json".
user	optional; defaults to NULL; a length one character vector.
openai_api_key	required; defaults to <code>Sys.getenv("OPENAI_API_KEY")</code> (i.e., the value is retrieved from the <code>.Renviron</code> file); a length one character vector. Specifies OpenAI API key.
openai_organization	optional; defaults to NULL; a length one character vector. Specifies OpenAI organization.

Details

For arguments description please refer to the [official documentation](#).

Value

Returns a list, an element of which contain either a link to the edited image or the edited image decoded in Base64.

See Also

Other image functions: [create_image_variation\(\)](#), [create_image\(\)](#)

Examples

```
## Not run:
image <- system.file("extdata", "astronaut.png", package = "openai")
mask <- system.file("extdata", "mask.png", package = "openai")
create_image_edit(
  image = image,
  mask = mask,
  prompt = "goat",
  n = 1,
  response_format = "url"
)

## End(Not run)
```

```
create_image_variation
```

Create image variation

Description

Creates a variation of a given image. See [this page](#) for details.

Usage

```
create_image_variation(  
  image,  
  n = 1,  
  size = c("1024x1024", "256x256", "512x512"),  
  response_format = c("url", "b64_json"),  
  user = NULL,  
  openai_api_key = Sys.getenv("OPENAI_API_KEY"),  
  openai_organization = NULL  
)
```

Arguments

image	required; a length one character vector.
n	required; defaults to 1; a length one numeric vector with the integer value greater than 0.
size	required; defaults to "1024x1024"; a length one character vector, one among "256x256", "512x512", and "1024x1024".
response_format	required; defaults to "url"; a length one character vector, one among "url" and "b64_json".
user	optional; defaults to NULL; a length one character vector.
openai_api_key	required; defaults to Sys.getenv("OPENAI_API_KEY") (i.e., the value is retrieved from the .Renviron file); a length one character vector. Specifies OpenAI API key.
openai_organization	optional; defaults to NULL; a length one character vector. Specifies OpenAI organization.

Details

For arguments description please refer to the [official documentation](#).

Value

Returns a list, an element of which contain either a link to the image variation or the image variation decoded in Base64.

See Also

Other image functions: [create_image_edit\(\)](#), [create_image\(\)](#)

Examples

```
## Not run:
image <- system.file("extdata", "astronaut.png", package = "openai")
create_image_variation(
  image = image,
  n = 1,
  size = "256x256",
  response_format = "url"
)

## End(Not run)
```

create_moderation	<i>Create moderation</i>
-------------------	--------------------------

Description

Classifies if text violates OpenAI's Content Policy. See [this page](#) for details.

Usage

```
create_moderation(
  input,
  model = c("text-moderation-stable", "text-moderation-latest"),
  openai_api_key = Sys.getenv("OPENAI_API_KEY"),
  openai_organization = NULL
)
```

Arguments

input	required; an arbitrary length character vector.
model	required; a length one character vector. One among "text-moderation-stable" and "text-moderation-latest".
openai_api_key	required; defaults to Sys.getenv("OPENAI_API_KEY") (i.e., the value is retrieved from the .Renviron file); a length one character vector. Specifies OpenAI API key.
openai_organization	optional; defaults to NULL; a length one character vector. Specifies OpenAI organization.

Details

For arguments description please refer to the [official documentation](#).

Value

Returns a list, elements of which contain information about the model.

Examples

```
## Not run:  
create_moderation("I want to kill them all.")  
  
## End(Not run)
```

delete_file	<i>Delete file</i>
-------------	--------------------

Description

Deletes a file. See [this page](#) for details.

Usage

```
delete_file(  
  file_id,  
  openai_api_key = Sys.getenv("OPENAI_API_KEY"),  
  openai_organization = NULL  
)
```

Arguments

`file_id` required; a length one character vector.

`openai_api_key` required; defaults to `Sys.getenv("OPENAI_API_KEY")` (i.e., the value is retrieved from the `.Renviron` file); a length one character vector. Specifies OpenAI API key.

`openai_organization` optional; defaults to `NULL`; a length one character vector. Specifies OpenAI organization.

Details

For arguments description please refer to the [official documentation](#).

Value

Returns a list, elements of which contains ID of the deleted file and status whether the file is deleted.

See Also

Other file functions: [list_files\(\)](#), [retrieve_file_content\(\)](#), [retrieve_file\(\)](#), [upload_file\(\)](#)

Examples

```
## Not run:
file <- system.file("extdata", "classification-file.jsonl", package = "openai")
file_info <- upload_file(file = file, purpose = "classification")
delete_file(file_info$id)

## End(Not run)
```

```
delete_fine_tune_model
```

Delete fine_tune model

Description

Deletes a fine-tuned model. See [this page](#) for details.

Usage

```
delete_fine_tune_model(
  model,
  openai_api_key = Sys.getenv("OPENAI_API_KEY"),
  openai_organization = NULL
)
```

Arguments

`model` required; a length one character vector.

`openai_api_key` required; defaults to `Sys.getenv("OPENAI_API_KEY")` (i.e., the value is retrieved from the `.Renviron` file); a length one character vector. Specifies OpenAI API key.

`openai_organization` optional; defaults to `NULL`; a length one character vector. Specifies OpenAI organization.

Details

For arguments description please refer to the [official documentation](#).

Value

Returns a list, elements of which contains information about the deleted model.

See Also

Other fine-tune functions: [cancel_fine_tune\(\)](#), [create_fine_tune\(\)](#), [list_fine_tune_events\(\)](#), [list_fine_tunes\(\)](#), [retrieve_fine_tune\(\)](#)

Examples

```
## Not run:
fine_tunes <- list_fine_tunes()

fine_tunes <- fine_tunes$data

id <- fine_tunes[!is.na(fine_tunes[, "fine_tuned_model"]), "fine_tuned_model"]

delete_fine_tune_model(model = id[1])

## End(Not run)
```

list_files	<i>List files</i>
------------	-------------------

Description

Lists files uploaded by user's organization. See [this page](#) for details.

Usage

```
list_files(
  openai_api_key = Sys.getenv("OPENAI_API_KEY"),
  openai_organization = NULL
)
```

Arguments

`openai_api_key` required; defaults to `Sys.getenv("OPENAI_API_KEY")` (i.e., the value is retrieved from the `.Renviron` file); a length one character vector. Specifies OpenAI API key.

`openai_organization` optional; defaults to `NULL`; a length one character vector. Specifies OpenAI organization.

Details

For arguments description please refer to the [official documentation](#).

Value

Returns a list, an element of which is a data frame containing information about files.

See Also

Other file functions: [delete_file\(\)](#), [retrieve_file_content\(\)](#), [retrieve_file\(\)](#), [upload_file\(\)](#)

Examples

```
## Not run:  
list_files()  
  
## End(Not run)
```

list_fine_tunes	<i>Lists fine-tunes</i>
-----------------	-------------------------

Description

Lists organization's fine-tuning jobs. See [this page](#) for details.

Usage

```
list_fine_tunes(  
  openai_api_key = Sys.getenv("OPENAI_API_KEY"),  
  openai_organization = NULL  
)
```

Arguments

`openai_api_key` required; defaults to `Sys.getenv("OPENAI_API_KEY")` (i.e., the value is retrieved from the `.Renv` file); a length one character vector. Specifies OpenAI API key.

`openai_organization` optional; defaults to `NULL`; a length one character vector. Specifies OpenAI organization.

Details

For arguments description please refer to the [official documentation](#).

Value

Returns a list, an element of which is a data frame containing information about fine-tunes.

See Also

Other fine-tune functions: [cancel_fine_tune\(\)](#), [create_fine_tune\(\)](#), [delete_fine_tune_model\(\)](#), [list_fine_tune_events\(\)](#), [retrieve_fine_tune\(\)](#)

Examples

```
## Not run:  
list_fine_tunes()  
  
## End(Not run)
```

`list_fine_tune_events` *List fine-tune events*

Description

Returns events related to a specified fine-tune job. See [this page](#) for details.

Usage

```
list_fine_tune_events(  
  fine_tune_id,  
  stream = FALSE,  
  openai_api_key = Sys.getenv("OPENAI_API_KEY"),  
  openai_organization = NULL  
)
```

Arguments

`fine_tune_id` required; a length one character vector.

`stream` required; defaults to FALSE; a length one logical vector. **Currently is not implemented.**

`openai_api_key` required; defaults to `Sys.getenv("OPENAI_API_KEY")` (i.e., the value is retrieved from the `.Renviron` file); a length one character vector. Specifies OpenAI API key.

`openai_organization` optional; defaults to NULL; a length one character vector. Specifies OpenAI organization.

Details

For arguments description please refer to the [official documentation](#).

Value

Returns a list, elements of which contains information about the fine-tune events.

See Also

Other fine-tune functions: [cancel_fine_tune\(\)](#), [create_fine_tune\(\)](#), [delete_fine_tune_model\(\)](#), [list_fine_tunes\(\)](#), [retrieve_fine_tune\(\)](#)

Examples

```
## Not run:  
training_file <- system.file(  
  "extdata", "sport_prepared_train.jsonl", package = "openai"  
)
```

```

validation_file <- system.file(
  "extdata", "sport_prepared_train.jsonl", package = "openai"
)

training_info <- upload_file(training_file, "fine-tune")
validation_info <- upload_file(validation_file, "fine-tune")

info <- create_fine_tune(
  training_file = training_info$id,
  validation_file = validation_info$id,
  model = "ada",
  compute_classification_metrics = TRUE,
  classification_positive_class = " baseball" # Mind space in front
)

id <- ifelse(
  length(info$data$id) > 1,
  info$data$id[length(info$data$id)],
  info$data$id
)

list_fine_tune_events(fine_tune_id = id)

## End(Not run)

```

list_models

List models

Description

Lists the currently available models, and provides basic information about each one such as the owner and availability. See [this page](#) for details.

Usage

```

list_models(
  openai_api_key = Sys.getenv("OPENAI_API_KEY"),
  openai_organization = NULL
)

```

Arguments

`openai_api_key` required; defaults to `Sys.getenv("OPENAI_API_KEY")` (i.e., the value is retrieved from the `.Renviron` file); a length one character vector. Specifies OpenAI API key.

`openai_organization` optional; defaults to `NULL`; a length one character vector. Specifies OpenAI organization.

Details

For arguments description please refer to the [official documentation](#).

Value

Returns a list, an element of which is a data frame containing information about models.

See Also

Other model functions: [retrieve_model\(\)](#)

Examples

```
## Not run:  
list_models()  
  
## End(Not run)
```

retrieve_file	<i>Retrieve file</i>
---------------	----------------------

Description

Provides information about a specific file. See [this page](#) for details.

Usage

```
retrieve_file(  
  file_id,  
  openai_api_key = Sys.getenv("OPENAI_API_KEY"),  
  openai_organization = NULL  
)
```

Arguments

`file_id` required; a length one character vector.

`openai_api_key` required; defaults to `Sys.getenv("OPENAI_API_KEY")` (i.e., the value is retrieved from the `.Renviron` file); a length one character vector. Specifies OpenAI API key.

`openai_organization` optional; defaults to `NULL`; a length one character vector. Specifies OpenAI organization.

Details

For arguments description please refer to the [official documentation](#).

Value

Returns a list, elements of which contains information about the file.

See Also

Other file functions: [delete_file\(\)](#), [list_files\(\)](#), [retrieve_file_content\(\)](#), [upload_file\(\)](#)

Examples

```
## Not run:
file <- system.file("extdata", "classification-file.jsonl", package = "openai")
file_info <- upload_file(file = file, purpose = "classification")
retrieve_file(file_info$id)

## End(Not run)
```

retrieve_file_content *Retrieve file content*

Description

Returns the content of the specified file. See [this page](#) for details. Please note that only output files are allowed to be downloaded, not the input ones.

Usage

```
retrieve_file_content(
  file_id,
  openai_api_key = Sys.getenv("OPENAI_API_KEY"),
  openai_organization = NULL
)
```

Arguments

`file_id` required; a length one character vector.

`openai_api_key` required; defaults to `Sys.getenv("OPENAI_API_KEY")` (i.e., the value is retrieved from the `.Renviron` file); a length one character vector. Specifies OpenAI API key.

`openai_organization` optional; defaults to `NULL`; a length one character vector. Specifies OpenAI organization.

Details

For arguments description please refer to the [official documentation](#).

Value

Returns a list, an element of which contains the content of the file.

See Also

Other file functions: [delete_file\(\)](#), [list_files\(\)](#), [retrieve_file\(\)](#), [upload_file\(\)](#)

retrieve_fine_tune	<i>Retrieve fine-tune</i>
--------------------	---------------------------

Description

Returns information about the specified fine-tune job. See [this page](#) for details.

Usage

```
retrieve_fine_tune(  
  fine_tune_id,  
  openai_api_key = Sys.getenv("OPENAI_API_KEY"),  
  openai_organization = NULL  
)
```

Arguments

`fine_tune_id` required; a length one character vector.

`openai_api_key` required; defaults to `Sys.getenv("OPENAI_API_KEY")` (i.e., the value is retrieved from the `.Renviron` file); a length one character vector. Specifies OpenAI API key.

`openai_organization` optional; defaults to `NULL`; a length one character vector. Specifies OpenAI organization.

Details

For arguments description please refer to the [official documentation](#).

Value

Returns a list, elements of which contains information about the fine-tune.

See Also

Other fine-tune functions: [cancel_fine_tune\(\)](#), [create_fine_tune\(\)](#), [delete_fine_tune_model\(\)](#), [list_fine_tune_events\(\)](#), [list_fine_tunes\(\)](#)

Examples

```
## Not run:
training_file <- system.file(
  "extdata", "sport_prepared_train.jsonl", package = "openai"
)
validation_file <- system.file(
  "extdata", "sport_prepared_train.jsonl", package = "openai"
)

training_info <- upload_file(training_file, "fine-tune")
validation_info <- upload_file(validation_file, "fine-tune")

info <- create_fine_tune(
  training_file = training_info$id,
  validation_file = validation_info$id,
  model = "ada",
  compute_classification_metrics = TRUE,
  classification_positive_class = " baseball" # Mind space in front
)

id <- ifelse(
  length(info$data$id) > 1,
  info$data$id[length(info$data$id)],
  info$data$id
)

retrieve_fine_tune(fine_tune_id = id)

## End(Not run)
```

retrieve_model

Retrieve model

Description

Retrieves a model instance, providing basic information about the model such as the owner and permissioning. See [this page](#) for details.

Usage

```
retrieve_model(
  model,
  openai_api_key = Sys.getenv("OPENAI_API_KEY"),
  openai_organization = NULL
)
```


Arguments

- `model` required; a length one character vector.
- `openai_api_key` required; defaults to `Sys.getenv("OPENAI_API_KEY")` (i.e., the value is retrieved from the `.Renv` file); a length one character vector. Specifies OpenAI API key.
- `openai_organization` optional; defaults to `NULL`; a length one character vector. Specifies OpenAI organization.

Details

For arguments description please refer to the [official documentation](#).

Value

Returns a list, elements of which contain information about the model.

See Also

Other model functions: [list_models\(\)](#)

Examples

```
## Not run:
retrieve_model("text-davinci-002")

## End(Not run)
```

upload_file

Upload file

Description

Uploads a file that will be used for various purposes. The size of the storage is limited to 1 Gb. See [this page](#) for details.

Usage

```
upload_file(
  file,
  purpose = c("search", "answers", "classifications", "fine-tune"),
  openai_api_key = Sys.getenv("OPENAI_API_KEY"),
  openai_organization = NULL
)
```

Arguments

file	required; a length one character vector.
purpose	required; defaults to "search"; a length one character vector, one among "search", "answers", "classifications", and "fine-tune".
openai_api_key	required; defaults to Sys.getenv("OPENAI_API_KEY") (i.e., the value is retrieved from the .Renviron file); a length one character vector. Specifies OpenAI API key.
openai_organization	optional; defaults to NULL; a length one character vector. Specifies OpenAI organization.

Details

For arguments description please refer to the [official documentation](#).

Value

Returns a list, elements of which contains ID of the uploaded file and other supplementary information.

See Also

Other file functions: [delete_file\(\)](#), [list_files\(\)](#), [retrieve_file_content\(\)](#), [retrieve_file\(\)](#)

Examples

```
## Not run:  
file <- system.file("extdata", "classification-file.jsonl", package = "openai")  
upload_file(file = file, purpose = "classification")  
  
## End(Not run)
```

Index

* file functions

delete_file, 15
list_files, 17
retrieve_file, 21
retrieve_file_content, 22
upload_file, 25

* fine-tune functions

cancel_fine_tune, 2
create_fine_tune, 8
delete_fine_tune_model, 16
list_fine_tune_events, 19
list_fine_tunes, 18
retrieve_fine_tune, 23

* image functions

create_image, 10
create_image_edit, 11
create_image_variation, 13

* model functions

list_models, 20
retrieve_model, 24

cancel_fine_tune, 2, 9, 16, 18, 19, 23
create_completion, 3
create_edit, 6
create_embedding, 7
create_fine_tune, 3, 8, 16, 18, 19, 23
create_image, 10, 12, 14
create_image_edit, 11, 11, 14
create_image_variation, 11, 12, 13
create_moderation, 14

delete_file, 15, 17, 22, 23, 26
delete_fine_tune_model, 3, 9, 16, 18, 19, 23

list_files, 15, 17, 22, 23, 26
list_fine_tune_events, 3, 9, 16, 18, 19, 23
list_fine_tunes, 3, 9, 16, 18, 19, 23
list_models, 20, 25

retrieve_file, 15, 17, 21, 23, 26

retrieve_file_content, 15, 17, 22, 22, 26
retrieve_fine_tune, 3, 9, 16, 18, 19, 23
retrieve_model, 21, 24

upload_file, 15, 17, 22, 23, 25