

Package ‘rENA’

October 14, 2022

Title Epistemic Network Analysis

Type Package

Author Cody L Marquart [aut, cre] (<<https://orcid.org/0000-0002-3387-6792>>),
Zachari Swiecki [aut],
Wesley Collier [aut],
Brendan Eagan [aut],
Roman Woodward [aut],
David Williamson Shaffer [aut]

Maintainer Cody L Marquart <cody.marquart@wisc.edu>

Version 0.2.4

Description ENA (Shaffer, D. W. (2017) Quantitative Ethnography. ISBN: 0578191687) is a method used to identify meaningful and quantifiable patterns in discourse or reasoning. ENA moves beyond the traditional frequency-based assessments by examining the structure of the co-occurrence, or connections in coded data. Moreover, compared to other methodological approaches, ENA has the novelty of (1) modeling whole networks of connections and (2) affording both quantitative and qualitative comparisons between different network models. Shaffer, D.W., Collier, W., & Ruis, A.R. (2016).

LazyData TRUE

Depends R (>= 3.0.0)

License GPL-3 | file LICENSE

URL <https://gitlab.com/epistemic-analytics/qe-packages/rENA>

BugReports <https://gitlab.com/epistemic-analytics/qe-packages/rENA/-/issues>

LinkingTo Rcpp, RcppArmadillo

Imports data.table, Rcpp, R6, methods, foreach, stats, plotly,
doParallel, parallel, scales, magrittr, concatenate

Suggests testthat (>= 2.1.0), knitr, rmarkdown, webshot

RoxygenNote 7.1.1

NeedsCompilation yes

Repository CRAN

Date/Publication 2022-03-25 16:50:02 UTC

R topics documented:

add_group	3
add_network	4
add_nodes	4
add_points	5
add_trajectory	5
as.ena.co.occurrence	6
as.ena.matrix	6
as.ena.metadata	7
as.matrix.ena.connections	7
as.matrix.ena.line.weights	8
as.matrix.ena.matrix	8
as.matrix.ena.nodes	9
as.matrix.ena.points	9
as.matrix.ena.rotation.matrix	10
as.matrix.row.connections	10
as_trajectory	11
clear	11
combn_c2	12
connection.matrix	12
ena	13
ena.accumulate.data	15
ena.conversations	17
ena.correlations	18
ena.group	19
ena.make.set	20
ena.plot	22
ena.plot.group	23
ena.plot.network	25
ena.plot.points	28
ena.plot.trajectory	31
ena.plotter	33
ena.rotate.by.mean	34
ena.set.creator	35
ena.svd	36
ena.writeup	37
ENAdata	38
ENApplot	40
ENARotationSet	42
ENAsset	43
ena_correlation	45
find_code_cols	45
find_dimension_cols	46
find_meta_cols	46
fun_cohens.d	47
fun_skip_sphere_norm	47
fun_sphere_norm	48

means_rotate	48
merge_columns_c	49
methods_report	49
methods_report_stream	50
move_nodes_to_unit_circle	51
move_nodes_to_unit_circle_with_equal_space	51
namesToAdjacencyKey	52
plot.ena.set	52
prepare_trajectory_data	53
print.ena.set	54
project_in	55
remove_meta_data	55
rENA	56
RS.data	56
scale.ena.set	56
show	57
vector_to_ut	57
with_means	58
with_trajectory	58
\$.ena.matrix	59
\$.ena.metadata	59
\$.ena.points	60
\$.line.weights	60

Index **61**

add_group *Add a group mean to an ena.plot*

Description

Add a group mean to an ena.plot

Usage

add_group(x, wh = NULL, ...)

Arguments

- x ena.plot object to plot on
- wh which points to plot as the trajectory
- ... additional parameters to pass along

Value

ena.plot.object

add_network	<i>Add a network to an ENA plot</i>
-------------	-------------------------------------

Description

Add a network to an ENA plot

Usage

```
add_network(x, wh = NULL, ..., with.mean = F)
```

Arguments

x	ena.plot object to plot with
wh	network to plot
...	Additional parameters to pass along
with.mean	Logical value, if TRUE plots the mean for the points in the network

Value

ena.plot.object

add_nodes	<i>Title</i>
-----------	--------------

Description

Title

Usage

```
add_nodes(x, ...)
```

Arguments

x	[TBD]
...	[TBD]

Value

TBD

add_points	<i>Plot points on an ena.plot</i>
------------	-----------------------------------

Description

Plot points on an ena.plot

Usage

```
add_points(x, wh = NULL, ..., name = "plot", mean = NULL, colors = NULL)
```

Arguments

x	ena.plot to add point on
wh	which points to plot
...	additional parameters to pass along
name	name to give the plot
mean	include a mean point for the provided points
colors	colors for plotted points

Value

ena.plot.object

add_trajectory	<i>Plot a trajectory on an ena.plot</i>
----------------	---

Description

Plot a trajectory on an ena.plot

Usage

```
add_trajectory(x, wh = NULL, ..., name = "plot")
```

Arguments

x	ena.plot object to plot on
wh	which points to plot as the trajectory
...	additional parameters to pass along
name	Name, as a character vector, to give the plot

Value

ena.plot.object

as.ena.co.occurrence *Re-class vector as ena.co.occurrence*

Description

Re-class vector as ena.co.occurrence

Usage

```
as.ena.co.occurrence(x)
```

Arguments

x Vector to re-class

Value

re-classed vector

as.ena.matrix *Re-class matrix as ena.matrix*

Description

Re-class matrix as ena.matrix

Usage

```
as.ena.matrix(x, new.class = NULL)
```

Arguments

x data.frame, data.table, or matrix to extend
new.class Additional class to extend the matrix with, default: NULL

Value

Object of same st

as.ena.metadata	<i>Re-class matrix as ena.metadata</i>
-----------------	--

Description

Re-class matrix as ena.metadata

Usage

```
as.ena.metadata(x)
```

Arguments

x data.frame, data.table, or matrix to extend

Value

Object of same st

as.matrix.ena.connections	<i>ENA Connections as a matrix</i>
---------------------------	------------------------------------

Description

ENA Connections as a matrix

Usage

```
## S3 method for class 'ena.connections'  
as.matrix(x, ...)
```

Arguments

x ena.connections object
... additional arguments to be passed to or from methods

Value

If square is FALSE (default), a matrix with all metadata columns removed, otherwise a list with square matrices

as.matrix.ena.line.weights
ENA line weights as matrix

Description

ENA line weights as matrix

Usage

```
## S3 method for class 'ena.line.weights'
as.matrix(x, ..., square = FALSE)
```

Arguments

x	ena.line.weights data.table to covert to matrix
...	additional arguments to be passed to or from methods
square	[TBD]

Value

matrix

as.matrix.ena.matrix *Matrix without metadata*

Description

Matrix without metadata

Usage

```
## S3 method for class 'ena.matrix'
as.matrix(x, ...)
```

Arguments

x	Object to convert to a matrix
...	additional arguments to be passed to or from methods

Value

matrix

as.matrix.ena.nodes *ENA nodes as matrix*

Description

ENA nodes as matrix

Usage

```
## S3 method for class 'ena.nodes'  
as.matrix(x, ...)
```

Arguments

x ena.nodes to convert to matrix
... additional arguments to be passed to or from methods

Value

matrix

as.matrix.ena.points *ENA points as matrix*

Description

ENA points as matrix

Usage

```
## S3 method for class 'ena.points'  
as.matrix(x, ...)
```

Arguments

x ena.points to convert to a matrix
... additional arguments to be passed to or from methods

Value

matrix

```
as.matrix.ena.rotation.matrix  
    ENA rotations as matrix
```

Description

ENA rotations as matrix

Usage

```
## S3 method for class 'ena.rotation.matrix'  
as.matrix(x, ...)
```

Arguments

x ena.rotation.matrix to conver to matrix
... additional arguments to be passed to or from methods

Value

matrix

```
as.matrix.row.connections  
    ENA row connections as matrix
```

Description

ENA row connections as matrix

Usage

```
## S3 method for class 'row.connections'  
as.matrix(x, ...)
```

Arguments

x ena.row.connections to conver to a matrix
... additional arguments to be passed to or from methods

Value

matrix

as_trajectory	<i>Title</i>
---------------	--------------

Description

Title

Usage

```
as_trajectory(
  x,
  by = x$`_function.params`$conversation[1],
  model = c("AccumulatedTrajectory", "SeperateTrajectory"),
  ...
)
```

Arguments

x	[TBD]
by	[TBD]
model	[TBD]
...	[TBD]

Value

TBD

clear	<i>Title</i>
-------	--------------

Description

Title

Usage

```
clear(x, wh = seq(x$plots))
```

Arguments

x	[TBD]
wh	[TBD]

Value

TBD

combn_c2

Fast combn choose 2

Description

faster combn alternative

Usage

combn_c2(n)

Argumentsn TBD

connection.matrix

Connection counts as square matrix

Description

Connection counts as square matrix

Usage

connection.matrix(x)

Arguments

x ena.set or ena.connections (i.e. set\$connection.counts)

Value

matrix

ena

*Wrapper to generate, and optionally plot, an ENA model***Description**

Generates an ENA model by constructing a dimensional reduction of adjacency (co-occurrence) vectors as defined by the supplied conversations, units, and codes.

Usage

```
ena(
  data,
  codes,
  units,
  conversation,
  metadata = NULL,
  model = c("EndPoint", "AccumulatedTrajectory", "SeparateTrajectory"),
  weight.by = "binary",
  window = c("MovingStanzaWindow", "Conversation"),
  window.size.back = 1,
  include.meta = TRUE,
  groupVar = NULL,
  groups = NULL,
  runTest = FALSE,
  points = FALSE,
  mean = FALSE,
  network = TRUE,
  networkMultiplier = 1,
  subtractionMultiplier = 1,
  unit = NULL,
  include.plots = T,
  print.plots = F,
  ...
)
```

Arguments

data	data.frame with containing metadata and coded columns
codes	vector, numeric or character, of columns with codes
units	vector, numeric or character, of columns representing units
conversation	vector, numeric or character, of columns to segment conversations by
metadata	vector, numeric or character, of columns with additional meta information for units
model	character: EndPoint (default), AccumulatedTrajectory, SeparateTrajectory
weight.by	"binary" is default, can supply a function to call (e.g. sum)

<code>window</code>	MovingStanzaWindow (default) or Conversation
<code>window.size.back</code>	Number of lines in the stanza window (default: 1)
<code>include.meta</code>	[TBD]
<code>groupVar</code>	vector, character, of column name containing group identifiers. If column contains at least two unique values, will generate model using a means rotation (a dimensional reduction maximizing the variance between the means of the two groups)
<code>groups</code>	vector, character, of values of <code>groupVar</code> column used for means rotation, plotting, or statistical tests
<code>runTest</code>	logical, TRUE will run a Student's t-Test and a Wilcoxon test for groups defined by the <code>groups</code> argument
<code>points</code>	logical, TRUE will plot points (default: FALSE)
<code>mean</code>	logical, TRUE will plot the mean position of the groups defined in the <code>groups</code> argument (default: FALSE)
<code>network</code>	logical, TRUE will plot networks (default: TRUE)
<code>networkMultiplier</code>	numeric, scaling factor for non-subtracted networks (default: 1)
<code>subtractionMultiplier</code>	numeric, scaling factor for subtracted networks (default: 1)
<code>unit</code>	vector, character, name of a single unit to plot
<code>include.plots</code>	logical, TRUE will generate plots based on the model (default: TRUE)
<code>print.plots</code>	logical, TRUE will show plots in the Viewer (default: FALSE)
<code>...</code>	Additional parameters passed to set creation and plotting functions

Details

This function generates an `ena.set` object given a `data.frame`, units, conversations, and codes. After accumulating the adjacency (co-occurrence) vectors, computes a dimensional reduction (projection), and calculates node positions in the projected ENA space. Returns location of the units in the projected space, as well as locations for node positions, and normalized adjacency (co-occurrence) vectors to construct network graphs. Includes options for returning statistical tests between groups of units, as well as plots of units, groups, and networks.

Value

`ena.set` object

Examples

```
data(RS.data)

rs = ena(
  data = RS.data,
  units = c("UserName", "Condition", "GroupName"),
  conversation = c("Condition", "GroupName"),
```

```

codes = c('Data',
          'Technical.Constraints',
          'Performance.Parameters',
          'Client.and.Consultant.Requests',
          'Design.Reasoning',
          'Collaboration'),
window.size.back = 4,
print.plots = FALSE,
groupVar = "Condition",
groups = c("FirstGame", "SecondGame")
)

```

ena.accumulate.data *Accumulate data from a data frame into a set of adjacency (co-occurrence) vectors*

Description

This function initializes an ENAdata object, processing conversations from coded data to generate adjacency (co-occurrence) vectors

Usage

```

ena.accumulate.data(
  units = NULL,
  conversation = NULL,
  codes = NULL,
  metadata = NULL,
  model = c("EndPoint", "AccumulatedTrajectory", "SeparateTrajectory"),
  weight.by = "binary",
  window = c("MovingStanzaWindow", "Conversation"),
  window.size.back = 1,
  window.size.forward = 0,
  mask = NULL,
  include.meta = T,
  as.list = T,
  ...
)

```

Arguments

units	A data frame where the columns are the properties by which units will be identified
conversation	A data frame where the columns are the properties by which conversations will be identified
codes	A data frame where the columns are the codes used to create adjacency (co-occurrence) vectors

metadata	(optional) A data frame with additional columns of metadata to be associated with each unit in the data
model	A character, choices: EndPoint (or E), AccumulatedTrajectory (or A), or SeparateTrajectory (or S); default: EndPoint. Determines the ENA model to be constructed
weight.by	(optional) A function to apply to values after accumulation
window	A character, choices are Conversation (or C), MovingStanzaWindow (MSW, MS); default MovingStanzaWindow. Determines how stanzas are constructed, which defines how co-occurrences are modeled
window.size.back	A positive integer, Inf, or character (INF or Infinite), default: 1. Determines, for each line in the data frame, the number of previous lines in a conversation to include in the stanza window, which defines how co-occurrences are modeled
window.size.forward	(optional) A positive integer, Inf, or character (INF or Infinite), default: 0. Determines, for each line in the data frame, the number of subsequent lines in a conversation to include in the stanza window, which defines how co-occurrences are modeled
mask	(optional) A binary matrix of size ncol(codes) x ncol(codes). 0s in the mask matrix row i column j indicates that co-occurrence will not be modeled between code i and code j
include.meta	Logical indicating if unit metadata should be attached to the resulting ENAdata object, default is TRUE
as.list	R6 objects will be deprecated, but if this is TRUE, the original R6 object will be returned, otherwise a list with class 'ena.set'
...	additional parameters addressed in inner function

Details

ENADdata objects are created using this function. This accumulation receives separate data frames for units, codes, conversation, and optionally, metadata. It iterates through the data to create an adjacency (co-occurrence) vector corresponding to each unit - or in a trajectory model multiple adjacency (co-occurrence) vectors for each unit.

In the default MovingStanzaWindow model, co-occurrences between codes are calculated for each line k in the data between line k and the $\text{window.size.back}-1$ previous lines and $\text{window.size.forward}-1$ subsequent lines in the same conversation as line k .

In the Conversation model, co-occurrences between codes are calculated across all lines in each conversation. Adjacency (co-occurrence) vectors are constructed for each unit u by summing the co-occurrences for the lines that correspond to u .

Options for how the data is accumulated are endpoint, which produces one adjacency (co-occurrence) vector for each until summing the co-occurrences for all lines, and two trajectory models: AccumulatedTrajectory and SeparateTrajectory. Trajectory models produce an adjacency (co-occurrence) model for each conversation for each unit. In a SeparateTrajectory model, each conversation is modeled as a separate network. In an AccumulatedTrajectory model, the adjacency (co-occurrence) vector for the current conversation includes the co-occurrences from all previous conversations in the data.

Value

[ENadata](#) object with data [adjacency (co-occurrence) vectors] accumulated from the provided data frames.

See Also

[ENadata](#), [ena.make.set](#)

ena.conversations *Find conversations by unit*

Description

Find rows of conversations by unit

Usage

```
ena.conversations(  
  set,  
  units,  
  units.by = NULL,  
  codes = NULL,  
  conversation.by = NULL,  
  window = 4,  
  conversation.exclude = c()  
)
```

Arguments

set	[TBD]
units	[TBD]
units.by	[TBD]
codes	[TBD]
conversation.by	[TBD]
window	[TBD]
conversation.exclude	[TBD]

Details

[TBD]

Value

list containing row indices representing conversations

Examples

```

data(RS.data)

codeNames = c('Data','Technical.Constraints','Performance.Parameters',
              'Client.and.Consultant.Requests','Design.Reasoning',
              'Collaboration');

accum = ena.accumulate.data(
  units = RS.data[,c("Condition","UserName")],
  conversation = RS.data[,c("Condition","GroupName")],
  metadata = RS.data[,c("CONFIDENCE.Change","CONFIDENCE.Pre",
                        "CONFIDENCE.Post","C.Change")],
  codes = RS.data[,codeNames],
  model = "EndPoint",
  window.size.back = 4
);
set = ena.make.set(
  enadata = accum,
  rotation.by = ena.rotate.by.mean,
  rotation.params = list(accum$meta.data$Condition=="FirstGame",
                        accum$meta.data$Condition=="SecondGame")
);
ena.conversations(set = RS.data,
  units = c("FirstGame.steven z"), units.by=c("Condition","UserName"),
  conversation.by = c("Condition","GroupName"),
  codes=codeNames, window = 4
)

```

ena.correlations

Calculate the correlations

Description

Calculate both Spearman and Pearson correlations for the provided ENAset

Usage

```
ena.correlations(enaset, dims = c(1:2))
```

Arguments

enaset	ENAset to run correlations on
dims	The dimensions to calculate the correlations for. Default: c(1,2)

Value

Matrix of 2 columns, one for each correlation method, with the corresponding correlations per dimension as the rows.

ena.group	<i>Compute summary statistic for groupings of units using given method (typically, mean)</i>
-----------	--

Description

Computes summary statistics for groupings (given as vector) of units in ena data using given method (typically, mean); computes summary statistic for point locations and edge weights for each grouping

Usage

```
ena.group(
  enaset = NULL,
  by = NULL,
  method = mean,
  names = as.vector(unique(by))
)
```

Arguments

enaset	An ENASET or a vector of values to group.
by	A vector of values the same length as units. Uses rotated points for group positions and normed data to get the group edge weights
method	A function that is used on grouped points. Default: mean(). If 'enaset' is an ENASET, enaset\$points.rotated will be groups using 'mean' regardless of 'method' provided
names	A vector of names to use for the results. Default: unique(by)

Value

A list containing names, points, and edge weights for each of the unique groups formed by the function

Examples

```
data(RS.data)

codeNames = c('Data', 'Technical.Constraints', 'Performance.Parameters',
  'Client.and.Consultant.Requests', 'Design.Reasoning', 'Collaboration');

accum = ena.accumulate.data(
  units = RS.data[,c("UserName", "Condition")],
  conversation = RS.data[,c("Condition", "GroupName")],
  metadata = RS.data[,c("CONFIDENCE.Change", "CONFIDENCE.Pre", "CONFIDENCE.Post")],
  codes = RS.data[,codeNames],
  window.size.back = 4
```

```

)

set = ena.make.set(
  enadata = accum
)

means = ena.group(set, "Condition")

```

ena.make.set

Generate ENA Set

Description

Generates an ENA model by constructing a dimensional reduction of adjacency (co-occurrence) vectors in an ENA data object

Usage

```

ena.make.set(
  enadata,
  dimensions = 2,
  norm.by = fun_sphere_norm,
  rotation.by = ena.svd,
  rotation.params = NULL,
  rotation.set = NULL,
  endpoints.only = TRUE,
  center.align.to.origin = TRUE,
  node.position.method = lws.positions.sq,
  as.list = TRUE,
  ...
)

```

Arguments

enadata	ENadata that will be used to generate an ENA model
dimensions	The number of dimensions to include in the dimensional reduction
norm.by	A function to be used to normalize adjacency (co-occurrence) vectors before computing the dimensional reduction, default: <code>sphere_norm_c()</code>
rotation.by	A function to be used to compute the dimensional reduction, default: <code>ena.svd()</code>
rotation.params	(optional) A character vector containing additional parameters for the function in <code>rotation.by</code> , if needed
rotation.set	A previously-constructed <code>ENARotationSet</code> object to use for the dimensional reduction

<code>endpoints.only</code>	A logical variable which determines whether to only show endpoints for trajectory models
<code>center.align.to.origin</code>	A logical variable when TRUE (default) determines aligns both point center and centroid center to the origin
<code>node.position.method</code>	A function to be used to determine node positions based on the dimensional reduction, default: <code>lws.position.es()</code>
<code>as.list</code>	R6 objects will be deprecated, but if this is TRUE, the original R6 object will be returned, otherwise a list with class 'ena.set'
<code>...</code>	additional parameters addressed in inner function

Details

This function generates an ENAset object from an ENAdata object. Takes the adjacency (co-occurrence) vectors from enadata, computes a dimensional reduction (projection), and calculates node positions in the projected ENA space. Returns location of the units in the projected space, as well as locations for node positions, and normalized adjacency (co-occurrence) vectors to construct network graphs

Value

[ENAset](#) class object that can be further processed for analysis or plotting

See Also

[ena.accumulate.data](#), [ENAset](#)

Examples

```
data(RS.data)

codeNames = c('Data','Technical.Constraints','Performance.Parameters',
              'Client.and.Consultant.Requests','Design.Reasoning','Collaboration');

accum = ena.accumulate.data(
  units = RS.data[,c("UserName","Condition")],
  conversation = RS.data[,c("Condition","GroupName")],
  metadata = RS.data[,c("CONFIDENCE.Change","CONFIDENCE.Pre","CONFIDENCE.Post")],
  codes = RS.data[,codeNames],
  window.size.back = 4
)

set = ena.make.set(
  enadata = accum
)

set.means.rotated = ena.make.set(
  enadata = accum,
  rotation.by = ena.rotate.by.mean,
```

```

rotation.params = list(
  accum$meta.data$Condition=="FirstGame",
  accum$meta.data$Condition=="SecondGame"
)
)

```

ena.plot

Generate a plot of an ENAset

Description

Generates an a plot from a given ENA set object

Usage

```

ena.plot(
  enaset,
  title = "ENA Plot",
  dimension.labels = c("", ""),
  font.size = 10,
  font.color = "#000000",
  font.family = c("Arial", "Courier New", "Times New Roman"),
  scale.to = "network",
  ...
)

```

Arguments

enaset	The ENASET that will be used to generate a plot
title	A character used for the title of the plot, default: ENA Plot
dimension.labels	A character vector containing labels for the axes, default: c(X, Y)
font.size	An integer determining the font size for graph labels, default: 10
font.color	A character determining the color of label font, default: black
font.family	A character determining the font type, choices: Arial, Courier New, Times New Roman, default: Arial
scale.to	"network" (default), "points", or a list with x and y ranges. Network and points both scale to the c(-max, max) of the corresponding data.frame
...	additional parameters addressed in inner function

Details

This function defines the axes and other features of a plot for displaying an ENASET; generates an ENAPLOT object that can used to plot points, network graphs, and other information from an ENASET

Value

[ENApplot](#) used for plotting an ENAset

See Also

[ena.make.set](#), [ena.plot.points](#)

Examples

```

data(RS.data)

codeNames = c('Data', 'Technical.Constraints', 'Performance.Parameters',
  'Client.and.Consultant.Requests', 'Design.Reasoning', 'Collaboration');

accum = ena.accumulate.data(
  units = RS.data[,c("UserName", "Condition")],
  conversation = RS.data[,c("Condition", "GroupName")],
  metadata = RS.data[,c("CONFIDENCE.Change", "CONFIDENCE.Pre", "CONFIDENCE.Post")],
  codes = RS.data[,codeNames],
  window.size.back = 4
)

set = ena.make.set(
  enadata = accum
)

plot = ena.plot(set)

group1.points = set$points.rotated[set$enadata$units$Condition == "FirstGame",]
plot = ena.plot.points(plot, points = group1.points);
print(plot);

```

ena.plot.group

Plot of ENA set groups

Description

Plot a point based on a summary statistic computed from a given method (typically, mean) for a set of points in a projected ENA space

Usage

```

ena.plot.group(
  enaplot,
  points = NULL,
  method = "mean",
  labels = NULL,
  colors = default.colors[1],

```

```

shape = c("square", "triangle-up", "diamond", "circle"),
confidence.interval = c("none", "crosshairs", "box"),
outlier.interval = c("none", "crosshairs", "box"),
label.offset = "bottom right",
label.font.size = NULL,
label.font.color = NULL,
label.font.family = NULL,
show.legend = T,
legend.name = NULL,
...
)

```

Arguments

enaplot	ENApplot object to use for plotting
points	A matrix or data.frame where columns contain coordinates of points in a projected ENA space
method	A function for computing a summary statistic for each column of points
labels	A character which will be the label for the group's point
colors	A character, determines color of the group's point, default: enaplot\$color
shape	A character, determines shape of the group's point, choices: square, triangle, diamond, circle, default: square
confidence.interval	A character that determines how the confidence interval is displayed, choices: none, box, crosshair, default: none
outlier.interval	A character that determines how outlier interval is displayed, choices: none, box, crosshair, default: none
label.offset	character: top left (default), top center, top right, middle left, middle center, middle right, bottom left, bottom center, bottom right
label.font.size	An integer which determines the font size for label, default: enaplot\$font.size
label.font.color	A character which determines the color of label, default: enaplot\$font.color
label.font.family	A character which determines font type, choices: Arial, Courier New, Times New Roman, default: enaplot\$font.family
show.legend	Logical indicating whether to show the point labels in the in legend
legend.name	Character indicating the name to show above the plot legend
...	Additional parameters

Details

Plots a point based on a summary statistic for a group (typically, mean)

Value

The `ENApplot` provided to the function, with its plot updated to include the new group point.

See Also

`ena.plot`, `ena.plot.points`

Examples

```

data(RS.data)

codeNames = c('Data', 'Technical.Constraints', 'Performance.Parameters',
              'Client.and.Consultant.Requests', 'Design.Reasoning', 'Collaboration');

accum = ena.accumulate.data(
  units = RS.data[,c("UserName", "Condition")],
  conversation = RS.data[,c("Condition", "GroupName")],
  metadata = RS.data[,c("CONFIDENCE.Change", "CONFIDENCE.Pre", "CONFIDENCE.Post")],
  codes = RS.data[,codeNames],
  window.size.back = 4
)

set = ena.make.set(
  enadata = accum,
  rotation.by = ena.rotate.by.mean,
  rotation.params = list(
    accum$meta.data$Condition=="FirstGame",
    accum$meta.data$Condition=="SecondGame"
  )
)

plot = ena.plot(set)

unitNames = set$enadata$units

### Plot Condition 1 Group Mean
plot = ena.plot.group(plot, as.matrix(set$points$Condition$FirstGame), labels = "FirstGame",
  colors = "red", confidence.interval = "box")

### plot Condition 2 Group Mean
plot = ena.plot.group(plot, as.matrix(set$points$Condition$SecondGame), labels = "SecondGame",
  colors = "blue", confidence.interval = "box")

print(plot);

```

Description

Plot an ENA network: nodes and edges

Usage

```
ena.plot.network(
  enaplot = NULL,
  network = NULL,
  node.positions = enaplot$enaset$rotation$nodes,
  adjacency.key = NULL,
  colors = c(pos = enaplot$palette[1], enaplot$palette[2]),
  edge_type = "line",
  show.all.nodes = T,
  threshold = c(0),
  thin.lines.in.front = T,
  layers = c("nodes", "edges"),
  thickness = c(min(abs(network)), max(abs(network))),
  opacity = thickness,
  saturation = thickness,
  scale.range = c(ifelse(min(network) == 0, 0, 0.1), 1),
  node.size = c(3, 10),
  labels = NULL,
  label.offset = "middle right",
  label.font.size = enaplot$get("font.size"),
  label.font.color = enaplot$get("font.color"),
  label.font.family = enaplot$get("font.family"),
  legend.name = NULL,
  legend.include.edges = F,
  scale.weights = F,
  ...
)
```

Arguments

enaplot	ENApplot object to use for plotting
network	dataframe or matrix containing the edge weights for the network graph; typically comes from ENAset\$line.weights
node.positions	matrix containing the positions of the nodes. Defaults to enaplot\$enaset\$node.positions
adjacency.key	matrix containing the adjacency key for looking up the names and positions
colors	A String or vector of colors for positive and negative line weights. E.g. red or c(pos= red, neg = blue), default: c(pos= red, neg = blue)
edge_type	A String representing the type of line to draw, either "line", "dash", or "dot"
show.all.nodes	A Logical variable, default: true
threshold	A vector of numeric min/max values, default: c(0,Inf) plotting . Edge weights below the min value will not be displayed; edge weights above the max value will be shown at the max value.

thin.lines.in.front	A logical, default: true
layers	ordering of layers, default: c("nodes", "edges")
thickness	A vector of numeric min/max values for thickness, default: c(min(abs(network)), max(abs(network)))
opacity	A vector of numeric min/max values for opacity, default: thickness
saturation	A vector of numeric min/max values for saturation, default: thickness
scale.range	A vector of numeric min/max to scale from, default: c(0.1,1) or if min(network) is 0, c(0,1)
node.size	A lower and upper bound used for scaling the size of the nodes, default c(0, 20)
labels	A character vector of node labels, default: code names
label.offset	A character vector of representing the positional offset relative to the respective node. Defaults to "middle right" for all nodes. If a single values is provided, it is used for all positions, else the length of the
label.font.size	An integer which determines the font size for graph labels, default: enaplot\$font.size
label.font.color	A character which determines the color of label font, default: enaplot\$font.color
label.font.family	A character which determines font type, choices: Arial, Courier New, Times New Roman, default: enaplot\$font.family
legend.name	A character name used in the plot legend. Not included in legend when NULL (Default), if legend.include.edges is TRUE will always be "Nodes"
legend.include.edges	Logical value indicating if the edge names should be included in the plot legend. Forces legend.name to be "Nodes"
scale.weights	Logical indicating to scale the supplied network
...	Additional parameters

Details

lots a network graph, including nodes (taken from codes in the ENAplot) and the edges (provided in network)

Value

The ENAplot provided to the function, with its plot updated to include the nodes and provided connecting lines.

See Also

[ena.plot](#), [ena.plot.points](#)

Examples

```

data(RS.data)

codeNames = c('Data','Technical.Constraints','Performance.Parameters',
  'Client.and.Consultant.Requests','Design.Reasoning','Collaboration');

accum = ena.accumulate.data(
  units = RS.data[,c("UserName","Condition")],
  conversation = RS.data[,c("Condition","GroupName")],
  metadata = RS.data[,c("CONFIDENCE.Change","CONFIDENCE.Pre","CONFIDENCE.Post")],
  codes = RS.data[,codeNames],
  window.size.back = 4
)

set = ena.make.set(
  enadata = accum,
  rotation.by = ena.rotate.by.mean,
  rotation.params = list(
    accum$meta.data$Condition=="FirstGame",
    accum$meta.data$Condition=="SecondGame"
  )
)

plot = ena.plot(set)

### Subset rotated points and plot Condition 1 Group Mean
as.matrix(set$points$Condition$FirstGame)

first.game.points = as.matrix(set$points$Condition$FirstGame)
plot = ena.plot.group(plot, first.game.points, labels = "FirstGame",
  colors = "red", confidence.interval = "box")

### Subset rotated points and plot Condition 2 Group Mean
second.game.points = as.matrix(set$points$Condition$SecondGame)
plot = ena.plot.group(plot, second.game.points, labels = "SecondGame",
  colors = "blue", confidence.interval = "box")

### get mean network plots
first.game.lineweights = as.matrix(set$line.weights$Condition$FirstGame)
first.game.mean = colMeans(first.game.lineweights)

second.game.lineweights = as.matrix(set$line.weights$Condition$SecondGame)
second.game.mean = colMeans(second.game.lineweights)

subtracted.network = first.game.mean - second.game.mean
plot = ena.plot.network(plot, network = subtracted.network)
print(plot)

```

Description

Plot all or a subset of the points of an ENAplot using the plotly plotting library

Usage

```
ena.plot.points(
  enaplot,
  points = NULL,
  point.size = enaplot$point.size,
  labels = NULL,
  label.offset = "top left",
  label.group = NULL,
  label.font.size = NULL,
  label.font.color = NULL,
  label.font.family = NULL,
  shape = "circle",
  colors = NULL,
  confidence.interval.values = NULL,
  confidence.interval = c("none", "crosshairs", "box"),
  outlier.interval.values = NULL,
  outlier.interval = c("none", "crosshairs", "box"),
  show.legend = T,
  legend.name = "Points",
  texts = NULL,
  ...
)
```

Arguments

enaplot	ENApplot object to use for plotting
points	A dataframe of matrix where the first two column are X and Y coordinates
point.size	A data.frame or matrix where the first two column are X and Y coordinates of points to plot in a projected ENA space defined in ENAplot
labels	A character vector of point labels, length nrow(points); default: NULL
label.offset	character: top left (default), top center, top right, middle left, middle center, middle right, bottom left, bottom center, bottom right
label.group	A string used to group the labels in the legend. Items plotted with the same label.group will show/hide together when clicked within the legend.
label.font.size	An integer which determines the font size for point labels, default: enaplot\$font.size
label.font.color	A character which determines the color of label font, default: enaplot\$font.color
label.font.family	A character which determines label font type, choices: Arial, Courier New, Times New Roman, default: enaplot\$font.family

shape	A character which determines the shape of point markers, choices: square, triangle, diamond, circle, default: circle
colors	A character vector of the point marker colors; if one given it is used for all, otherwise must be same length as points; default: black
confidence.interval.values	A matrix/dataframe where columns are CI x and y values for each point
confidence.interval	A character determining markings to use for confidence intervals, choices: none, box, crosshair, default: none
outlier.interval.values	A matrix/dataframe where columns are OI x and y values for each point
outlier.interval	A character determining markings to use for outlier interval, choices: none, box, crosshair, default: none
show.legend	Logical indicating whether to show the point labels in the in legend
legend.name	Character indicating the name to show above the plot legend
texts	[TBD]
...	additional parameters addressed in inner function

Value

[ENApplot](#) The ENApplot provided to the function, with its plot updated to include the new points.

See Also

[ena.plot](#), [ENApplot](#), [ena.plot.group](#)

Examples

```

data(RS.data)

codeNames = c('Data','Technical.Constraints','Performance.Parameters',
              'Client.and.Consultant.Requests','Design.Reasoning','Collaboration');

accum = ena.accumulate.data(
  units = RS.data[,c("UserName","Condition")],
  conversation = RS.data[,c("Condition","GroupName")],
  metadata = RS.data[,c("CONFIDENCE.Change","CONFIDENCE.Pre","CONFIDENCE.Post")],
  codes = RS.data[,codeNames],
  window.size.back = 4
)

set = ena.make.set(
  enadata = accum,
  rotation.by = ena.rotate.by.mean,
  rotation.params = list(
    accum$meta.data$Condition=="FirstGame",
    accum$meta.data$Condition=="SecondGame"
  )
)

```

```

    )
  )

  plot = ena.plot(set)

  group1.points = set$points[set$meta.data$Condition == "FirstGame",]
  group2.points = set$points[set$meta.data$Condition == "SecondGame",]
  plot = ena.plot.points(plot, points = group1.points);
  plot = ena.plot.points(plot, points = group2.points);
  print(plot);

```

ena.plot.trajectory *Plot of ENA trajectories*

Description

Function used to plot trajectories

Usage

```

ena.plot.trajectory(
  enaplot,
  points,
  by = NULL,
  labels = NULL,
  labels.show = c("Always", "Hover", "Both"),
  names = NULL,
  label.offset = NULL,
  label.font.size = enaplot$get("font.size"),
  label.font.color = enaplot$get("font.color"),
  label.font.family = c("Arial", "Courier New", "Times New Roman"),
  shape = c("circle", "square", "triangle-up", "diamond"),
  colors = NULL,
  default.hidden = F
)

```

Arguments

enaplot	ENApplot object to use for plotting
points	dataframe of matrix - first two column are X and Y coordinates, each row is a point in a trajectory
by	vector used to subset points into individual trajectories, length nrow(points)
labels	character vector - point labels, length nrow(points)
labels.show	A character choice: Always, Hover, Both. Default: Both
names	character vector - labels for each trajectory of points, length length(unique(by))

label.offset	A numeric vector of an x and y value to offset labels from the coordinates of the points
label.font.size	An integer which determines the font size for labels, default: enaplot\font.size
label.font.color	A character which determines the color of label font, default: enaplot\font.color
label.font.family	A character which determines font type, choices: Arial, Courier New, Times New Roman, default: enaplot\font.family
shape	A character which determines the shape of markers, choices: square, triangle, diamond, circle, default: circle
colors	A character vector, that determines marker color, default NULL results in alternating random colors. If single color is supplied, it will be used for all trajectories, otherwise the length of the supplied color vector should be equal to the length of the supplied names (i.e a color for each trajectory being plotted)
default.hidden	A logical indicating if the trajectories should start hidden (click on the legend to show them) Default: FALSE

Value

The [ENaplot](#) provided to the function, with its plot updated to include the trajectories

See Also

[ena.plot](#)

Examples

```

data(RS.data)

codeNames = c('Data','Technical.Constraints','Performance.Parameters',
              'Client.and.Consultant.Requests','Design.Reasoning','Collaboration');

accum = ena.accumulate.data(
  units = RS.data[,c("UserName","Condition")],
  conversation = RS.data[,c("GroupName","ActivityNumber")],
  metadata = RS.data[,c("CONFIDENCE.Change","CONFIDENCE.Pre","CONFIDENCE.Post","C.Change")],
  codes = RS.data[,codeNames],
  window.size.back = 4,
  model = "A"
);

set = ena.make.set(accum);

### get mean network plots
first.game.lineweights = as.matrix(set$line.weights$Condition$FirstGame)
first.game.mean = colMeans(first.game.lineweights)

second.game.lineweights = as.matrix(set$line.weights$Condition$SecondGame)

```



```

second.game.mean = colMeans(second.game.lineweights)

subtracted.network = first.game.mean - second.game.mean

# Plot dimension 1 against ActivityNumber metadata
dim.by.activity = cbind(
  as.matrix(set$points)[,1],
  set$trajectories$ActivityNumber * .8/14-.4 #scale down to dimension 1
)

plot = ena.plot(set)
plot = ena.plot.network(plot, network = subtracted.network, legend.name="Network")
plot = ena.plot.trajectory(
  plot,
  points = dim.by.activity,
  names = unique(set$model$unit.label),
  by = set$trajectories$ENA_UNIT
);
print(plot)

```

ena.plotter

Wrapper to generate plots of units, groups, and networks

Description

Plots individual units, all units, groups of units, networks, and network subtractions

Usage

```

ena.plotter(
  set,
  groupVar = NULL,
  groups = NULL,
  points = FALSE,
  mean = FALSE,
  network = TRUE,
  networkMultiplier = 1,
  subtractionMultiplier = 1,
  unit = NULL,
  print.plots = F,
  ...
)

```

Arguments

set	an ena.set object
groupVar	vector, character, of column name containing group identifiers.

groups	vector, character, of values of groupVar column you wish to plot. Maxium of two groups allowed.
points	logical, TRUE will plot points (default: FALSE)
mean	logical, TRUE will plot the mean position of the groups defined in the groups argument (default: FALSE)
network	logical, TRUE will plot networks (default: TRUE)
networkMultiplier	numeric, scaling factor for non-subtracted networks (default: 1)
subtractionMultiplier	numeric, scaling factor for subtracted networks (default: 1)
unit	vector, character, name of a single unit to plot
print.plots	logical, TRUE will show plots in the Viewer (default: FALSE)
...	Additional parameters passed to set creation and plotting functions

Details

This function includes options to plots individual units, all units, groups of units, networks, and network subtractions, given an ena.set objects. Plots are stored on the supplied ena.set object.

Value

ena.set object

ena.rotate.by.mean *ENA Rotate by mean*

Description

Computes a dimensional reduction from a matrix of points such that the first dimension of the projected space passes through the means of two groups in a the original space. Subsequent dimensions of the projected space are computed using ena.svd

Usage

```
ena.rotate.by.mean(enaset, groups)
```

Arguments

enaset	An ENaset
groups	A list containing two logical vectors of length nrow(ENA.set\$ena.data\$units), where each vector defines whether a unit is in one of the two groups whose means are used to determine the dimensional reduction

Value

[ENARotationSet](#)

ena.set.creator

*Wrapper to generate an ENA model***Description**

Generates an ENA model by constructing a dimensional reduction of adjacency (co-occurrence) vectors as defined by the supplied conversations, units, and codes.

Usage

```
ena.set.creator(
  data,
  codes,
  units,
  conversation,
  metadata = NULL,
  model = c("EndPoint", "AccumulatedTrajectory", "SeparateTrajectory"),
  weight.by = "binary",
  window = c("MovingStanzaWindow", "Conversation"),
  window.size.back = 1,
  include.meta = TRUE,
  groupVar = NULL,
  groups = NULL,
  runTest = FALSE,
  ...
)
```

Arguments

data	data.frame with containing metadata and coded columns
codes	vector, numeric or character, of columns with codes
units	vector, numeric or character, of columns representing units
conversation	vector, numeric or character, of columns to segment conversations by
metadata	vector, numeric or character, of columns with additional meta information for units
model	character: EndPoint (default), AccumulatedTrajectory, SeparateTrajectory
weight.by	"binary" is default, can supply a function to call (e.g. sum)
window	MovingStanzaWindow (default) or Conversation
window.size.back	Number of lines in the stanza window (default: 1)
include.meta	[TBD]
groupVar	vector, character, of column name containing group identifiers. If column contains at least two unique values, will generate model using a means rotation (a dimensional reduction maximizing the variance between the means of the two groups)

groups	vector, character, of values of groupVar column used for means rotation or statistical tests
runTest	logical, TRUE will run a Student's t-Test and a Wilcoxon test for groups defined by the groups argument
...	Additional parameters passed to model generation

Details

This function generates an ena.set object given a data.frame, units, conversations, and codes. After accumulating the adjacency (co-occurrence) vectors, computes a dimensional reduction (projection), and calculates node positions in the projected ENA space. Returns location of the units in the projected space, as well as locations for node positions, and normalized adjacency (co-occurrence) vectors to construct network graphs. Includes options for returning statistical tests between groups of units.

Value

ena.set object

ena.svd	<i>ENA SVD</i>
---------	----------------

Description

ENA method computing a dimensional reduction of points in an ENA set using SVD

Usage

```
ena.svd(enaset, ...)
```

Arguments

enaset	An ENAsset
...	Unused, necessary for ena.make.set

ena.writeup	<i>Calculate the correlations</i>
-------------	-----------------------------------

Description

Calculate both Spearman and Pearson correlations for the provided ENAset

Usage

```
ena.writeup(
  enaset,
  tool = "rENA",
  tool.version = as.character(packageVersion(tool)),
  comparison = NULL,
  comparison.groups = NULL,
  sig.dig = 2,
  output_dir = getwd(),
  type = c("file", "stream"),
  theory = T,
  methods = T,
  params = NULL,
  output_file = NULL,
  output_format = NULL
)
```

Arguments

enaset	ENAset to view methods of
tool	c("rENA","webENA")
tool.version	as.character(packageVersion(tool))
comparison	character string representing the comparison used, c(NULL, "parametric", "non-parametric"). Default NULL
comparison.groups	Groups that were used for the comparison
sig.dig	Integer for the number of digits to round to
output_dir	Where to save the output file
type	c("file","stream") File will save to a file in output_dir, Stream returns the contents directly
theory	Logical indicating whether to include theory in the writeup
methods	Logical indicating whether to include methods in the writeup
params	additional parameters for rmarkdown::render
output_file	character
output_format	character

Value

String representing the methods used to generate the model

 ENAdata

ENAdata R6class

Description

ENAdata R6class

ENAdata R6class

Public fields

`raw` A data frame constructed from the unit, convo, code, and metadata parameters of `ena.accumulate.data`

`adjacency.vectors` A data frame of adjacency (co-occurrence) vectors by row

`accumulated.adjacency.vectors` A data frame of adjacency (co-occurrence) vectors accumulated per unit

`model` The type of ENA model: EndPoint, Accumulated Trajectory, or Separate Trajectory

`units` A data frame of columns that were combined to make the unique units. Includes column for trajectory selections. (unique)

`unit.names` A vector of unique unit values

`metadata` A data frame of unique metadata for each unit

`trajectories` A list: units - data frame, for a given row tells which trajectory it's a part; step - data frame, where along the trajectory a row sits

`adjacency.matrix` TBD

`adjacency.vectors.raw` TBD

`codes` A vector of code names

`function.call` The string representation of function called and parameters provided

`function.params` A list of all parameters sent to function call Construct ENAdata

Methods**Public methods:**

- [ENAdata\\$new\(\)](#)
- [ENAdata\\$process\(\)](#)
- [ENAdata\\$get\(\)](#)
- [ENAdata\\$add.metadata\(\)](#)
- [ENAdata\\$clone\(\)](#)

Method `new()`:

Usage:

```
ENadata$new(  
  file,  
  units = NULL,  
  units.used = NULL,  
  units.by = NULL,  
  conversations.by = NULL,  
  codes = NULL,  
  model = NULL,  
  weight.by = "binary",  
  window.size.back = 1,  
  window.size.forward = 0,  
  mask = NULL,  
  include.meta = T,  
  ...  
)
```

Arguments:

file TBD
units TBD
units.used TBD
units.by TBD
conversations.by TBD
codes TBD
model TBD
weight.by TBD
window.size.back TBD
window.size.forward TBD
mask TBD
include.meta TBD
... TBD

Returns: Process accumulation

Method process():

Usage:

```
ENadata$process()
```

Returns: ENadata Get property from object

Method get():

Usage:

```
ENadata$get(x = "data")
```

Arguments:

x character key to retrieve from object

Returns: value from object at x Add metadata

Method add.metadata():

Usage:

```
ENadata$add.metadata(merge = F)
```

Arguments:

```
merge logical (default: FALSE)
```

Returns: data.frame

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
ENadata$clone(deep = FALSE)
```

Arguments:

```
deep Whether to make a deep clone.
```

 ENApplot

ENaset R6class

Description

ENaset R6class

ENaset R6class

Public fields

`enaset` - The [ENaset](#) object from which the ENApplot was constructed

`plot` - The plotly object used for data visualization

`axes` - TBD

`point` - TBD

`palette` - TBD

`plotted` - TBD Create ENApplot

Methods**Public methods:**

- [ENApplot\\$new\(\)](#)
- [ENApplot\\$print\(\)](#)
- [ENApplot\\$get\(\)](#)
- [ENApplot\\$clone\(\)](#)

Method `new()`:

Usage:


```
ENApLOT$new(  
  enaset = NULL,  
  title = "ENA Plot",  
  dimension.labels = c("", ""),  
  font.size = 14,  
  font.color = "#000000",  
  font.family = "Arial",  
  scale.to = "network",  
  ...  
)
```

Arguments:

enaset TBD

title TBD

dimension.labels TBD

font.size TBD

font.color TBD

font.family TBD

scale.to TBD

... TBD

showticklabels TBD

autosize TBD

automargin TBD

axispadding TBD

Returns: ENApLOT Print ENA plot

Method print():

Usage:

```
ENApLOT$print()
```

Returns: Get property from object

Method get():

Usage:

```
ENApLOT$get(x)
```

Arguments:

x character key to retrieve from object

Returns: value from object at x

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
ENApLOT$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

ENARotationSet *ENARotationSet R6class*

Description

ENARotationSet R6class

ENARotationSet R6class

Public fields

rotation TBD

node.positions TBD

codes TBD

eigenvalues TBD Create ENARotationSet

Methods

Public methods:

- [ENARotationSet\\$new\(\)](#)
- [ENARotationSet\\$clone\(\)](#)

Method new():

Usage:

ENARotationSet\$new(rotation, codes, node.positions, eigenvalues = NULL)

Arguments:

rotation TBD

codes TBD

node.positions TBD

eigenvalues TBD

Returns: ENARotationsSet

Method clone(): The objects of this class are cloneable with this method.

Usage:

ENARotationSet\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

ENAsset

*ENAsset R6class***Description**

ENAsset R6class

ENAsset R6class

Public fields

`enadata` An [ENadata](#) object originally used to create the set
`points.raw` A data frame containing accumulated adjacency (co-occurrence) vectors per unit
`points.normed.centered` A data frame of centered normed accumulated adjacency (co-occurrence) vectors for each unit
`points.rotated` A data frame of point positions for number of dimensions specified in `ena.make.set` (i.e., the centered, normed, and rotated data)
`line.weights` A data frame of connections strengths per unit (Data frame of normed accumulated adjacency (co-occurrence) vectors for each unit)
`node.positions` - A data frame of positions for each code
`codes` - A vector of code names
`rotation.set` - An [ENARotationSet](#) object
`variance` - A vector of variance accounted for by each dimension specified
`centroids` - A matrix of the calculated centroid positions
`function.call` - The string representation of function called
`function.params` - A list of all parameters sent to function call
`rotation_dists` TBD
`points.rotated.scaled` TBD
`points.rotated.non.zero` TBD
`line.weights.unrotated` TBD
`line.weights.non.zero` TBD
`correlations` A data frame of spearman and pearson correlations for each dimension specified
`center.align.to.origin` - align point and centroid centers to origin Create ENAsset

Methods**Public methods:**

- [ENAsset\\$new\(\)](#)
- [ENAsset\\$process\(\)](#)
- [ENAsset\\$get\(\)](#)
- [ENAsset\\$clone\(\)](#)

Method new():*Usage:*

```
ENASET$new(
  enadata,
  dimensions = 2,
  norm.by = fun_sphere_norm,
  rotation.by = ena.svd.R6,
  rotation.params = NULL,
  rotation.set = NULL,
  node.position.method = lws.positions.sq.R6,
  endpoints.only = TRUE,
  center.align.to.origin = TRUE,
  ...
)
```

Arguments:

```
enadata TBD
dimensions TBD
norm.by TBD
rotation.by TBD
rotation.params TBD
rotation.set TBD
node.position.method TBD
endpoints.only TBD
center.align.to.origin TBD
... TBD
```

Returns: ENASET Process ENASET**Method process():***Usage:*

```
ENASET$process()
```

Returns: ENASET Get property from object**Method get():***Usage:*

```
ENASET$get(x = "enadata")
```

Arguments:

```
x character key to retrieve from object
```

Returns: value from object at x**Method clone():** The objects of this class are cloneable with this method.*Usage:*

```
ENASET$clone(deep = FALSE)
```

Arguments:

```
deep Whether to make a deep clone.
```

ena_correlation	<i>Calculate the correlations</i>
-----------------	-----------------------------------

Description

Calculate both Pearson correlations for the provided points and centroids

Usage

```
ena_correlation(points, centroids, conf_level = 0.95)
```

Arguments

points	TBD
centroids	TBD
conf_level	TBD

find_code_cols	<i>Find code columns</i>
----------------	--------------------------

Description

Find code columns

Usage

```
find_code_cols(x)
```

Arguments

x	data.table (or frame) to search for columns of class ena.co.occurrence
---	--

Value

logical vector

find_dimension_cols *Find dimension columns*

Description

Find dimension columns

Usage

```
find_dimension_cols(x)
```

Arguments

x data.table (or frame) to search for columns of class ena.dimension

Value

logical vector

find_meta_cols *Find metadata columns*

Description

Find metadata columns

Usage

```
find_meta_cols(x)
```

Arguments

x data.table (or frame) to search for columns of class ena.metadata

Value

logical vector

fun_cohens.d	<i>Cohen's d</i>
--------------	------------------

Description

Calculate Conhen's d

Usage

fun_cohens.d(x, y)

Arguments

x [TBD]

y [TBD]

Details

Cohen's d calculation

[TBD]

Value

numeric Cohen's d calculation

fun_skip_sphere_norm	<i>Non sphere norm</i>
----------------------	------------------------

Description

TBD

Usage

fun_skip_sphere_norm(dfM)

Arguments

dfM Dataframe

Details

Non sphere norm

fun_sphere_norm	<i>Sphere norm</i>
-----------------	--------------------

Description

TBD

Usage

fun_sphere_norm(dfM)

Arguments

dfM Dataframe

Details

Sphere norm

means_rotate	<i>Title</i>
--------------	--------------

Description

Title

Usage

means_rotate(x, on = NULL)

Arguments

x [TBD]

on [TBD]

Value

TBD

merge_columns_c	<i>Merge data frame columns</i>
-----------------	---------------------------------

Description

TBD

Usage

```
merge_columns_c(df, cols, sep = ".")
```

Arguments

df	Dataframe
cols	Vector
sep	Character seperator

Details

Merge data frame columns

methods_report	<i>methods_report</i>
----------------	-----------------------

Description

Methods report for rmarkdwon

Usage

```
methods_report(  
  toc = FALSE,  
  toc_depth = 3,  
  fig_width = 5,  
  fig_height = 4,  
  keep_md = FALSE,  
  md_extensions = NULL,  
  pandoc_args = NULL  
)
```

Arguments

toc	[TBD]
toc_depth	[TBD]
fig_width	[TBD]
fig_height	[TBD]
keep_md	[TBD]
md_extensions	[TBD]
pandoc_args	[TBD]

methods_report_stream *methods_report_stream*

Description

Methods report for rmarkdwon

Usage

```
methods_report_stream(  
  toc = FALSE,  
  toc_depth = 3,  
  fig_width = 5,  
  fig_height = 4,  
  keep_md = FALSE,  
  md_extensions = NULL,  
  pandoc_args = NULL  
)
```

Arguments

toc	[TBD]
toc_depth	[TBD]
fig_width	[TBD]
fig_height	[TBD]
keep_md	[TBD]
md_extensions	[TBD]
pandoc_args	[TBD]

move_nodes_to_unit_circle
Title

Description

Title

Usage

```
move_nodes_to_unit_circle(set, dimension_name_1, dimension_name_2)
```

Arguments

```
set          TBD
dimension_name_1
dimension_name_2  TBD
              TBD
```

Value

TBD

move_nodes_to_unit_circle_with_equal_space
Title

Description

Title

Usage

```
move_nodes_to_unit_circle_with_equal_space(  
  set,  
  dimension_name_1,  
  dimension_name_2  
)
```

Arguments

```
set          TBD
dimension_name_1
              TBD
dimension_name_2
              TBD
```

Value

TBD

namesToAdjacencyKey *Names to Adjacency Key*

Description

Convert a vector of strings, representing names of a square matrix, to an adjacency

Usage

```
namesToAdjacencyKey(vector, upper_triangle = TRUE)
```

Arguments

vector Vector representing the names of a square matrix
upper_triangle Not Implemented

Details

Returns a matrix of 2 rows by choose(length(vector), 2) columns

plot.ena.set *Plot an ena.set object*

Description

Plot an ena.set object

Usage

```
## S3 method for class 'ena.set'  
plot(x, y, ...)
```

Arguments

x ena.set to plot
y ignored.
... Additional parameters passed along to ena.plot functions

Value

ena.plot.object

Examples

```

library(magrittr)

data(RS.data)

codeNames = c('Data','Technical.Constraints','Performance.Parameters',
              'Client.and.Consultant.Requests','Design.Reasoning','Collaboration');

accum = ena.accumulate.data(
  units = RS.data[,c("UserName","Condition")],
  conversation = RS.data[,c("Condition","GroupName")],
  metadata = RS.data[,c("CONFIDENCE.Change","CONFIDENCE.Pre","CONFIDENCE.Post")],
  codes = RS.data[,codeNames],
  window.size.back = 4
)

set = ena.make.set(
  enadata = accum
)

plot(set) %>%
  add_points(Condition$FirstGame, colors = "blue", with.mean = TRUE) %>%
  add_points(Condition$SecondGame, colors = "red", with.mean = TRUE)

plot(set) %>%
  add_network(Condition$FirstGame - Condition$SecondGame)

```

```
prepare_trajectory_data
```

Title

Description

Title

Usage

```

prepare_trajectory_data(
  x = NULL,
  by = x$`_function.params`$conversation[1],
  rotation_matrix = x$rotation.matrix,
  points = NULL,
  units = points,
  units_by = x$`_function.params`$units,
  steps = NULL
)

```

Arguments

x	[TBD]
by	[TBD]
rotation_matrix	[TBD]
points	[TBD]
units	[TBD]
units_by	[TBD]
steps	[TBD]

Value

TBD

print.ena.set	<i>Title</i>
---------------	--------------

Description

Title

Usage

```
## S3 method for class 'ena.set'
print(x, ..., plot = FALSE, set = TRUE)
```

Arguments

x	[TBD]
...	[TBD]
plot	[TBD]
set	[TBD]

Value

TBD

project_in	<i>Title</i>
------------	--------------

Description

Title

Usage

project_in(x, by = NULL, ...)

Arguments

x	[TBD]
by	[TBD]
...	[TBD]

Value

TBD

remove_meta_data	<i>Remove meta columns from data.table</i>
------------------	--

Description

Remove meta columns from data.table

Usage

remove_meta_data(x)

Arguments

x	[TBD]
---	-------

Value

data.table with the columns of class ena.meta.data removed

rENA	<i>rENA creates ENA sets</i>
------	------------------------------

Description

rENA is used to create and visualize network models of discourse and other phenomena from coded data using Epistemic Network Analysis (ENA). A more complete description of the methods will be provided with the next release. See also XXXXX

RS.data	<i>Coded Rescushell Chat Data</i>
---------	-----------------------------------

Description

A dataset containing sample chat data from the Rescushell Virtual Internship

Usage

RS.data

Format

An object of class `data.frame` with 3824 rows and 20 columns.

scale.ena.set	<i>Title</i>
---------------	--------------

Description

Title

Usage

```
## S3 method for class 'ena.set'
scale(x, center = TRUE, scale = TRUE)
```

Arguments

x	[TBD]
center	Ignored.
scale	[TBD]

Value

TBD

show	<i>Title</i>
------	--------------

Description

Title

Usage

show(x, ...)

Arguments

x [TBD]

... [TBD]

Value

TBD

vector_to_ut	<i>vector to upper triangle</i>
--------------	---------------------------------

Description

TBD

Usage

vector_to_ut(v)

Arguments

v [TBD]

Details

Upper Triangle from Vector

with_means	<i>Title</i>
------------	--------------

Description

Title

Usage

```
with_means(x)
```

Arguments

x	[TBD]
---	-------

Value

TBD

with_trajectory	<i>Title</i>
-----------------	--------------

Description

Title

Usage

```
with_trajectory(
  x,
  ...,
  by = x$`_function.params`$conversation[1],
  add_jitter = TRUE,
  frame = 1100,
  transition = 1000,
  easing = "circle-in-out"
)
```

Arguments

x	[TBD]
...	[TBD]
by	[TBD]
add_jitter	[TBD]
frame	[TBD]
transition	[TBD]
easing	[TBD]

Value

TBD

\$.ena.matrix *Extract from ena.matrix easily using metadata*

Description

Extract from ena.matrix easily using metadata

Usage

```
## S3 method for class 'ena.matrix'  
x$i
```

Arguments

x	[TBD]
i	[TBD]

Value

TBD

\$.ena.metadata *Extract metadata easily*

Description

Extract metadata easily

Usage

```
## S3 method for class 'ena.metadata'  
x$i
```

Arguments

x	[TBD]
i	[TBD]

Value

TBD

\$.ena.points *Extract points easily*

Description

Extract points easily

Usage

```
## S3 method for class 'ena.points'  
x$i
```

Arguments

x	[TBD]
i	[TBD]

Value

TBD

\$.line.weights *Extract line.weights easily*

Description

Extract line.weights easily

Usage

```
## S3 method for class 'line.weights'  
x$i
```

Arguments

x	[TBD]
i	[TBD]

Value

TBD

Index

* datasets

- RS.data, 56
- \$.ena.matrix, 59
- \$.ena.metadata, 59
- \$.ena.points, 60
- \$.line.weights, 60

- add_group, 3
- add_network, 4
- add_nodes, 4
- add_points, 5
- add_trajectory, 5
- as.ena.co.occurrence, 6
- as.ena.matrix, 6
- as.ena.metadata, 7
- as.matrix.ena.connections, 7
- as.matrix.ena.line.weights, 8
- as.matrix.ena.matrix, 8
- as.matrix.ena.nodes, 9
- as.matrix.ena.points, 9
- as.matrix.ena.rotation.matrix, 10
- as.matrix.row.connections, 10
- as_trajectory, 11

- clear, 11
- combn_c2, 12
- connection.matrix, 12

- ena, 13
- ena.accumulate.data, 15, 21
- ena.conversations, 17
- ena.correlations, 18
- ena.group, 19
- ena.make.set, 17, 20, 23
- ena.plot, 22, 25, 27, 30, 32
- ena.plot.group, 23, 30
- ena.plot.network, 25
- ena.plot.points, 23, 27, 28
- ena.plot.trajectory, 31
- ena.plotter, 33

- ena.rotate.by.mean, 34
- ena.set.creator, 35
- ena.svd, 36
- ena.writeup, 37
- ena_correlation, 45
- ENAdata, 17, 20, 38, 43
- ENApplot, 23–27, 29–32, 40
- ENARotationSet, 34, 42, 43
- ENAsset, 19, 21, 22, 34, 36, 40, 43

- find_code_cols, 45
- find_dimension_cols, 46
- find_meta_cols, 46
- fun_cohens.d, 47
- fun_skip_sphere_norm, 47
- fun_sphere_norm, 48

- means_rotate, 48
- merge_columns_c, 49
- methods_report, 49
- methods_report_stream, 50
- move_nodes_to_unit_circle, 51
- move_nodes_to_unit_circle_with_equal_space, 51

- namesToAdjacencyKey, 52

- plot.ena.set, 52
- prepare_trajectory_data, 53
- print.ena.set, 54
- project_in, 55

- remove_meta_data, 55
- rENA, 56
- RS.data, 56

- scale.ena.set, 56
- show, 57

- vector_to_ut, 57

- with_means, 58
- with_trajectory, 58