

Package ‘sentopics’

October 14, 2022

Type Package

Title Tools for Joint Sentiment and Topic Analysis of Textual Data

Version 0.7.1

Date 2022-05-17

Maintainer Olivier Delmarcelle <delmarcelle.olivier@gmail.com>

Description A framework that joins topic modeling and sentiment analysis of textual data. The package implements a fast Gibbs sampling estimation of Latent Dirichlet Allocation (Griffiths and Steyvers (2004) <[doi:10.1073/pnas.0307752101](https://doi.org/10.1073/pnas.0307752101)>) and Joint Sentiment/Topic Model (Lin, He, Everson and Ruger (2012) <[doi:10.1109/TKDE.2011.48](https://doi.org/10.1109/TKDE.2011.48)>). It offers a variety of helpers and visualizations to analyze the result of topic modeling. The framework also allows enriching topic models with dates and externally computed sentiment measures. A flexible aggregation scheme enables the creation of time series of sentiment or topical proportions from the enriched topic models. Moreover, a novel method jointly aggregates topic proportions and sentiment measures to derive time series of topical sentiment.

License GPL (>= 3)

BugReports <https://github.com/odelmarcelle/sentopics/issues>

URL <https://github.com/odelmarcelle/sentopics>

Encoding UTF-8

Depends R (>= 3.5.0)

Imports Rcpp (>= 1.0.4.6), methods, quanteda (>= 3.2.0), data.table (>= 1.13.6), RcppHungarian

Suggests ggplot2, ggridges, plotly, RColorBrewer, xts, zoo, future, future.apply, progressr, progress, testthat, covr, stm, lda, topicmodels, seededlda, LDAvis, servr, textcat, stringr, sentometrics, spacyr, knitr, rmarkdown, webshot

LinkingTo Rcpp, RcppArmadillo, RcppProgress

RcppModules model_module

RoxygenNote 7.1.2

LazyData true

SystemRequirements C++11

VignetteBuilder knitr

NeedsCompilation yes

Author Olivier Delmarcelle [aut, cre]

(<<https://orcid.org/0000-0003-4347-070X>>),

Samuel Borms [ctb] (<<https://orcid.org/0000-0001-9533-1870>>),

Chengua Lin [cph] (Original JST implementation),

Yulan He [cph] (Original JST implementation),

Jose Bernardo [cph] (Original JST implementation),

David Robinson [cph] (Implementation of reorder_within()),

Julia Silge [cph] (Implementation of reorder_within()),

<<https://orcid.org/0000-0002-3671-836X>>

Repository CRAN

Date/Publication 2022-05-18 13:20:02 UTC

R topics documented:

sentopics-package	3
as.LDA	4
as.tokens.dfm	6
chainsDistances	7
chainsScores	8
coherence	9
compute_PicaultRenault_scores	11
ECB_press_conferences	12
ECB_press_conferences_tokens	13
get_ECB_press_conferences	14
get_ECB_speeches	14
grow	15
JST	16
LDA	18
LDavis	19
LoughranMcDonald	20
melt	21
melt.sentopicmodel	22
mergeTopics	23
PicaultRenault	24
PicaultRenault_data	25
plot.multiChains	26
plot.sentopicmodel	27
print.sentopicmodel	28
proportion_topics	28
reset	30
rJST	31
sentiment_breakdown	33

sentiment_series	35
sentiment_topics	36
sentopics_date	39
sentopics_labels	40
sentopics_sentiment	41
topWords	43

Index	46
--------------	-----------

sentopics-package	<i>Tools for joining sentiment and topic analysis (sentopics)</i>
-------------------	---

Description

sentopics provides function to easily estimate a range of topic models and process their output. Particularly, it facilitates the integration of topic analysis with a time dimension through time-series generating functions. In addition, **sentopics** interacts with sentiment analysis to compute the sentiment conveyed by topics. Finally, the package implements a number of visualization helping interpreting the results of topic models.

Usage

Please refer to the vignettes for a comprehensive introduction to the package functions.

- **Basic usage:** Introduction to topic model estimation with **sentopics**
- **Topical time series:** Integrate topic analysis with sentiment analysis along a time dimension

For further details, you may browse the package [documentation](#).

Note

Please cite the package in publications. Use `citation("sentopics")`.

Author(s)

Maintainer: Olivier Delmarcelle <delmarcelle.olivier@gmail.com> ([ORCID](#))

Other contributors:

- Samuel Borms <samuel.borms@unine.ch> ([ORCID](#)) [contributor]
- Chenghua Lin <chenghua.lin@abdn.ac.uk> (Original JST implementation) [copyright holder]
- Yulan He <yulan.he@warwick.ac.uk> (Original JST implementation) [copyright holder]
- Jose Bernardo (Original JST implementation) [copyright holder]
- David Robinson <admiral.david@gmail.com> (Implementation of `reorder_within()`) [copyright holder]
- Julia Silge <julia.silge@gmail.com> ([ORCID](#)) (Implementation of `reorder_within()`) [copyright holder]

See Also

Useful links:

- <https://github.com/odelmarcelle/sentopics>
- Report bugs at <https://github.com/odelmarcelle/sentopics/issues>

 as.LDA

Conversions from other packages to LDA

Description

These functions converts estimated models from other topic modeling packages to the format used by **sentopics**.

Usage

```
as.LDA(x, ...)

## S3 method for class 'STM'
as.LDA(x, docs, ...)

## S3 method for class 'LDA_Gibbs'
as.LDA(x, docs, ...)

## S3 method for class 'LDA_VEM'
as.LDA(x, docs, ...)

## S3 method for class 'textmodel_lda'
as.LDA(x, ...)

as.LDA_lda(list, docs, alpha, eta)
```

Arguments

x	an estimated topic model from stm , topicmodels or seededlda .
...	arguments passed to other methods.
docs	for some objects, the documents used to initialize the model.
list	the list containing an estimated model from lda .
alpha	for lda models, the document-topic mixture hyperparameter. If missing, the hyperparameter will be set to 50/K.
eta	for lda models, the topic-word mixture hyperparameter. Other packages refer to this hyperparameter as <i>beta</i> . If missing, the hyperparameter will be set to 0.01.

Details

Some models do not store the topic assignment of each word (for example, estimated through variational inference). For these, the conversion is limited and some functionalities of **sentopics** will be disabled. The list of affected functions is subject to change and currently includes `grow()`, `mergeTopics()` and `rJST.LDA()`.

Since models from the **lda** package are simply lists of outputs, the function `as.LDA_lda()` is not related to the other methods and should be applied directly on lists containing a model.

Value

A S3 list of class LDA, as if it was created and estimated using `LDA()` and `grow()`.

Examples

```
## stm
library("stm")
stm <- stm(poliblog5k.docs, poliblog5k.voc, K=25,
           prevalence=~rating, data=poliblog5k.meta,
           max.em.its=2, init.type="Spectral")
as.LDA(stm, docs = poliblog5k.docs)

## lda
library("lda")
data("cora.documents")
data("cora.vocab")
lda <- lda.collapsed.gibbs.sampler(cora.documents,
                                   5, ## Num clusters
                                   cora.vocab,
                                   100, ## Num iterations
                                   0.1,
                                   0.1)
LDA <- as.LDA_lda(lda, cora.documents, alpha = .1, eta = .1)

## topicmodels
data("AssociatedPress", package = "topicmodels")
lda <- topicmodels::LDA(AssociatedPress[1:20,],
                       control = list(alpha = 0.1), k = 2)
LDA <- as.LDA(lda, AssociatedPress[1:20,])

## seededlda
library("seededlda")
lda <- textmodel_lda(dfm(ECB_press_conferences_tokens),
                    k = 6, max_iter = 100)
LDA <- as.LDA(lda)
```

as.tokens.dfm *Convert back a dfm to a tokens object*

Description

Convert back a dfm to a tokens object

Usage

```
## S3 method for class 'dfm'
as.tokens(
  x,
  concatenator = NULL,
  tokens = NULL,
  ignore_list = NULL,
  case_insensitive = FALSE,
  padding = TRUE,
  ...
)
```

Arguments

x	quanteda::dfm to be coerced
concatenator	only used for consistency with the generic
tokens	optionally, the tokens from which the dfm was created. Providing the initial tokens will ensure that the word order will be respected in the coerced object.
ignore_list	a character vector of words that should not be removed from the initial tokens object. Useful to avoid removing some lexicon word following the usage of quanteda::dfm_trim() .
case_insensitive	only used when the tokens argument is provided. Default to FALSE. This function removes words in the initial tokens based on the remaining features in the dfm object. This check is case-sensitive by default, and can be relaxed by setting this argument to TRUE.
padding	if TRUE, leaves an empty string where the removed tokens previously existed. The use of padding is encouraged to improve the behavior of the coherence metrics (see coherence()) that rely on word positions.
...	unused

Value

a [quanteda](#) [quanteda::tokens](#) object.

See Also

[quanteda::as.tokens\(\)](#) [quanteda::dfm\(\)](#)

Examples

```
library("quanteda")
dfm <- dfm(ECB_press_conferences_tokens, tolower = FALSE)
dfm <- dfm_trim(dfm, min_termfreq = 200)
as.tokens(dfm)
as.tokens(dfm, tokens = ECB_press_conferences_tokens)
as.tokens(dfm, tokens = ECB_press_conferences_tokens, padding = FALSE)
```

chainsDistances *Distances between topic models (chains)*

Description

Computes the distance between different estimates of a topic model. Since the estimation of a topic model is random, the results may largely differ as the process is repeated. This function allows to compute the distance between distinct realizations of the estimation process. Estimates are referred to as *chains*.

Usage

```
chainsDistances(
  x,
  method = c("euclidean", "hellinger", "cosine", "minMax", "naiveEuclidean",
             "invariantEuclidean"),
  ...
)
```

Arguments

x	a valid multiChains object, obtained through the estimation of a topic model using <code>grow()</code> and the argument <code>nChains</code> greater than 1.
method	the method used to measure the distance between chains.
...	further arguments passed to internal distance functions.

Details

The method argument determines how are computed distance.

- `euclidean` finds the pairs of topics that minimizes and returns the total Euclidean distance.
- `hellinger` does the same but based on the Hellinger distance.
- `cosine` does the same but based on the Cosine distance.
- `minMax` computes the maximum distance among the best pairs of distances. Inspired by the *minimum-matching distance* from Tang et al. (2014).
- `naiveEuclidean` computes the Euclidean distance without searching for the best pairs of topics.

- `invariantEuclidean` computes the best pairs of topics for all allowed permutations of topic indices. For JST and reversed-JST models, the two-levels hierarchy of document-sentiment-topic leads some permutations of indices to represent a drastically different outcome. This setting restricts the set of permutations to the ones that do not change the interpretation of the model. Equivalent to `euclidean` for LDA models.

Value

A matrix of distance between the elements of `x`

Author(s)

Olivier Delmarcelle

References

Tang, J., Meng, Z., Nguyen, X., Mei, Q., and Zhang, M. (2014). **Understanding the Limiting Factors of Topic Modeling via Posterior Contraction Analysis**. In *Proceedings of the 31st International Conference on Machine Learning*, 32, 90–198.

See Also

`plot.multiChains()` `chainsScores()`

Examples

```
model <- LDA(ECB_press_conferences_tokens)
model <- grow(model, 10, nChains = 5)
chainsDistances(model)
```

chainsScores

Compute scores of topic models (chains)

Description

Compute various scores (log likelihood, coherence) for a list of topic models.

Usage

```
chainsScores(x, window = 110, nWords = 10)
```


Arguments

x	a valid multiChains object, obtained through the estimation of a topic model using <code>grow()</code> and the argument <code>nChains</code> greater than 1.
window	optional. If NULL, use the default window for each coherence metric (10 for C_NPMI and 110 for C_V). It is possible to override these default windows by providing an integer or "boolean" to this argument, determining a new window size for all measures.
nWords	the number of words used to compute coherence. See <code>coherence()</code> .

Value

A data.table with some statistics about each chain. For the coherence metrics, the value shown is the mean coherence across all topics of a chain

Parallelism

When `nChains > 1`, the function can take advantage of `future.apply::future_lapply` (if installed) to spread the computation over multiple processes. This requires the specification of a parallel strategy using `future::plan()`. See the examples below.

See Also

`chainsDistances()` `coherence()`

Examples

```
model <- LDA(ECB_press_conferences_tokens[1:10])
model <- grow(model, 10, nChains = 5)
chainsScores(model, window = 5)
chainsScores(model, window = "boolean")

# -- Parallel computation --
require(future.apply)
future::plan("multisession", workers = 2) # Set up 2 workers
chainsScores(model, window = "boolean")

future::plan("sequential") # Shut down workers
```

coherence

Coherence of estimated topics

Description

Computes various coherence based metrics for topic models. It assesses the quality of estimated topics based on co-occurrences of words. For best results, consider cleaning the initial tokens object with `padding = TRUE`.

Usage

```
coherence(  
  x,  
  nWords = 10,  
  method = c("C_NPMI", "C_V"),  
  window = NULL,  
  NPMIs = NULL  
)
```

Arguments

x	a model created from the <code>LDA()</code> , <code>JST()</code> or <code>rJST()</code> function and estimated with <code>grow()</code>
nWords	the number of words in each topic used for evaluation.
method	the coherence method used.
window	optional. If NULL, use the default window for each coherence metric (10 for C_NPMI and 110 for C_V). It is possible to override these default windows by providing an integer or "boolean" to this argument, determining a new window size for all measures. No effect is the NPMIs argument is also provided.
NPMIs	optional NPMI matrix. If provided, skip the computation of NPMI between words, substantially decreasing computing time.

Details

Currently, only C_NPMI and C_V are documented. The implementation follows Röder & al. (2015). For C_NPMI, the sliding window is 10 whereas it is 110 for C_V.

Value

A vector or matrix containing the coherence score of each topic.

Author(s)

Olivier Delmarcelle

References

Röder, M., Both, A., & Hinneburg, A. (2015). *Exploring the Space of Topic Coherence Measures*. In *Proceedings of the Eighth ACM International Conference on Web Search and Data Mining*, 399-408.

`compute_PicaultRenault_scores`*Compute scores using the Picault-Renault lexicon*

Description

Computes Monetary Policy and Economic Condition scores using the Picault-Renault lexicon for central bank communication.

Usage

```
compute_PicaultRenault_scores(x, min_ngram = 2, return_dfm = FALSE)
```

Arguments

<code>x</code>	a <code>quanteda::corpus</code> object.
<code>min_ngram</code>	the minimum length of n-grams considered in the computation
<code>return_dfm</code>	if TRUE, returns the scaled word-per-document score under two <code>dfm</code> , one for the Monetary Policy and one for the Economic Condition categories. If FALSE, returns the sum of all word scores per document.

Details

The computation is done on a per-document basis, such as each document is scored with a value between -1 and 1. This is relevant to the computation of the denominator of the score.

It is possible to compute the score for paragraphs and sentences for a `quanteda::corpus` segmented using `quanteda::corpus_reshape`. Segmenting a corpus using `quanteda`'s helpers retain track to which document each paragraph/sentence belong. However, in that case, it is possible that paragraphs or sentences are scored outside the (-1,1) interval. In any case, the of the paragraph/sentences scores averaged over documents will be contained in the (-1,1) interval.

Value

A matrix with two columns, indicating respectively the MP (Monetary Policy) and EC (Economic Condition) scores of each document.

References

Picault, M. & Renault, T. (2017). **Words are not all created equal: A new measure of ECB communication**. *Journal of International Money and Finance*, 79, 136–156.

See Also

[PicaultRenault](#)

Examples

```
# on documents
docs <- quanteda::corpus_reshape(ECB_press_conferences, "documents")
compute_PicaultRenault_scores(docs)

# on paragraphs
compute_PicaultRenault_scores(ECB_press_conferences)
```

ECB_press_conferences *Corpus of press conferences from the European Central Bank*

Description

A corpus of 260 ECB press conference, split into 4224 paragraphs. The corpus contains a number of *docvars* indicating the date of the press conference and a measured sentiment based on the Loughran-McDonald lexicon.

Usage

```
ECB_press_conferences
```

Format

A `quanteda::corpus` object.

Source

<https://www.ecb.europa.eu/press/key/date/html/index.en.html>.

See Also

[ECB_press_conferences_tokens](#)

Examples

```
docvars(ECB_press_conferences)
```

ECB_press_conferences_tokens
Tokenized press conferences

Description

The pre-processed and tokenized version of the [ECB_press_conferences](#) corpus of press conferences. The processing involved the following steps:

- Subset paragraphs shorter than 10 words
- Removal of stop words
- Part-of-speech tagging, following which only nouns, proper nouns and adjective were retained.
- Detection and merging of frequent compound words
- Frequency-based cleaning of rare and very common words

Usage

ECB_press_conferences_tokens

Format

A `quanteda::tokens` object.

Source

<https://www.ecb.europa.eu/press/key/date/html/index.en.html>.

See Also

[ECB_press_conferences](#)

Examples

```
LDA(ECB_press_conferences_tokens)
```

`get_ECB_press_conferences`*Download press conferences from the European Central Bank*

Description

This helper function automatically retrieve the full data set of press conferences made available by the ECB. It implements a number of pre-processing steps used to remove the Q&A section from the text.

Usage

```
get_ECB_press_conferences(  
  years = 1998:2021,  
  language = "en",  
  data.table = TRUE  
)
```

Arguments

<code>years</code>	the years for which press conferences should be retrieved
<code>language</code>	the language in which press conferences should be retrieved
<code>data.table</code>	if TRUE, returns a data.table . Otherwise, return a list in which each element is a press conference.

Value

Depending on the arguments, returns either a `data.frame` or a [quanteda::tokens](#) object containing press conferences of the ECB.

`get_ECB_speeches`*Download and pre-process speeches from the European Central Bank*

Description

This helper function automatically retrieve the full data set of speeches made available by the ECB. In addition, it implements a number of pre-processing steps that may be turned on or off as needed.

Usage

```
get_ECB_speeches(  
  filter_english = TRUE,  
  clean_footnotes = TRUE,  
  compute_sentiment = TRUE,  
  tokenize_w_POS = FALSE  
)
```

Arguments

- `filter_english` if TRUE, attempts to select English speeches only using `textcat::textcat()`.
- `clean_footnotes`
if TRUE, attempts to clean footnotes from speeches texts using some regex patterns.
- `compute_sentiment`
if TRUE, computes the sentiment of each speech using `sentometrics::compute_sentiment()` with the the Loughran & McDonald lexicon.
- `tokenize_w_POS` if TRUE, tokenizes and apply Part-Of-Speech tagging with `spacyr::spacy_parse()`. Nouns, adjectives and proper nouns are then extracted from the parsed speeches to form a tokens object.

Value

Depending on the arguments, returns either a data.frame or a `quanteda::tokens` object containing speeches of the ECB.

<code>grow</code>	<i>Estimate a topic model</i>
-------------------	-------------------------------

Description

This function is used to estimate a topic model created by `LDA()`, `JST()` or `rJST()`. In essence, this function iterates a Gibbs sampler MCMC.

Usage

```
grow(
  x,
  iterations = 100,
  nChains = 1,
  displayProgress = TRUE,
  computeLikelihood = TRUE,
  seed = NULL
)
```

Arguments

- `x` a model created with the `LDA()`, `JST()` or `rJST()` function.
- `iterations` the number of iterations by which the model should be grown.
- `nChains` if set above 1, the model will be grown into multiple chains. from various starting positions. Latent variables will be re-initialized if `x` has not been grown before.
- `displayProgress`
if TRUE, a progress bar will be displayed indicating the progress of the computation. When `nChains` is greater than 1, this requires the package **progressr** and optionally **progress**.

`computeLikelihood` if set to FALSE, does not compute the likelihood at each iteration. This can slightly decrease the computing time.

`seed` for reproducibility, a seed can be provided.

Value

a `sentopicmodel` of the relevant model class if `nChains` is unspecified or equal to 1. A `multiChains` object if `nChains` is greater than 1.

Parallelism

When `nChains > 1`, the function can take advantage of `future.apply::future_lapply` (if installed) to spread the computation over multiple processes. This requires the specification of a parallel strategy using `future::plan()`. See the examples below.

See Also

[LDA\(\)](#), [JST\(\)](#), [rJST\(\)](#), [reset\(\)](#)

Examples

```
model <- rJST(ECB_press_conferences_tokens)
grow(model, 10)

# -- Parallel computation --
require(future.apply)
future::plan("multisession", workers = 2) # Set up 2 workers
grow(model, 10, nChains = 2)

future::plan("sequential") # Shut down workers
```

JST

Create a Joint Sentiment/Topic model

Description

This function initialize a Joint Sentiment/Topic model.

Usage

```
JST(
  x,
  lexicon = NULL,
  S = 3,
  K = 5,
  gamma = 1,
  alpha = 5,
```



```

    beta = 0.01,
    gammaCycle = 0,
    alphaCycle = 0
  )

```

Arguments

x	tokens object containing the texts. A coercion will be attempted if x is not a tokens.
lexicon	a quanteda dictionary with positive and negative categories
S	the number of sentiments
K	the number of topics
gamma	the hyperparameter of sentiment-document distribution
alpha	the hyperparameter of topic-document distribution
beta	the hyperparameter of vocabulary distribution
gammaCycle	integer specifying the cycle size between two updates of the hyperparameter alpha
alphaCycle	integer specifying the cycle size between two updates of the hyperparameter alpha

Details

The `rJST.LDA` methods enable the transition from a previously estimated [LDA](#) model to a sentiment-aware `rJST` model. The function retains the previously estimated topics and randomly assigns sentiment to every word of the corpus. The new model will retain the iteration count of the initial [LDA](#) model.

Value

An S3 list containing the model parameter and the estimated mixture. This object corresponds to a Gibbs sampler estimator with zero iterations. The MCMC can be iterated using the [grow\(\)](#) function.

- `tokens` is the tokens object used to create the model
- `vocabulary` contains the set of words of the corpus
- it tracks the number of Gibbs sampling iterations
- `za` is the list of topic assignment, aligned to the `tokens` object with padding removed
- `logLikelihood` returns the measured log-likelihood at each iteration, with a breakdown of the likelihood into hierarchical components as attribute

The [topWords\(\)](#) function easily extract the most probables words of each topic/sentiment.

Author(s)

Olivier Delmarcelle

References

- Lin, C. and He, Y. (2009). **Joint sentiment/topic model for sentiment analysis**. In *Proceedings of the 18th ACM conference on Information and knowledge management*, 375–384.
- Lin, C., He, Y., Everson, R. and Ruger, S. (2012). **Weakly Supervised Joint Sentiment-Topic Detection from Text**. *IEEE Transactions on Knowledge and Data Engineering*, 24(6), 1134—1145.

See Also

Growing a model: [grow\(\)](#), extracting top words: [topWords\(\)](#)
Other topic models: [LDA\(\)](#), [rJST\(\)](#), [sentopicmodel\(\)](#)

Examples

```
# creating a JST model
JST(ECB_press_conferences_tokens)

# estimating a JST model including a lexicon
jst <- JST(ECB_press_conferences_tokens, lexicon = LoughranMcDonald)
jst <- grow(jst, 100)
```

LDA

Create a Latent Dirichlet Allocation model

Description

This function initialize a Latent Dirichlet Allocation model.

Usage

```
LDA(x, K = 5, alpha = 1, beta = 0.01)
```

Arguments

x	tokens object containing the texts. A coercion will be attempted if x is not a tokens.
K	the number of topics
alpha	the hyperparameter of topic-document distribution
beta	the hyperparameter of vocabulary distribution

Details

The `rJST.LDA` methods enable the transition from a previously estimated [LDA](#) model to a sentiment-aware `rJST` model. The function retains the previously estimated topics and randomly assigns sentiment to every word of the corpus. The new model will retain the iteration count of the initial [LDA](#) model.

Value

An S3 list containing the model parameter and the estimated mixture. This object corresponds to a Gibbs sampler estimator with zero iterations. The MCMC can be iterated using the `grow()` function.

- `tokens` is the tokens object used to create the model
- `vocabulary` contains the set of words of the corpus
- it tracks the number of Gibbs sampling iterations
- `za` is the list of topic assignment, aligned to the tokens object with padding removed
- `logLikelihood` returns the measured log-likelihood at each iteration, with a breakdown of the likelihood into hierarchical components as attribute

The `topWords()` function easily extract the most probables words of each topic/sentiment.

Author(s)

Olivier Delmarcelle

References

Blei, D.M., Ng, A.Y. and Jordan, M.I. (2003). *Latent Dirichlet Allocation*. *Journal of Machine Learning Research*, 3, 993–1022.

See Also

Growing a model: `grow()`, extracting top words: `topWords()`

Other topic models: `JST()`, `rJST()`, `sentopicmodel()`

Examples

```
# creating a model
LDA(ECB_press_conferences_tokens, K = 5, alpha = 0.1, beta = 0.01)

# estimating an LDA model
lda <- LDA(ECB_press_conferences_tokens)
lda <- grow(lda, 100)
```

LDAvis

Visualize a LDA model using LDAvis

Description

This function call **LDAvis** to create a dynamic visualization of an estimated topic model.

Usage

```
LDAvis(x, ...)
```

Arguments

`x` an LDA model
`...` further arguments passed on to `LDavis::createJSON()` and `LDavis::serVis()`.

Details

The CRAN release of **LDavis** does not support UTF-8 characters and automatically reorder topics. To solve these two issues, please install the development version of **LDavis** from github (`devtools::install_github("cpsievert/LDavis")`).

Value

Nothing, called for its side effects.

See Also

[plot.sentopicmodel\(\)](#)

Examples

```
lda <- LDA(ECB_press_conferences_tokens)
lda <- grow(lda, 100)
LDavis(lda)
```

LoughranMcDonald

Loughran-McDonald lexicon

Description

The Loughran-McDonald lexicon for financial texts adapted for usage in **sentopics**. The lexicon is enhanced with two list of valence-shifting words.

Usage

```
LoughranMcDonald
```

Format

A `quanteda::dictionary` containing two polarity categories (negative and positive) and two valence-shifting categories (negator and amplifier).

Source

<https://sraf.nd.edu/loughranmcdonald-master-dictionary/> for the lexicon and `lexicon::hash_valence_shifters` for the valence shifters.

References

Loughran, T. & McDonald, B. (2011). *When Is a Liability Not a Liability? Textual Analysis, Dictionaries, and 10-Ks*. *The Journal of Finance*, 66(1), 35–65.

See Also

[JST\(\)](#), [rJST\(\)](#)

Examples

```
JST(ECB_press_conferences_tokens, lexicon = LoughranMcDonald)
```

melt

Replacement generic for [data.table::melt\(\)](#)

Description

Up to the CRAN release of the 1.14.3 version of **data.table**, the [data.table::melt\(\)](#) function is not a generic. This function aims to temporarily provide a generic to this function, so that [melt.sentopicmodel\(\)](#) can be effectively dispatched when used. Expect this function to disappear shortly after the release of **data.table** 1.14.3.

Usage

```
melt(data, ...)
```

Arguments

data	an object to melt
...	arguments passed to other methods

Value

An unkeyed `data.table` containing the molten data.

See Also

[data.table::melt\(\)](#), [melt.sentopicmodel\(\)](#)

melt.sentopicmodel *Melt for sentopicmodels*

Description

This function extracts the estimated document mixtures from a topic model and returns them in a long [data.table](#) format.

Usage

```
## S3 method for class 'sentopicmodel'  
melt(data, ..., include_docvars = FALSE)
```

Arguments

data	a model created from the LDA() , JST() or rJST() function and estimated with grow()
...	not used
include_docvars	if TRUE, the melted result will also include the <i>docvars</i> stored in the tokens object provided at model initialization

Value

A [data.table](#) in the long format, where each line is the estimated proportion of a single topic/sentiment for a document. For JST and rJST models, the probability is also decomposed into 'L1' and 'L2' layers, representing the probability at each layer of the topic-sentiment hierarchy.

Author(s)

Olivier Delmarcelle

See Also

[topWords\(\)](#) for extracting representative words, [data.table::melt\(\)](#) and [data.table::dcast\(\)](#)

Examples

```
# only returns topic proportion for LDA models  
lda <- LDA(ECB_press_conferences_tokens)  
lda <- grow(lda, 10)  
melt(lda)  
  
# includes sentiment for JST and rJST models  
jst <- JST(ECB_press_conferences_tokens)  
jst <- grow(jst, 10)  
melt(jst)
```

`mergeTopics`*Merge topics into fewer themes*

Description

This operation is especially useful for the analysis of the model's output, by grouping together topics that share a common theme.

Usage

```
mergeTopics(x, merging_list)
```

Arguments

<code>x</code>	a <code>LDA()</code> or <code>rJST()</code> model.
<code>merging_list</code>	a list where each element is an integer vector containing the indices of topics to be merged. If named, the list's names become the label of the aggregated themes.

Details

Topics are aggregated at the word assignment level. New document-topic and topic-word probabilities are derived from the aggregated assignments.

Note that the output of this function does not constitute an estimated topic model, but merely an aggregation to ease the analysis. It is not advised to use `grow()` on the merged topic model as it will radically affect the content and proportions of the new themes.

Value

A `LDA()` or `rJST()` model with the merged topics.

See Also

`sentopics_labels`

Examples

```
lda <- LDA(ECB_press_conferences_tokens, K = 5)
lda <- grow(lda, 100)
merging_list <- list(
  c(1,5),
  2:4
)
mergeTopics(lda, merging_list)

# also possible with a named list
merging_list2 <- list(
  mytheme_1 = c(1,5),
```

```
mytheme_2 = 2:4
)
merged <- mergeTopics(lda, merging_list2)
sentopics_labels(merged)

# implemented for rJST
rjst <- rJST(ECB_press_conferences_tokens, lexicon = LoughranMcDonald)
rjst <- grow(rjst, 100)
mergeTopics(rjst, merging_list2)
```

PicaultRenault

Picault-Renault lexicon

Description

The Picault-Renault lexicon, specialized in the analysis of central bank communication. The lexicon identifies a large number of n-grams and gives their probability to belong to six categories:

- Monetary Policy - accommodative
- Monetary Policy - neutral
- Monetary Policy - restrictive
- Economic Condition - negative
- Economic Condition - neutral
- Economic Condition - positive

Usage

```
PicaultRenault
```

Format

A [data.table](#) object.

Source

<http://www.cbcomindex.com/lexicon.php>

References

Picault, M. & Renault, T. (2017). **Words are not all created equal: A new measure of ECB communication**. *Journal of International Money and Finance*, 79, 136–156.

See Also

[compute_PicaultRenault_scores\(\)](#)

Examples

```
head(PicaultRenault)
```

PicaultRenault_data *Regression dataset based on Picault & Renault (2017)*

Description

A regression dataset built to partially replicate the result of Picault & Renault. This dataset contains, for each press conference published after 2000:

- The Main Refinancing Rate (MRR) of the ECB set following the press conference
- The change in the MRR following the press conference
- The change in the MRR observed at the previous press conference
- The Bloomberg consensus on the announced MRR
- The Surprise brought by the announcement, computed as the Bloomberg consensus minus the MRR following the conference
- The EURO STOXX 50 return on the day of the press conference
- The EURO STOXX 50 return on the day preceding the announcement

Usage

```
PicaultRenault_data
```

Format

An `xts::xts` object.

Source

The data was manually prepared by the author of this package.

References

Picault, M. & Renault, T. (2017). **Words are not all created equal: A new measure of ECB communication**. *Journal of International Money and Finance*, 79, 136–156.

Examples

```
head(PicaultRenault_data)
```

plot.multiChains *Plot the distances between topic models (chains)*

Description

Plot the results of `chainsDistance(x)` using multidimensional scaling. See `chainsDistances()` for details on the distance computation and `stats::cmdscale()` for the implementation of the multidimensional scaling.

Usage

```
## S3 method for class 'multiChains'
plot(
  x,
  ...,
  method = c("euclidean", "hellinger", "cosine", "minMax", "naiveEuclidean",
             "invariantEuclidean")
)
```

Arguments

<code>x</code>	a valid <code>multiChains</code> object, obtained through the estimation of a topic model using <code>grow()</code> and the argument <code>nChains</code> greater than 1.
<code>...</code>	not used
<code>method</code>	the method used to measure the distance between chains.

Value

Invisibly, the coordinates of each topic model resulting from the multidimensional scaling.

See Also

`chainsDistances()` `cmdscale()`

Examples

```
models <- LDA(ECB_press_conferences_tokens)
models <- grow(models, 10, nChains = 5)
plot(models)
```

plot.sentopicmodel *Plot a topic model using Plotly*

Description

Summarize and plot a **sentopics** model using a sunburst chart from the [plotly::plotly](#) library.

Usage

```
## S3 method for class 'sentopicmodel'  
plot(x, nWords = 15, layers = 3, sort = FALSE, ...)
```

Arguments

x	a model created from the LDA() , JST() or rJST() function and estimated with grow()
nWords	the number of words per topic/sentiment to display in the outer layer of the plot
layers	specifies the number of layers for the sunburst chart. This will restrict the output to the layers uppermost levels of the chart. For example, setting layers = 1 will only display the top level of the hierarchy (topics for an LDA model).
sort	if TRUE, sorts the plotted topics in a decreasing frequency.
...	not used

Value

A plotly sunburst chart.

See Also

[topWords\(\)](#) [LDAvis\(\)](#)

Examples

```
lda <- LDA(ECB_press_conferences_tokens)  
lda <- grow(lda, 100)  
plot(lda, nWords = 5)  
  
# only displays the topic proportions  
plot(lda, layers = 1)
```

```
print.sentopicmodel Print method for sentopics models
```

Description

Print methods for **sentopics** models. Once per session (or forced by using `extended = TRUE`), it lists the most important function related to **sentopics** models.

Usage

```
## S3 method for class 'sentopicmodel'
print(x, extended = FALSE, ...)

## S3 method for class 'rJST'
print(x, extended = FALSE, ...)

## S3 method for class 'LDA'
print(x, extended = FALSE, ...)

## S3 method for class 'JST'
print(x, extended = FALSE, ...)
```

Arguments

<code>x</code>	the model to be printed
<code>extended</code>	if TRUE, extends the print to include some helpful related functions. Automatically displayed once per session.
<code>...</code>	not used

Value

No return value, called for side effects (printing).

```
proportion_topics Compute the topic or sentiment proportion time series
```

Description

Aggregate the topical or sentiment proportions at the document level into time series.

Usage

```

proportion_topics(
  x,
  period = c("year", "quarter", "month", "day", "identity"),
  rolling_window = 1,
  complete = TRUE,
  plot = c(FALSE, TRUE, "silent"),
  plot_ridgelines = TRUE,
  as.xts = TRUE,
  ...
)

plot_proportion_topics(
  x,
  period = c("year", "quarter", "month", "day"),
  rolling_window = 1,
  complete = TRUE,
  plot_ridgelines = TRUE,
  ...
)

```

Arguments

<code>x</code>	a <code>LDA()</code> , <code>JST()</code> or <code>rJST()</code> model populated with internal dates and/or internal sentiment.
<code>period</code>	the sampling period within which the sentiment of documents will be averaged. <code>period = "identity"</code> is a special case that will return document-level variables before the aggregation happens. Useful to rapidly compute topical sentiment at the document level.
<code>rolling_window</code>	if greater than 1, determines the rolling window to compute a moving average of sentiment. The rolling window is based on the period unit and rely on actual dates (i.e. is not affected by unequally spaced data points).
<code>complete</code>	if <code>FALSE</code> , only compute proportions at the upper level of the topic model hierarchy (topics for <code>rJST</code> and sentiment for <code>JST</code>). No effect on <code>LDA</code> models.
<code>plot</code>	if <code>TRUE</code> , prints a plot of the time series and attaches it as an attribute to the returned object. If <code>'silent'</code> , do not print the plot but still attaches it as an attribute.
<code>plot_ridgelines</code>	if <code>TRUE</code> , time series are plotted as ridgelines. Requires <code>ggridges</code> package installed. If <code>FALSE</code> , the plot will use only standards <code>ggplot2</code> functions. If the argument is missing and the package <code>ggridges</code> is not installed, this will quietly switch to a <code>ggplot2</code> output.
<code>as.xts</code>	if <code>TRUE</code> , returns an <code>xts::xts</code> object. Otherwise, returns a <code>data.frame</code> .
<code>...</code>	other arguments passed on to <code>zoo::rollapply()</code> or <code>mean()</code> and <code>sd()</code> .

Value

A time series of proportions, stored as an `xts::xts` object or as a `data.frame`.

See Also

`senttopics_sentiment` `senttopics_date`

Other series functions: `sentiment_breakdown()`, `sentiment_series()`, `sentiment_topics()`

Examples

```
lda <- LDA(ECB_press_conferences_tokens)
lda <- grow(lda, 100)
proportion_topics(lda)

# plot shortcut
plot_proportion_topics(lda, period = "month", rolling_window = 3)
# with or without ridgelines
plot_proportion_topics(lda, period = "month", plot_ridgelines = FALSE)

# also available for rJST and JST models
jst <- JST(ECB_press_conferences_tokens, lexicon = LoughranMcDonald)
jst <- grow(jst, 100)
# including both layers
proportion_topics(jst)
# or not
proportion_topics(jst, complete = FALSE)
```

reset

Re-initialize a topic model

Description

This function is used re-initialize a topic model, as if it was created from `LDA()`, `JST()` or another model. The re-initialized model retains its original parameter specification.

Usage

```
reset(x)
```

Arguments

`x` a model created from the `LDA()`, `JST()` or `rJST()` function and estimated with `grow()`

Value

a `sentopicmodel` of the relevant model class, with the iteration count reset to zero and re-initialized assignment of latent variables.

Author(s)

Olivier Delmarcelle

See Also[grow\(\)](#)**Examples**

```
model <- LDA(ECB_press_conferences_tokens)
model <- grow(model, 10)
reset(model)
```

rJST*Create a Reversed Joint Sentiment/Topic model*

Description

This function initialize a Reversed Joint Sentiment/Topic model.

Usage

```
rJST(x, ...)
```

```
## Default S3 method:
rJST(
  x,
  lexicon = NULL,
  K = 5,
  S = 3,
  alpha = 1,
  gamma = 5,
  beta = 0.01,
  alphaCycle = 0,
  gammaCycle = 0,
  ...
)
```

```
## S3 method for class 'LDA'
rJST(x, lexicon = NULL, S = 3, gamma = 5, ...)
```

Arguments

x	tokens object containing the texts. A coercion will be attempted if x is not a tokens.
...	not used
lexicon	a quanteda dictionary with positive and negative categories

K	the number of topics
S	the number of sentiments
alpha	the hyperparameter of topic-document distribution
gamma	the hyperparameter of sentiment-document distribution
beta	the hyperparameter of vocabulary distribution
alphaCycle	integer specifying the cycle size between two updates of the hyperparameter alpha
gammaCycle	integer specifying the cycle size between two updates of the hyperparameter alpha

Details

The `rJST.LDA` methods enable the transition from a previously estimated `LDA` model to a sentiment-aware `rJST` model. The function retains the previously estimated topics and randomly assigns sentiment to every word of the corpus. The new model will retain the iteration count of the initial `LDA` model.

Value

An S3 list containing the model parameter and the estimated mixture. This object corresponds to a Gibbs sampler estimator with zero iterations. The MCMC can be iterated using the `grow()` function.

- `tokens` is the tokens object used to create the model
- `vocabulary` contains the set of words of the corpus
- `it` tracks the number of Gibbs sampling iterations
- `za` is the list of topic assignment, aligned to the `tokens` object with padding removed
- `logLikelihood` returns the measured log-likelihood at each iteration, with a breakdown of the likelihood into hierarchical components as attribute

The `topWords()` function easily extract the most probables words of each topic/sentiment.

Author(s)

Olivier Delmarcelle

References

- Lin, C. and He, Y. (2009). **Joint sentiment/topic model for sentiment analysis**. In *Proceedings of the 18th ACM conference on Information and knowledge management*, 375–384.
- Lin, C., He, Y., Everson, R. and Ruger, S. (2012). **Weakly Supervised Joint Sentiment-Topic Detection from Text**. *IEEE Transactions on Knowledge and Data Engineering*, 24(6), 1134—1145.

See Also

Growing a model: `grow()`, extracting top words: `topWords()`
 Other topic models: `JST()`, `LDA()`, `sentopicmodel()`

Examples

```
# simple rJST model
rJST(ECB_press_conferences_tokens)

# estimating a rJST model including lexicon
rjst <- rJST(ECB_press_conferences_tokens, lexicon = LoughranMcDonald)
rjst <- grow(rjst, 100)

# from an LDA model:
lda <- LDA(ECB_press_conferences_tokens)
lda <- grow(lda, 100)

# creating a rJST model out of it
rjst <- rJST(lda, lexicon = LoughranMcDonald)
# topic proportions remain identical
identical(lda$theta, rjst$theta)
# model should be iterated to estimate sentiment proportions
rjst <- grow(rjst, 100)
```

sentiment_breakdown *Breakdown the sentiment into topical components*

Description

Break down the sentiment series obtained with `sentiment_series()` into topical components. Sentiment is broken down at the document level using estimated topic proportions, then processed to create a time series and its components.

Usage

```
sentiment_breakdown(
  x,
  period = c("year", "quarter", "month", "day", "identity"),
  rolling_window = 1,
  scale = TRUE,
  scaling_period = c("1900-01-01", "2099-12-31"),
  plot = c(FALSE, TRUE, "silent"),
  as.xts = TRUE,
  ...
)

plot_sentiment_breakdown(
  x,
  period = c("year", "quarter", "month", "day"),
  rolling_window = 1,
  scale = TRUE,
  scaling_period = c("1900-01-01", "2099-12-31"),
  ...
)
```

Arguments

<code>x</code>	a <code>LDA()</code> or <code>rJST()</code> model populated with internal dates and/or internal sentiment.
<code>period</code>	the sampling period within which the sentiment of documents will be averaged. <code>period = "identity"</code> is a special case that will return document-level variables before the aggregation happens. Useful to rapidly compute topical sentiment at the document level.
<code>rolling_window</code>	if greater than 1, determines the rolling window to compute a moving average of sentiment. The rolling window is based on the period unit and rely on actual dates (i.e, is not affected by unequally spaced data points).
<code>scale</code>	if TRUE, the resulting time series will be scaled to a mean of zero and a standard deviation of 1. This argument also has the side effect of attaching scaled sentiment values as <code>docvars</code> to the input object with the <code>_scaled</code> suffix.
<code>scaling_period</code>	the date range over which the scaling should be applied. Particularly useful to normalize only the beginning of the time series.
<code>plot</code>	if TRUE, prints a plot of the time series and attaches it as an attribute to the returned object. If 'silent', do not print the plot but still attaches it as an attribute.
<code>as.xts</code>	if TRUE, returns an <code>xts::xts</code> object. Otherwise, returns a <code>data.frame</code> .
<code>...</code>	other arguments passed on to <code>zoo::rollapply()</code> or <code>mean()</code> and <code>sd()</code> .

Details

The sentiment is broken down at the sentiment level assuming the following composition:

$$s = \sum_{i=1}^K s_i \times \theta_i$$

, where s_i is the sentiment of topic i and θ_i the proportion of topic i in a given document. For an LDA model, the sentiment of each topic is considered equal to the document sentiment (i.e. $s_i = s \forall i \in K$). The topical sentiment attention, defined by $s*_i = s_i \times \theta_i$ represent the effective sentiment conveyed by a topic in a document. The topical sentiment attention of all documents in a period are averaged to compute the breakdown of the sentiment time series.

Value

A time series of sentiment, stored as an `xts::xts` object or as a `data.frame`.

See Also

`senttopics_sentiment` `senttopics_date`

Other series functions: `proportion_topics()`, `sentiment_series()`, `sentiment_topics()`

Examples

```
lda <- LDA(ECB_press_conferences_tokens)
lda <- grow(lda, 100)
sentiment_breakdown(lda)

# plot shortcut
plot_sentiment_breakdown(lda)

# also available for rJST models (with topic-level sentiment)
rjst <- rJST(ECB_press_conferences_tokens, lexicon = LoughranMcDonald)
rjst <- grow(rjst, 100)
sentopics_sentiment(rjst, override = TRUE)
plot_sentiment_breakdown(rjst)
```

sentiment_series	<i>Compute a sentiment time series</i>
------------------	--

Description

Compute a sentiment time series based on the internal sentiment and dates of a sentopicmodel. The time series computation supports multiple sampling period and optionally allow computing a moving average.

Usage

```
sentiment_series(
  x,
  period = c("year", "quarter", "month", "day"),
  rolling_window = 1,
  scale = TRUE,
  scaling_period = c("1900-01-01", "2099-12-31"),
  as.xts = TRUE,
  ...
)
```

Arguments

x	a <code>LDA()</code> , <code>JST()</code> or <code>rJST()</code> model populated with internal dates and/or internal sentiment.
period	the sampling period within which the sentiment of documents will be averaged. <code>period = "identity"</code> is a special case that will return document-level variables before the aggregation happens. Useful to rapidly compute topical sentiment at the document level.
rolling_window	if greater than 1, determines the rolling window to compute a moving average of sentiment. The rolling window is based on the period unit and rely on actual dates (i.e, is not affected by unequally spaced data points).

scale	if TRUE, the resulting time series will be scaled to a mean of zero and a standard deviation of 1. This argument also has the side effect of attaching scaled sentiment values as <i>docvars</i> to the input object with the <code>_scaled</code> suffix.
scaling_period	the date range over which the scaling should be applied. Particularly useful to normalize only the beginning of the time series.
as.xts	if TRUE, returns an <code>xts::xts</code> object. Otherwise, returns a <code>data.frame</code> .
...	other arguments passed on to <code>zoo::rollapply()</code> or <code>mean()</code> and <code>sd()</code> .

Value

A time series of sentiment, stored as an `xts::xts` or `data.frame`.

See Also

`sentopics_sentiment` `sentopics_date`

Other series functions: `proportion_topics()`, `sentiment_breakdown()`, `sentiment_topics()`

Examples

```
lda <- LDA(ECB_press_conferences_tokens)
series <- sentiment_series(lda, period = "month")

# JST and rJST models can use computed sentiment from the sentiment layer,
# but the model must be estimated first.
rjst <- rJST(ECB_press_conferences_tokens, lexicon = LoughranMcDonald)
sentiment_series(rjst)

sentopics_sentiment(rjst) <- NULL ## remove existing sentiment
rjst <- grow(rjst, 10) ## estimating the model is then needed
sentiment_series(rjst)

# note the presence of both raw and scaled sentiment values
# in the initial object
sentopics_sentiment(lda)
sentopics_sentiment(rjst)
```

sentiment_topics *Compute time series of topical sentiments*

Description

Derive topical time series of sentiment from a `LDA()` or `rJST()` model. The time series are created by leveraging on estimated topic proportions and internal sentiment (for LDA models) or topical sentiment (for rJST models).

Usage

```

sentiment_topics(
  x,
  period = c("year", "quarter", "month", "day", "identity"),
  rolling_window = 1,
  scale = TRUE,
  scaling_period = c("1900-01-01", "2099-12-31"),
  plot = c(FALSE, TRUE, "silent"),
  plot_ridgelines = TRUE,
  as.xts = TRUE,
  ...
)

plot_sentiment_topics(
  x,
  period = c("year", "quarter", "month", "day"),
  rolling_window = 1,
  scale = TRUE,
  scaling_period = c("1900-01-01", "2099-12-31"),
  plot_ridgelines = TRUE,
  ...
)

```

Arguments

<code>x</code>	a <code>LDA()</code> or <code>rJST()</code> model populated with internal dates and/or internal sentiment.
<code>period</code>	the sampling period within which the sentiment of documents will be averaged. <code>period = "identity"</code> is a special case that will return document-level variables before the aggregation happens. Useful to rapidly compute topical sentiment at the document level.
<code>rolling_window</code>	if greater than 1, determines the rolling window to compute a moving average of sentiment. The rolling window is based on the period unit and rely on actual dates (i.e, is not affected by unequally spaced data points).
<code>scale</code>	if TRUE, the resulting time series will be scaled to a mean of zero and a standard deviation of 1. This argument also has the side effect of attaching scaled sentiment values as <code>docvars</code> to the input object with the <code>_scaled</code> suffix.
<code>scaling_period</code>	the date range over which the scaling should be applied. Particularly useful to normalize only the beginning of the time series.
<code>plot</code>	if TRUE, prints a plot of the time series and attaches it as an attribute to the returned object. If 'silent', do not print the plot but still attaches it as an attribute.
<code>plot_ridgelines</code>	if TRUE, time series are plotted as ridgelines. Requires <code>ggridges</code> package installed. If FALSE, the plot will use only standards <code>ggplot2</code> functions. If the argument is missing and the package <code>ggridges</code> is not installed, this will quietly switch to a <code>ggplot2</code> output.

`as.xts` if TRUE, returns an `xts::xts` object. Otherwise, returns a `data.frame`.
 ... other arguments passed on to `zoo::rollapply()` or `mean()` and `sd()`.

Details

A topical sentiment is computed at the document level for each topic. For an LDA model, the sentiment of each topic is considered equal to the document sentiment (i.e. $s_i = s \forall i \in K$). For a rJST model, these result from the proportions in the sentiment layer under each topic. To compute the topical time series, the topical sentiment of all documents in a period are aggregated according to their respective topic proportion. For example, for a given topic, the topical sentiment in period t is computed using:

$$s_t = \frac{\sum_{d=1}^D s_d \times \theta_d}{\sum_{d=1}^D \theta_d}$$

, where s_d is the sentiment of the topic in document d and θ_d the topic proportion in a document d .

Value

an `xts::xts` or `data.frame` containing the time series of topical sentiments.

See Also

`senttopics_sentiment` `senttopics_date`

Other series functions: `proportion_topics()`, `sentiment_breakdown()`, `sentiment_series()`

Examples

```
lda <- LDA(ECB_press_conferences_tokens)
lda <- grow(lda, 100)
sentiment_topics(lda)

# plot shortcut
plot_sentiment_topics(lda, period = "month", rolling_window = 3)
# with or without ridgelines
plot_sentiment_topics(lda, period = "month", plot_ridgelines = FALSE)

# also available for rJST models with internal sentiment computation
rjst <- rJST(ECB_press_conferences_tokens, lexicon = LoughranMcDonald)
rjst <- grow(rjst, 100)
senttopics_sentiment(rjst, override = TRUE)
sentiment_topics(rjst)
```

sentopics_date	<i>Internal date</i>
----------------	----------------------

Description

Extract or replace the internal dates of a `sentopicmodel`. The internal dates are used to create time series using the functions `sentiment_series()` or `sentiment_topics()`. Dates should be provided by using `sentopics_date(x) <- value` or by storing a `'.date'` docvars in the `tokens` object used to create the model.

Usage

```
sentopics_date(x, include_docvars = FALSE)
```

```
sentopics_date(x) <- value
```

Arguments

<code>x</code>	a <code>sentopicmodel</code> created from the <code>LDA()</code> , <code>JST()</code> , <code>rJST()</code> or <code>sentopicmodel()</code> function
<code>include_docvars</code>	if TRUE the function will return all docvars stored in the internal <code>tokens</code> object of the model
<code>value</code>	a Date-coercible vector of dates to input into the model.

Value

a `data.frame` with the stored date per document.

Note

The internal date is stored internally in the `docvars` of the topic model. This means that dates may also be accessed through the `docvars()` function, although this is discouraged.

Author(s)

Olivier Delmarcelle

See Also

Other sentopics helpers: `sentopics_labels()`, `sentopics_sentiment()`

Examples

```
# example dataset already contains ".date" docvar
docvars(ECB_press_conferences_tokens)
# dates are automatically stored in the sentopicmodel object
lda <- LDA(ECB_press_conferences_tokens)
sentopics_date(lda)

# dates can be removed or modified by the assignment operator
sentopics_date(lda) <- NULL
sentopics_date(lda) <- docvars(ECB_press_conferences_tokens, ".date")
```

sentopics_labels *Setting topic or sentiment labels*

Description

Extract or replace the labels of a `sentopicmodel`. The replaced labels will appear in most functions dealing with the output of the `sentopicmodel`.

Usage

```
sentopics_labels(x, flat = TRUE)

sentopics_labels(x) <- value
```

Arguments

<code>x</code>	a <code>sentopicmodel</code> created from the <code>LDA()</code> , <code>JST()</code> , <code>rJST()</code> or <code>sentopicmodel()</code> function
<code>flat</code>	if <code>FALSE</code> , return a list of dimension labels instead of a character vector.
<code>value</code>	a list of future labels for the topic model. The list should be named and contain a character vector for each dimension to label. See the examples for a correct usage.

Value

a character vector of topic/sentiment labels.

Author(s)

Olivier Delmarcelle

See Also

`mergeTopics`

Other sentopics helpers: `sentopics_date()`, `sentopics_sentiment()`

Examples

```
# by default, sentopics_labels() generate standard topic names
lda <- LDA(ECB_press_conferences_tokens)
sentopics_labels(lda)

# to change labels, a named list must be provided
sentopics_labels(lda) <- list(
  topic = paste0("superTopic", 1:lda$K)
)
sentopics_labels(lda)

# using NULL remove labels
sentopics_labels(lda) <- NULL
sentopics_labels(lda)

# also works for JST/rJST models
jst <- JST(ECB_press_conferences_tokens)
sentopics_labels(jst) <- list(
  topic = paste0("superTopic", 1:jst$K),
  sentiment = c("negative", "neutral", "positive")
)
sentopics_labels(jst)

# setting flat = FALSE return a list or labels for each dimension
sentopics_labels(jst, flat = FALSE)
```

sentopics_sentiment *Internal sentiment*

Description

Compute, extract or replace the internal sentiment of a `sentopicmodel`. The internal sentiment is used to create time series using the functions `sentiment_series()` or `sentiment_topics()`. If the input model contains a sentiment layer, sentiment can be computed directly from the output of the model. Otherwise, sentiment obtained externally should be added for each document.

Usage

```
sentopics_sentiment(
  x,
  method = c("proportional", "proportionalPol"),
  override = FALSE,
  quiet = FALSE,
  include_docvars = FALSE
)

sentopics_sentiment(x) <- value
```

Arguments

x	a sentopicmodel created from the LDA() , JST() , rJST() or sentopicmodel() function
method	the method used to compute sentiment, see "Methods" below. Ignored if an internal sentiment is already stored, unless override is TRUE.
override	by default, the function computes sentiment only if no internal sentiment is already stored within the sentopicmodel object. This avoid, for example, erasing externally provided sentiment. Set to TRUE to force computation of new sentiment values. Only useful for models with a sentiment layer.
quiet	if FALSE, print a message when internal sentiment is found.
include_docvars	if TRUE the function will return all docvars stored in the internal tokens object of the model
value	a numeric vector of sentiment to input into the model.

Details

The computed sentiment varies depending on the model. For [LDA](#), sentiment computation is not possible.

For [JST](#), the sentiment is computed on a per-document basis according to the document-level sentiment mixtures.

For a [rJST](#) model, a sentiment is computed for each topic, resulting in K sentiment values per document. In that case, the `.sentiment` column is an average of the K sentiment values, weighted by they respective topical proportions.

Value

A data.frame with the stored sentiment per document.

Methods

The function accepts two methods of computing sentiment:

- **proportional** computes the difference between the estimated positive and negative proportions for each document (and possibly each topic).

$$positive - negative$$

- **proportionalPol** computes the difference between positive and negative proportions, divided by the sum of positive and negative proportions. As a result, the computed sentiment lies within the (-1;1) interval.

$$\frac{positive - negative}{positive + negative}$$

Both methods will lead to the same result for a JST model containing only negative and positive sentiments.

Note

The internal sentiment is stored internally in the *docvars* of the topic model. This means that sentiment may also be accessed through the `docvars()` function, although this is discouraged.

Author(s)

Olivier Delmarcelle

See Also

Other sentopics helpers: [sentopics_date\(\)](#), [sentopics_labels\(\)](#)

Examples

```
# example dataset already contains ".sentiment" docvar
docvars(ECB_press_conferences_tokens)
# sentiment is automatically stored in the sentopicmodel object
lda <- LDA(ECB_press_conferences_tokens)
sentopics_sentiment(lda)

# sentiment can be removed or modified by the assignment operator
sentopics_sentiment(lda) <- NULL
sentopics_sentiment(lda) <- docvars(ECB_press_conferences_tokens, ".sentiment")

# for JST models, sentiment can be computed from the output of the model
jst <- JST(ECB_press_conferences_tokens, lexicon = LoughranMcDonald)
jst <- grow(jst, 100)
sentopics_sentiment(jst, override = TRUE) # replace existing sentiment

## for rJST models one sentiment value is computed by topic
rjst <- rJST(ECB_press_conferences_tokens, lexicon = LoughranMcDonald)
rjst <- grow(rjst, 100)
sentopics_sentiment(rjst, override = TRUE)
```

topWords

Extract the most representative words from topics

Description

Extract the top words in each topic/sentiment from a `sentopicmodel`.

Usage

```
topWords(
  x,
  nWords = 10,
  method = c("frequency", "probability", "term-score", "FREQ"),
  output = c("data.frame", "plot", "matrix"),
  subset,
```

```

    w = 0.5
  )

plot_topWords(
  x,
  nWords = 10,
  method = c("frequency", "probability", "term-score", "FREX"),
  subset,
  w = 0.5
)

```

Arguments

x	a <code>sentopicmodel</code> created from the <code>LDA()</code> , <code>JST()</code> or <code>rJST()</code>
nWords	the number of top words to extract
method	specify if a re-ranking function should be applied before returning the top words
output	determines the output of the function
subset	allows to subset using a logical expression, as in <code>subset()</code> . Particularly useful to limit the number of observation on plot outputs. The logical expression uses topic and sentiment <i>indices</i> rather than their label. It is possible to subset on both topic and sentiment but adding a <code>&</code> operator between two expressions.
w	only used when <code>method = "FREX"</code> . Determines the weight assigned to the frequency score at the expense of the exclusivity score.

Value

The top words of the topic model. Depending on the output chosen, can result in either a long-style `data.frame`, a `ggplot2` object or a matrix.

Author(s)

Olivier Delmarcelle

See Also

`melt.sentopicmodel()` for extracting estimated mixtures

Examples

```

model <- LDA(ECB_press_conferences_tokens)
model <- grow(model, 10)
topWords(model)
topWords(model, output = "matrix")
topWords(model, method = "FREX")
plot_topWords(model)
plot_topWords(model, subset = topic %in% 1:2)

jst <- JST(ECB_press_conferences_tokens)
jst <- grow(jst, 10)

```

```
plot_topWords(jst)
plot_topWords(jst, subset = topic %in% 1:2 & sentiment == 3)
```

Index

- * **datasets**
 - ECB_press_conferences, [12](#)
 - ECB_press_conferences_tokens, [13](#)
 - LoughranMcDonald, [20](#)
 - PicaultRenault, [24](#)
 - PicaultRenault_data, [25](#)
- * **sentopics helpers**
 - sentopics_date, [39](#)
 - sentopics_labels, [40](#)
 - sentopics_sentiment, [41](#)
- * **series functions**
 - proportion_topics, [28](#)
 - sentiment_breakdown, [33](#)
 - sentiment_series, [35](#)
 - sentiment_topics, [36](#)
- * **topic models**
 - JST, [16](#)
 - LDA, [18](#)
 - rJST, [31](#)
- as.LDA, [4](#)
- as.LDA_lda(as.LDA), [4](#)
- as.tokens.dfm, [6](#)
- chainsDistances, [7](#)
- chainsDistances(), [9](#), [26](#)
- chainsScores, [8](#)
- chainsScores(), [8](#)
- cmdscale(), [26](#)
- coherence, [9](#)
- coherence(), [6](#), [9](#)
- compute_PicaultRenault_scores, [11](#)
- compute_PicaultRenault_scores(), [24](#)
- data.table, [14](#), [22](#), [24](#)
- data.table::dcast(), [22](#)
- data.table::melt(), [21](#), [22](#)
- dfm, [6](#), [11](#)
- docvars(), [39](#), [43](#)
- ECB_press_conferences, [12](#), [13](#)
- ECB_press_conferences_tokens, [12](#), [13](#)
- future.apply::future_lapply, [9](#), [16](#)
- future::plan(), [9](#), [16](#)
- get_ECB_press_conferences, [14](#)
- get_ECB_speeches, [14](#)
- grow, [15](#)
- grow(), [5](#), [7](#), [9](#), [10](#), [17–19](#), [22](#), [23](#), [26](#), [27](#), [30–32](#)
- JST, [16](#), [19](#), [29](#), [32](#), [42](#)
- JST(), [10](#), [15](#), [16](#), [21](#), [22](#), [27](#), [29](#), [30](#), [35](#), [39](#), [40](#), [42](#), [44](#)
- LDA, [17](#), [18](#), [18](#), [29](#), [32](#), [42](#)
- LDA(), [5](#), [10](#), [15](#), [16](#), [22](#), [23](#), [27](#), [29](#), [30](#), [34–37](#), [39](#), [40](#), [42](#), [44](#)
- LDAAvis, [19](#)
- LDAAvis(), [27](#)
- LDAAvis::createJSON(), [20](#)
- LDAAvis::serVis(), [20](#)
- lexicon::hash_valence_shifters, [20](#)
- LoughranMcDonald, [20](#)
- mean(), [29](#), [34](#), [36](#), [38](#)
- melt, [21](#)
- melt.sentopicmodel, [22](#)
- melt.sentopicmodel(), [21](#), [44](#)
- mergeTopics, [23](#)
- mergeTopics(), [5](#)
- PicaultRenault, [11](#), [24](#)
- PicaultRenault_data, [25](#)
- plot.multiChains, [26](#)
- plot.multiChains(), [8](#)
- plot.sentopicmodel, [27](#)
- plot.sentopicmodel(), [20](#)
- plot_proportion_topics
 - (proportion_topics), [28](#)

plot_sentiment_breakdown
 (sentiment_breakdown), 33
plot_sentiment_topics
 (sentiment_topics), 36
plot_topWords (topWords), 43
plotly::plotly, 27
print.JST (print.sentopicmodel), 28
print.LDA (print.sentopicmodel), 28
print.rJST (print.sentopicmodel), 28
print.sentopicmodel, 28
proportion_topics, 28, 34, 36, 38

quanteda::as.tokens(), 6
quanteda::corpus, 11, 12
quanteda::corpus_reshape, 11
quanteda::dfm, 6
quanteda::dfm(), 6
quanteda::dfm_trim(), 6
quanteda::dictionary, 20
quanteda::tokens, 6, 13–15

reset, 30
reset(), 16
rJST, 18, 19, 29, 31, 42
rJST(), 10, 15, 16, 21–23, 27, 29, 30, 34–37,
 39, 40, 42, 44
rJST.LDA(), 5

sd(), 29, 34, 36, 38
sentiment_breakdown, 30, 33, 36, 38
sentiment_series, 30, 34, 35, 38
sentiment_series(), 33, 39, 41
sentiment_topics, 30, 34, 36, 36
sentiment_topics(), 39, 41
sentometrics::compute_sentiment(), 15
sentopicmodel, 18, 19, 32
sentopicmodel(), 39, 40, 42
sentopics (sentopics-package), 3
sentopics-package, 3
sentopics_date, 39, 40, 43
sentopics_date<- (sentopics_date), 39
sentopics_labels, 39, 40, 43
sentopics_labels<- (sentopics_labels),
 40
sentopics_sentiment, 39, 40, 41
sentopics_sentiment<-
 (sentopics_sentiment), 41
spacyr::spacy_parse(), 15
stats::cmdscale(), 26

subset(), 44
textcat::textcat(), 15
tokens, 6, 22, 39
topWords, 43
topWords(), 17–19, 22, 27, 32

xts::xts, 25, 29, 30, 34, 36, 38

zoo::rollapply(), 29, 34, 36, 38